

98311

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/24060 A2

(51) International Patent Classification⁷: **G06F 17/30**

(21) International Application Number: **PCT/US00/26964**

(22) International Filing Date:
29 September 2000 (29.09.2000)

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
09/410,367 30 September 1999 (30.09.1999) **US**

(71) Applicant: **BATTELLE MEMORIAL INSTITUTE**
[US/US]; 505 King Avenue, Columbus, OH 43201-2693
(US).

(72) Inventors: **SAFFER, Jeffrey, D.**; 202 Hartwood Street,
Richland, WA 99352 (US). **CALAPRISTI, Augustin,**
J.; 3104 Mount Granite Court W., Richland, WA 99353
(US). **MILLER, Nancy, E.**; 4919 Brookburn Drive,
San Diego, CA 92130 (US). **SCARBERRY, Randall,**
E.; 2224 Benton Avenue, Richland, WA 99352 (US).
THURSTON, Sarah, J.; 221 Douglass Avenue, Richland,
WA 99352 (US). **HAVRE, Susan, L.**; 300 Rockwood
Drive, Richland, WA 99352 (US). **DECKER, Scott, D.**;
1309 Buena Court, Richland, WA 99352 (US). **PAYNE,**
Deborah, A.; 1968 Newhaven Loop, Richland, WA 99352
(US). **SOFIA, Heidi, J.**; 383 S. Palouse, Walla Walla, WA
99362 (US). **THOMAS, Gregory, S.**; 93006 East Reata
Road, Kennewick, WA 99338 (US). **CHEN, Guang;**
1329 Goethals Drive, Apt. 9, Richland, WA 99352 (US).
CROW, Vernon, L.; 415 South Grant, Kennewick, WA

99336 (US). **ALBRIGHT, Cory, L.**; 1110 McPherson,
Richland, WA 99352 (US). **ZABRISKI, Sean, J.**; 8943
W. Canyon Place, Richland, WA 99352 (US). **GROCH,**
Kevin, M.; 2433 George Washington Way, Suite 6105,
Richland, WA 99352 (US). **MALARD, Joel, M.**; 1312
RocheFontaine, Richland, WA 99352 (US). **NOWELL,**
Lucille, T.; 40 Edgewood Drive, Richland, WA 99352
(US).

(74) Agents: **GOLDSTEIN, Steven, J. et al.**; Frost & Jacobs
LLP, 2500 PNC Center, 201 East Fifth Street, Cincinnati,
OH 45202 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— Without international search report and to be republished
upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **DATA PROCESSING, ANALYSIS, AND VISUALIZATION SYSTEM FOR USE WITH DISPARATE DATA TYPES**

(57) Abstract: A system or method consistent with an embodiment of the present invention is useful in analyzing large volumes of different types of data, such as textual data, numeric data, categorical data, or sequential string data, for use in identifying relationships among the data types or different operations that have been performed on the data. A system or method consistent with the present invention determines and displays the relative content and context of related information and is operative to aid in identifying relationships among disparate data types. Various data types, such as numerical data, protein and DNA sequence data, categorical information, and textual information, such as annotations associated with the numerical data or research papers may be correlated for visual analysis. A variety of user-selectable views may be correlated for user interaction to identify relationships that exist among the different types of data or various operations performed on the data. Furthermore, the user may explore the information contained in sets of records and their associated attributes through the use of interactive 2-D line charts and interactive summary miniplots.

WO 01/24060 A2

**Data Processing, Analysis, and Visualization System
For Use with Disparate Data Types**

5 RELATED APPLICATIONS

The following identified U.S. patent applications are relied upon and are incorporated by reference in this application:

10 U.S. Patent Application Ser. No. _____, entitled "METHOD AND APPARATUS FOR EXTRACTING ATTRIBUTES FROM SEQUENCE STRINGS AND BIOPOLYMER MATERIALS," filed on the same date herewith by Jeffrey Saffer, et al.;

15 U.S. Patent Application Ser. No. 08/695,455, entitled "THREE-DIMENSIONAL DISPLAY OF DOCUMENT SET," filed on August 12, 1996; and

20 U.S. Patent Application Ser. No. 08/713,313, entitled "SYSTEM FOR INFORMATION DISCOVERY," filed on September 13, 1996.

The disclosures of each of these applications are herein incorporated by reference in their entirety.

TECHNICAL FIELD

This invention relates to data mining and visualization. In particular,
25 the invention relates to methods for analyzing text, numerical, categorical, and sequence data within a single framework. The invention also relates to an integrated approach for interactively linking and visualizing disparate data types.

30 BACKGROUND OF THE INVENTION

A problem today for many practitioners, particularly in the science disciplines, is the scarcity of time to review the large volumes of information that are being collected. For example, modern methods in the life and

chemical sciences are producing data at an unprecedented pace. This data may include not only text information, but also DNA sequences, protein sequences, numerical data (e.g., from gene chip assays), and categoric data.

5 Effective and timely use of this array of information is no longer possible using traditional approaches, such as lists, tables, or even simple graphs. Furthermore, it is clear that more valuable hypotheses can be derived by simultaneous consideration of multiple types of experimental data (e.g., protein sequence in addition to gene expression data), a
10 process that is currently problematic with large amounts of data.

Visualization-based tools for analyzing data are discussed in, for example, Nielson GM, Hagen H, Müller H, eds., (1997) Scientific Visualization, IEEE Computer Society, Los Alamitos); (Becker RA, Cleveland WS (1987) *Brushing Scatterplots*, Technometrics 29:127-142;
15 Cleveland WS (1993) Visualizing Data, Hobart Press, Summit, NJ); (Bertin J (1983) Seminology of Graphics, University of Wisconsin Press, London; Cleveland WS (1993) Visualizing Data, Hobart Press, Summit, NJ). These tools have focused largely on data characterization, and have provided limited user interactivity. For example, the user may gain access to
20 underlying information by selecting an item with a pointer.

These tools, however, have significant drawbacks. Although current tools can handle certain data types (e.g., text, or numerical data), they do not allow a user to interact with disparate data types (i.e., text, numerical, categoric, and sequence data) within an integrated data analysis, mining,

and visualization framework. Furthermore, these tools do not allow a user to interact well between different visualizations in the manner required to gain knowledge.

What is needed, therefore, is a tool that allows a user to analyze,
5 mine, link, and visualize information of disparate data types within an integrated framework.

SUMMARY OF THE INVENTION

Systems and methods consistent with the present invention aid a
10 user in analyzing large volumes of information that contain different types of data, such as textual data, numeric data, categorical data, or sequential string data. Such systems and methods determine and display the relative content and context of information and aid in identifying relationships among disparate data types.

15 More specifically, one such method defines a uniform data structure for representing the content of an object of different data types, selects attributes of different objects of a variety of different data types that may be represented in the uniform data structure and operates on the selected attributes to produce first representations of the objects in correspondence
20 with the uniform data structure.

The data types may include numeric, sequence string, categorical and text data types. An index may be produced that includes second representations of non-selected attributes of a particular object and that associates the non-selected attributes with a particular first representation.

The first and second representations may be vector representations. A first set of the selected attributes associated with a first set of objects may be used to determine the relationships among the first set of objects of a particular data type and non-selected attributes associated with the first set of selected attributes may be used to correlate objects represented by the first set of selected attributes with a second set of objects represented by a second set of selected attributes. The first and second set of objects may be displayed in first and second windows on a display screen and the second set of objects that corresponds to the selected object or objects may be highlighted.

A method consistent with the present invention identifies relationships among different visualizations of data sets and includes displaying first graphical results of a first type analysis performed on selected attributes of a first set of objects and displaying second graphical results of a second type analysis performed on selected attributes of a second set of objects. Certain objects represented in the first graphical results may be selected and corresponding objects represented by the second graphical results that correspond to the certain objects are highlighted. The highlighting may be based on attributes not used for creating the first graphical results.

Another aspect of the present invention is directed to a system and a method for visualization of multiple queries to a database that includes selecting multiple queries to a database, querying records in the database based on the multiple queries, creating a query matrix indexed based on

the selecting, and populating the query matrix based on the querying.

Another method consistent with the present invention interactively displays records and their corresponding attributes and includes generating a first 2-D chart for a first record, where at least two attributes associated with the first record are shown along one axis, and the values of the attributes are shown along the other axis. Input is received from a user selecting the first record on the first 2-D chart and an index is analyzed to determine if the first record is shown in another view. If the first record is shown in another view, the visual representation of the first record is altered in the another view based on the user input.

Another method consistent with the present invention interactively displays records and their corresponding attributes and includes generating a 2-D scatter chart that depicts a plurality of records. A 2-D line chart is generated for a group of records contained in a portion of the 2-D scatter chart. At least two attributes associated with the group of records are shown along one axis, and a statistical value for each of the at least two attributes is shown along the other axis. A 2-D line chart is superimposed at a location on the 2-D scatter chart that is based on the location of the group of records on the 2-D scatter chart.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in, and constitute a part of, this specification illustrate at least one embodiment of the invention and, together with the description, serve to explain the

advantages and principles of the invention. In the drawings,

FIG. 1 is a block diagram of visualizations screens or views that are consistent with the present invention;

FIG. 2a is a block diagram of a computer system and program
5 modules consistent with the present invention;

Figs. 2b, 2c, 2d and 2e are block diagrams of program modules consistent with the present invention;

FIG. 3 is a flow diagram of a processes associated with a data editor consistent with the present invention;

10 Figs. 4a and 4b are screen shots associated with a data editor consistent with the present invention;

FIG. 5a - 5d are flow diagrams of a processes associated with a view editor consistent with the present invention;

Figs. 6a - 6m are screen shots associated with a view editor
15 consistent with the present invention;

FIG. 7a and 7b are flow diagrams of processes associated with an analysis processing module consistent with the present invention;

FIG. 8 is an example file format consistent with an embodiment of the present invention;

20 FIG. 9 is a flow diagram of a clustering process consistent with the present invention;

FIG. 10 is a flow diagram of a projection process consistent with the present invention;

FIG. 11 is table that identifies operations of program modules used

in conjunction the meta data consistent with the present invention;

FIG. 12 is a flow diagram of a visualization linking process
consistent with the present invention;

FIG. 13 a flow diagram of a method consistent with the invention for
5 displaying information interactively by using 2-D charts;

FIG. 14 is a representative user interface screen showing 2-D line
charts consistent with the invention;

FIG. 15 is another representative user interface screen showing 2-D
point charts consistent with the invention;

10 FIG. 16 is another representative user interface screen showing 2-D
line charts linked to a galaxy view consistent with the invention;

FIG. 17 a flow diagram of a method consistent with the invention for
displaying information interactively by using summary miniplots;

FIG. 18 is a representative user interface screen showing the use of
15 summary miniplots in a galaxy view;

FIG. 19 provides an illustration of a multiple query tool visualization
according to the present invention;

FIG. 20 illustrates a process of creating a visualization using the
multiple query tool;

20 FIG. 21 illustrates a dialog box to set the type of query;

Figs. 22A-22C display exemplary parameter-setting dialog boxes for
query types shown in FIG. 21;

FIG. 23 illustrates a query matrix according to an aspect of the
present invention;

FIG. 24 illustrates a visualization of the query matrix of FIG. 23 indexed by records;

FIG. 25 illustrates a visualization of the query matrix of FIG. 23 indexed by clusters;

5 FIG. 26 illustrates a visualization as a three-dimensional view;

FIG. 27 illustrates a two-dimensional scatter plot of rows vs. values;

FIG. 28 illustrates the contents of a menu bar, with associated sub-menus, of the visualization of FIG. 19;

FIG. 29 illustrates examples of functions of a tool bar associated
10 with the visualization of FIG. 19; and

Figs. 30A and 30B illustrates views of a visualization matrix having a grid and not having a grid, respectively.

DETAILED DESCRIPTION

15 Reference will now be made in detail to one or more embodiments of the present invention as illustrated in the accompanying drawings. The same reference numbers may be used throughout the drawings and the following description to refer to the same or like parts.

A. Overview

20 Systems and methods consistent with the present invention are useful in analyzing information that contains different types of data and presenting the information to the user in an interactive visual format that allows the user to discover relationships among the different data types. Such methods and systems include high-dimensional context vector

creation for representing elements of a dataset, visualization techniques for representing elements of a dataset including methods for indicating relationships among objects in a proximity map, and interaction among datasets including linking the visualizations and a common set of
5 interactive tools. In an embodiment, the interactions, regardless of data type, among the visualizations and the common set of tools for the interactions is enabled by maintaining meta data, as discussed herein, in a common set of file structures (or database).

Methods and systems consistent with the present invention may
10 include various visualization tools for representing information. A tool for visualizing multiple queries to a database is provided. In another visualization tool, if a first record of a 2-D chart of one view is shown in a second view, the visual representation of the first record is altered in the second view based on the user input. In another visualization tool, a 2-D
15 line chart is superimposed at a location on a 2-D scatter chart that is based on the location of a group of records on the 2-D scatter chart. Other tools consistent with the present invention may be used in conjunction with the methods and systems described herein.

As used herein, a record (or object) generally refers to an individual
20 element of a data set. The characteristics associated with records are generally referred to herein as attributes. A data set containing records is generally processed as follows. First, the information represented by the records (including text, numeric, categoric, and sequence/string data) are received in electronic form. Second, the records are analyzed to produce a

high-dimensional vector for each record. Third, the high-dimensional vectors may be grouped in space (i.e. a coordinate system) to identify relationships, such as clustering among the various records of the data set. Fourth, the high-dimensional vectors are converted to a two-dimensional representation for viewing purposes. The two-dimensional representation of the high-dimensional vectors is generally referred to herein as "projection." Fifth, the projections may be viewed in different formats according to user-selected options, as shown by the four views (110, 120, 130, and 140) on display monitor 100 in Fig. 1.

Systems and methods consistent with the present invention enable a user to select a record in view 110 and cause the corresponding record in another view to be highlighted. For example, selecting a particular record in view 110 causes the corresponding records 122 and 132 to be highlighted in views 120 and 130, respectively. The highlighted points may represent different analyses performed on the same records or may represent different data types associated with the records.

B. Architecture

Fig. 2a depicts a computer system 200 consistent with the present invention. Computer programs used to implement methods consistent with the present invention are generally located in a memory unit 210, and the processes of the present invention are carried out through the use of a central processing unit (CPU) 280 in conjunction with application programs or modules. Those skilled in the art will appreciate that memory unit 210 is representative of read-only, random access memory, and other memory

elements used in a computer system. For simplicity, many components of a computer system have not been illustrated, such as address buffers and other standard control circuits; these elements are well known in the art.

Memory unit 210 contains databases, tables, and files that are used
5 in carrying out the processes associated with the present invention. CPU 280, in combination with computer software and an operating system, controls the operations of the computer system. Memory unit 210, CPU 280, and other components of the computer system communicate via a bus 284. Data or signals resulting from the processes of the present invention
10 are output from the computer system via an input/output (I/O) interface 290.

The computer program modules and data used by methods and systems consistent with the present invention include visualization set up programs 212, processing programs 220, meta data files 230, interactive graphics and tools programs 240, and an application interface 250. The
15 visualization set up programs 212 determine the name to be used for a collection of records identified by a user, determine the formats to be used for reading files associated with the records, identify formatting conventions for storing and indexing the records, and determine parameters to be used for analysis and viewing of the records. The processing programs 220
20 transform the raw data of the identified records into meta data, which in turn is used by the interactive visualization tools. The meta data files 230 include the results of statistical feature extraction, n-space representation, clustering, indexing and other information used to construct and interact among the different views. The interactive graphics and tools programs

240 enable the user to explore and interact with various views to identify the relationships among records. The application programming interface (API) 250 enables the components 212, 220, 230, and 240 to exchange and interface information as needed for use in analysis and visual display.

5 The visualization setup programs 212 further include a data set editor 214 and a view editor 216. The processing programs 220 further include vector programs 222, cluster programs 224, and projection programs 226. The meta data files 230 are a subset of databases and files 260.

10 The data set editor 212 enables the user to define the collection of records (i.e., a data set) to be analyzed, identifies the data type, and creates directories for use in organizing the data of the data set. The view editor 216 sets up the user's raw data for viewing by the interactive tools and graphics. Vector programs 222 create high-dimensional context
15 vectors that represent attributes of the records of the data set. Cluster program 224 groups related records near each other in a given space (cluster) to enable a user to visually determine relationships. Projection programs 226 convert high-dimensional representations of the records of a data set to a two-dimensional or three-dimensional representation that is
20 used for display. The databases and files 260 contain data used in conjunction with the present invention, such as the meta data 230.

C. Architectural Operation

1. Data Collection (Data Set Editor)

Fig. 3 illustrates an implementation of processes performed to define

and enable the formatting of a selected data set, as performed by the data set editor 212. A data file to be used as the source for the subsequent analysis is requested (step 302). After a file name, data type and directory location is entered (step 304), the process determines and validates the data type indicated by the user (step 310). The validation process first determines whether the data of the source data file is in a common sequence data format (step 312). If the data is not one of the common sequence data formats, the process determines whether the data is an array of data consisting of numeric, categoric, sequence, or text (step 314). If the data is not a data array, the process determines whether the data is free form text (step 316). If the data is not free form text (step 316), an error message is generated (step 320).

If the validation process determines that the data is sequence data, such as genome sequence data (step 312), the process determines whether the sequence data is in FastA file format (step 322) or whether the sequence data is in a SwissProt file format (step 324). An example FastA input file is provided in Appendix B. The operations and data associated with processing sequence data is discussed in more detail in U.S. Patent application serial no. _____, entitled "Method and Apparatus for Extracting Attributes from Sequence Strings and Biopolymer Materials" filed on the same day herewith by Jeffrey Saffer, et al. If the sequence data is not in one of these formats, an error message is generated (step 320). If, however, the data is either a FASTA file (step 322) or a SwissProt file (step 324), the appropriate formats and delimiters, as discussed herein, are

determined to be used for the respective FASTA file or SwissProt file (step 330). After the appropriate format/delimiters for the data type are determined (step 330), the corresponding format file/record delimiters are established (step 340). The format file/record delimiters specify the valid
5 formats for reading the files and identifies the meta data files that are to be used for subsequent processing of the data set as discussed herein.

A file directory 360 is created for storing the meta data files associated with the data set (step 350). The file directory 360 includes a document catalog file (DCAT) 362 and a data set properties file 364. The
10 DCAT file 362 is used as a master index for all records in the data set. The indexes stored in the DCAT file are used to integrate the information associated with the various views selected for the data set. For example, the DCAT file 362 contains indexes that associate all the data of a data set with a particular view, although only a subset of the data set is used to
15 create the view. The properties file 364 is also produced and stored in the file directory and contains information about the source data files for the view, including their type (corpus type), the number and full path (location) for the source files, the format used, and the date created. In addition, the properties file keeps track of subsequently processed views including the
20 subdirectory where those views reside. An example properties file is provided in Appendix A.

Figs. 4a and 4b depict exemplary screen shots presented on a display monitor to a user for defining a new data set (i.e., collection of records) using data set editor 212. A user names and defines a data set

using the data set editor 212. When the data set editor is selected, a graphical interface screen 400 is presented to a user for use in defining options or parameters associated with the data set. For example, graphical interface screen 400 is presented to a user when the user selects the
5 sources tab 410.

The user may enter a name for the data set in a field 412 and may specify the data set type as indicated by the selection options 414, such as array data, protein or nucleotide sequences, or text. The source of this data set may be specified in the field 418 as indicated by the directory and
10 subdirectory specification 420. The user may select the add, view, or delete options 424 to perform the function indicated by the name on the data set source. The user may save the data as indicated by the option 426 or continue to a new view as indicated by the option 428.

By selecting the format tab 440, the user may specify how fields
15 contained within the source file are delimited by selection of a field delimiter option 442. The field delimiter options illustrated include an option to delimit the field by a colon, comma, space, tab, or a user defined delimiter.

2. Analysis and View Setup (View Editor)

Fig. 5a illustrates an implementation of a process used for creating
20 parameters when defining the type of analyses or views for a data set, as performed by view editor 216. The user may enter this information using a graphical interface as depicted in Fig. 6a, which shows source file tab 604, format tab 610, preparation tab 630, processing tab 660, clustering tab 680, and projection tab 690, respectively.

Fig. 6b is a screen display showing the options presented to a user when the format tab 610 is selected. The user may provide in the format file field 610, a file to use for formatting the view such as medline 31.fmt. The user may also specify a stop words file such as the default text stop file shown in the field 614. This stop words file is a list of words that the text engine will ignore during analysis. The user may input a file to specify the default punctuation of the file as indicated by the default.punc file indicated in the field 616. The punctuation file tells the text engine how to handle non-alphabet characters. For each of the files requested, the user may use the default file specified by the system or choose another. The user may select or view any of the files of the format screen of Fig. 6b by selecting the select option 620 or the view option 622.

The user is also requested to provide preparation parameters (step 540). The processes associated with step 540 are discussed in more detail in Fig. 5b. The user may specify vector creation, cluster, and projection parameters to be used in constructing a view (steps 550, 560, and 570, respectively). The projection parameters include cluster cohesion, cluster area, and cluster spread. Vector creation and clustering parameter processes are discussed in more detail in Figs. 5c and 5d, respectively.

Referring to Fig. 5b, the view editor processes are discussed. The view editor first checks the data type (step 541) by evaluating whether the

and motif pattern file parameters (step 544). If the data is not sequence
5 data (step 542), the process determines whether the data is numeric data
(step 545). If the data is not numeric data, no preprocessing or preparation
information is required for text information (step 546). If the data is numeric
data, a display screen that requests numeric data and preparation
information from a user (step 547) is presented. The numeric preparation
10 data request may include column/row specifications, operation sets, and
clustering fields (step 548).

Fig. 5c illustrates an implementation of the processes associated
with gathering vector creation parameters within the view editor 216 (Fig.
2). The view editor 216 first checks the data type (step 551). If the data is
15 sequence data (step 552), sequence specific text engine parameters are
requested or obtained for the particular data set (step 553). The text
engine parameters requested may include the number of topics/cross
terms, topicality settings, use association t/f parameters, associated matrix
threshold parameters, and record filter ranges (step 554).

20 If the data is not sequence data (step 552), the view editor
determines whether the data is text data (step 555). If the data is text data,
text specific text engine parameters are requested from the user (step 556)
such as the text engine parameters discussed above (step 554). If the data
is not text data (step 555), no user specified parameters are needed and

Fig. 5c illustrates an implementation of a process specifying clustering parameters. Various types of clustering may be used such as k-means or hierarchical clustering as known to those skilled in the art. The view editor 216 presents a display screen to the user for the user to specify the clustering choice (step 561). The process determines whether k-means clustering has been chosen (step 562). If k-means clustering is requested (step 562), k-means clustering parameters are requested from a user or obtained (step 563) such as the number of clusters, the number of iterations, the cluster seed method or whether correlation order is to be used (step 564). If k-means clustering is not requested (step 562), the process determines whether the user desires hierarchical clustering (step 565), and displays or gets hierarchical clustering parameters (step 566). The hierarchical clustering parameters may include determining the number of clusters or cluster coherence values to be used and whether the user desires correlation order for the clusters may be determined (step 567). If hierarchical clustering is not desired (step 565), no parameters are required (step 568).

Referring to Fig. 6c, when the preparation tab 630 is selected, the user is presented with a data specification option 632, an operation set option 640 and a clustering selection option 650. The user may enter a value for the columns in the field 634. For the data set specified, the user may identify the type of data, such as numeric data, categorical data,

specify the columns 636 in which that data type is located and may specify a field name for that specific data as indicated under the field name 637. A predefined selection field 638 may be used to specify the types of data for the field name and columns provided.

A user may perform any number of mathematical manipulations on the numeric data (one or more manipulations or transformations of the data is referred to as an operation set). These options include various logarithmic operations, methods for normalizing data, methods for filling missing data points, and all algebraic functions. Referring to Fig. 6d, for example, the reciprocal or the value for each numeric data item may be requested and then the logarithm taken for that reciprocal, creating a new field 642 called Operation Set1.

Fig. 6e shows the screen displayed if the clustering selection tab 650 is selected. The user is presented with a set of field/trench forms 652 for which clustering operations may be applied. In the example illustrated, operation set 1, or numeric field name 1 may be chosen for clustering.

Referring to Fig. 6f, for a sequence, the user may have motifs/n-grams, complexity filtering, exclusions, and amino acid substitutions options from which to select. Operation on or with sequence data is discussed in more detail in U.S. patent application entitled "Method and Apparatus for Extracting Attributes from Sequence Strings and Biopolymer Materials" filed concurrently herewith and is expressly incorporated herein by reference. If the user wants to represent the sequence as a high-

dimensional vector based on the occurrence of functional or structural motifs, a file is specified which defines those motifs. The user can have that vector based on the number of occurrences of each motif or, if desired, have the vector based on a binary format (the motif is either there or not) by checking the single motif output option. Alternatively, or in addition, the user may specify any combination of overlapping n-grams to be created to represent the sequence in field 654. The user also has the option to specify whether the n-gram should be included based on number of occurrences within the sequence. If neither motif nor n-gram options are selected, the program will analyze the text (e.g., annotations) associated with the sequence records. The complexity filtering options provide the user the ability to include the entire sequence or eliminate regions of low or high complexity, for example, using the public domain tool SEG. The user may also specify certain records to be excluded, for example, based on sequence length, or title, by selecting options in the exclusion interface. Finally, the use of amino acid or nucleotide substitutions can be defined in the Amino Acid Substitution interface.

Referring to Fig. 6g, the options provided to the user for processing data is illustrated. The user may use a sliding scale to specify the magnitude or weight to give to associations as indicated by the association field 672. The user may enter the number of topics to be used in the field 674. The topics are the features that describe the vectors. For text, these are the vocabulary words that best describe the thematic content of the records; for sequences, the topics are the n-gram vocabulary words that

best distinguish one sequence from another. The user may specify the requested number of cross terms as indicated in the field 676. Cross terms are the vocabulary words that are not topics. The user may specify the number of times that the topics may appear in a record before being
5 identified as a topic and an upper limit may be included as well as indicated in the fields 678a and 678b. In the field 679a and 679b, the user may specify the number of times that the terms must appear in other documents by specifying a lower limit in field 679a and an upper limit in field 679b. These fields are used as filtering fields for processing. The topicality
10 method for Fig. 6g is 'Specify the settings by the number of terms.'

Referring to Fig. 6h, the topicality method for the processing option is specified as 'Specify the settings by threshold.' The user may use the sliding scale field 680 to specify the number of associations needed. The user may use a sliding scale input for identifying the minimum topicality for
15 topics weight and the minimum topicality for cross terms as indicated by the fields 682 and 684, respectively. The user may specify upper and lower limits for defining the number of appearances to trigger identification for topics and cross terms, as indicated by the fields 686a, 686b, 688a, and 688b.

20 Referring to Fig. 6i, the user may specify a topicality method that automatically calculates the setting for the view all indicated in the display screen illustrated. The user may use a sliding scale selection field that specifies the weights of association as indicated by the field 689. Referring to Fig. 6j, the user may specify the weights of association for the topicality

method that automatically calculates the settings with emphasis on local topics.

Referring to Fig. 6k, when a user selects the clustering tab 690, the user may specify a clustering method such as hierarchical or k-means.

- 5 When hierarchical clustering is chosen, the user may select an option to compute clusters based on coherence. The user may indicate the number of clusters, and the cluster coherence. The user may also select whether to correlate the order after clustering.

- Referring to Fig. 6l, the graphical interface used for specifying the
- 10 parameters of the k-means is illustrated. The user may specify the number of clusters or the number of iterations to be used for the k-means. When k-means is used, the user may select the cluster seeding parameters such as using random seeding or using dimensional seeding. The seeding may also occur by using the computer's internal clock (system time) to seed
 - 15 random number generator. The user may alternatively specify a value for the random generator seed.

- Referring to Fig. 6m, the user may select the type of projection to use by selecting the projection tab 695. The user may select cluster cohesion, cluster area, or cluster spread. When the user selects either of
- 20 these options, the user may use a weighted scale for each of the options to identify the weight to be associated with each projection option.

3. Common Formatting, Vector Creation, and Index Creation

Fig. 2b illustrates vector creation engines consistent with the present invention. In an implementation, vector creation programs 222 include a

numeric engine 222a, and a text engine 222b.

Referring to Fig. 7a, the general processes performed by the processing programs are discussed. Certain types of data, such as sequence data, is preprocessed (step 702) prior to data being input into the text engine. The sequence data is modified to a form that is acceptable to the text engine for generating the high-dimensional context vectors.

High-dimensional context vectors are created based upon the attributes of the objects or records to be used for a view and vector indices that correspond to the particular view are created and stored in a vector file associated with the data set (step 706). The vectors are clustered using known clustering programs based upon information from the vector files (step 708). The cluster assignment file (.hcls), as discussed below, is created (step 708). Two dimensional coordinates of the records and centroids are calculated for creating a two dimensional projection of the clustered vectors (step 710). Two dimensional coordinate files are created (.docpt) for each document.

i. Vector Creation and Formatting

The visualizations discussed herein are based on high-dimensional context vector representations of the data. Thus, each type of data is represented in that manner. For purely numeric data, the vector representation is simply the values associated with each record attribute. For categorical data, the vector representation can be based on any method that translates categorical values or the distances between values as a number. For text data, the vector representation can be derived by

latent semantic indexing as known to those skilled in the art or by related methods, such as described in U.S. patent application serial number No. 08/713,313, entitled "System for Information Discovery," filed on September 13, 1996. For sequence data, the context vector can be derived from any
5 combination of numerical or categorical attributes of the sequence or by methods described herein. In addition, a user skilled in the art will recognize that the vectors created for each record do not have to be created from a single data type. Rather, the vectors can be created from mixed mode data, such as combined numeric and text data.

10 Not only are high-dimensional vectors created for each record of a data type, but also a common method is used to store that information about the records and their vectors so that later processes can access the data. Methods consistent with the present invention create a group of meta data files through the action of a series of computational steps (collectively
15 referred to as the numeric engine) alone, or in conjunction with another series of computational steps, referred to as the text engine. The files that are produced are binary, for reasons of access speed and storage compactness. The files produced during vector creation are discussed below in more detail.

20 Unless otherwise noted, the files discussed below have the following characteristics: (1) Files are binary, and remain within a directory established for the analysis; (2) IDs and positions are 0-based; (3) Terms have been converted to lowercase, and are listed in ascending lexical order; (4) Record IDs are listed in ascending order; (5) Index files

(.<x>_index) contain cumulative counts of records written to the file they are indexing (<x>). This cumulative count is for the current record and all previous records. This cumulative count is equivalent to the record no. of the next record; and (6) Internal Numerical representations in a Sun

5 Microsystem Operating System are:

TermID (4 bytes)
TermCount (4)
DocID (4)
DocCount (4)
10 streampos (4)
double (8)

Although the examples provided refer to flat file storage of the relevant information, one skilled in the art will recognize that a database
15 could equally serve as the method for storing and retrieving the meta data.

The files produced during vector creation are:

.dcat (document catalog)
number of records in the source file
20 for each record (line number-2 is the record id)
Source file id
Starting byte offset with the source file
Length (in bytes) of the record

.tl (title file)
25 for each record (line number-1 is the record id)
title field

.docv (vector file)
30 no. of records in view
no. of dimensions for vectors (= no. of topics)
for each record
for each dimension
coordinate value (float)

35

ii. Visualization and Formatting

The visualization methods keep track of the location of the record representation and may use an object-oriented design. One type of visualization that is especially effective with high-dimensional data is a proximity map or a galaxy view. This and related visualizations can take advantage of methods to group the records in the high-dimensional space (clustering) and to project the arrangement of objects in high-dimensional space to two or three dimensions (projection).

Clustering can be by any of a number of methods including partition methods (such as k-means) or hierarchical methods (such as complete linkage). Any of these type methods can be used with the present invention. Despite the different methods, the computational processes that carry out the clustering create a common set of meta files that allow the chosen visualization method to access the clustering information, regardless of original data type.

The files produced during cluster analysis are:

.hcls (cluster assignment file)

This file contains the assignments for each record to a cluster. The format of the file is as follows :

Number of total Clusters

For each cluster (in correlation order)

Cluster ID

Cluster vector as determined by taking the average of the record vectors assigned to the cluster

Number of Records in the Cluster

The record id's of the records assigned to the cluster

After the .hcls file is produced, it may be resorted in correlation order (a user-definable option).

An example .hcls file:

```

9 (number of clusters)
6 (cluster ID)
0.0457451 0.0399342 0.0864002 0.0652852 0.0635923 0.0429373 0.0650352
0.0661765 0.0487868 0.0885645 0.10 0173 0.0482019 0.048553 0.091455
0.0991594 (cluster vector)
4 (number of records in the cluster)
7 (record ID)
4 (record ID)
3 (record ID)
5 (record ID)

5
0.0392523 0.0364486 0.0897196 0.0626168 0.0598131 0.0364486 0.0616822
0.0794393 0.0448598 0.0925234 0.11
215 0.0429907 0.0420561 0.0962617 0.103738
1
6
1
0.0341207 0.0209974 0.0918635 0.0682415 0.0603675 0.0314961 0.0629921
0.0656168 0.0393701 0.11811 0.1049
87 0.0393701 0.0393701 0.112861 0.110236
1
8
3
0.0587949 0.0578231 0.0739416 0.0695847 0.0651338 0.0544486 0.0705118
0.0665825 0.0739358 0.0612976 0.07
11892 0.0697833 0.0711892 0.0645948 0.0711892
3
12
13
2

```

iii. Projection and Formatting

Projection can also be by any number of methods, for example, multidimensional scaling. Like cluster analysis, a specific projection method is not required for use with the present invention. However, as with clustering, the results of that projection are stored in a common format so that the visualization operations can retrieve the data independent of the original data type.

Files created during projection from high-dimensional space to 2 or 3 dimensions are:

.cluster (2-D coordinates for the cluster centroids)

This file contains the 2-D coordinates for placing the cluster centroid on a galaxy view). For each cluster, a single line in the file contains:

Cluster ID
X coordinate
Y coordinate

An example .cluster file:

```
6 0.770783 0.831761
5 1 1
1 0.920542 0.989886
3 0.073888 0.210541
7 0.0206639 0.109404
4 0 0.13854
0 0.0187581 0.153266
2 0.139079 0.0695485
8 0.374849 0
```

.docpt (2-D coordinates for the individual records)

This file contains the 2-D coordinates for placing the records on the Galaxy

For each record, a single line in the file contains

Record ID
X coordinate
Y coordinate
Cluster ID that the record belongs to

Example of a .docpt file

```
0 0.374849 -4.46282e-07 8
1 0.0300137 0.145639 0
2 0.0890008 0.222 3
3 0.861783 0.90898 6
4 0.745403 0.813245 6
5 0.84583 0.896318 6
6 1 1 5
7 0.630116 0.708499 6
8 0.920542 0.989886 1
9 0.0206639 0.109405 7
10 0.0206639 0.109405 7
11 -4.91018e-08 0.1385 4
```

Note that the X and Y coordinates in the .cluster and .docpt files are represented by a number between 0 and 1 inclusive. Also note that analogous file structures would be used for a 3D projection.

iv. Data Linkage and Formatting

5 Advantageously, the present invention enables linkage among all visualizations and data types (text, categorical, numerical, or sequence). Prior methods enabled linkage between views of the same data visualized using different attributes or visualizations. In addition to the attributes used to create the visualization, other attributes or descriptors for each data
10 record are linked and readily available for interaction. These interactions are possible with any of the data types. That is, additional attributes related to a record, as well as those used for vector creation, are equally available regardless of data type. This is accomplished through the use of a
15 common set of file or database structures created by the numeric or text engines. These files store information about each record attribute, which itself can be any of the data types. These files are created during an initial processing of the data and are independent of the specific visualization method to be employed. These files provide a common framework that can be addressed by any visualization or interactive tool through an API.

20 The files created to store and manage the ancillary data, such as data not used in creating a view, are:

.headings (used for data input through a matrix array only)

25 for each record (line number-1 is the record id)
 name of the column heading

.vocab (text)

for each term in the view
term (i.e., a word)

.vocab_index

for each term in the view
cumulative no. of chars written to .vocab (including \n's);

.field_off

for each record
for each field defined in the format file
starting position (in bytes) of the field from the start of the
record and the number bytes in the field

.corr

for each correlatable field defined in the format file
number of unique values of field
for each unique value of the field
number of records that contain the unique value
record id's of the records that contain the value

.ifi (inverted file index)

for each term in the view
for each record containing that term
doc ID
frequency of term within the record

.ifi_index

for each term in the view
cumulative no. of records written to .ifi

.docterm (document term file)

for each record
for each term in the record
term ID
frequency of term within the record

.docterm_index

for each record
cumulative no. of records written to .docterm

.topic (topic file)

no. of topics
minimum topicality for topics
minimum no. of docs containing a topic
maximum no. of docs containing a topic
no. of cross terms
minimum topicality for cross terms
minimum no. of docs containing a cross term

maximum no. of docs containing a cross term
 for each major term (topic or cross term)
 term ID
 topicality
 5 no. of docs containing the term
 term strength (4 bytes; 0=MINOR_TERM,
 1=CROSS_TERM, 2=TOPIC_TERM)

.rel (Association matrix file)
 no. of major terms
 10 no. of topics
 conditional correction
 for each major term
 for each topic
 relation value of major term to topic (values are encoded as
 15 four-bits and packed into bytes)
 four zero bits to pad last byte for major term, if needed

In each of the above files, "terms" refer to text vocabulary words;
 "topics" refer to text vocabulary words deemed by statistical analysis to be
 most likely to convey the thematic meaning of the text; and "crossterms"
 20 refer to text vocabulary words that provide some meaningful description of
 the text content but are not topics. U.S. Patent Application Ser. No.
 08/713,313, entitled "System for Information Discovery," filed on September
 13, 1996 discusses topics and crossterms in more detail.

Many of the binary files are paired, with the first file holding the
 25 information, and the second providing an easily accessed index into the
 first. For example, the inverted file index consists of .ifi and .ifi_index files.
 Each index is a list of the cumulative number of records in the data file.

Together these files provide indexing of and access to the textual
 information associated with each record including the distribution of
 30 keywords within each record and co-occurrences of those keywords.
 Furthermore, the files provide a catalog of all the categorical data including

the distribution of the values. For numerical attributes not used in the actual vector representation, additional files are created using the .docv format so that this type of ancillary information will also be readily available to establish interaction among the various views.

5 The processes associated with producing the series of common files described above are depicted in Fig. 7b. Referring to Fig. 7b, the text engine (730) creates the files associated with text or categorical fields. The expected input for the text engine (block 730) is a tagged formatted file. For text data sets, the input is either the original format for the input or the
10 result of a processing step to identify the beginning and end of each record along with special information, such as the record title. An example original input file to the text engine is provided in Appendix C.

For sequence data in the commonly used formats FASTA (720) or SwissProt (722), a software module (724) reformats the input file to contain
15 a series of fields that delineate the initial input and meta data created for the vector representation (726). The reformatting and processing of sequence data is discussed in more detail in the U.S. patent application entitled "Method and Apparatus for Extracting Attributes from Sequence Strings and Biopolymer Materials" filed concurrently herewith and
20 incorporated herein by reference. Once in this tagged format (726), the text engine (730) is able to create all the required meta data files.

Numerical data, or any other data presented in a data matrix, (750) is received at the numeric engine (752). The data in the input file can be tab delimited or use any other delimiter. The numeric engine (752) creates

the record vectors for data presented in a data matrix instead of the text engine. In addition to the numerical columns, the user may specify other columns within the table that can contain textual, sequence, or categorical information or additional numerical data that will not be used for the vector
5 created. Usually, each row in the table becomes a record; however, the user can choose to make each column the record. Each user-defined set of columns becomes an attribute (also called fields) within the record. A set of numeric columns is specified by the user for subsequent clustering. The other fields, which can be numeric, text, categorical, or sequence, will
10 become attributes of the record that can be queried, listed, or otherwise made available within the interactive tools.

If categorical data is specified by the file format (Fig. 8), as indicated by the index 804 for the view used, categorical data is processed during the text engine processing steps for all types of data. The categorical data
15 shown in Fig. 8 records where each unique character strain and the categorical field occurs in the data set. Thus, subsequent categorical tools are enabled to correlate various records based upon the categorical values.

Each field expected in the input file is defined by a section beginning with ||F followed by the field number (e.g., ||F0). For each field, the name is
20 defined (in this case, title). Then the type of field is defined; this could be string (text or categorical), numeric, or sequence. Next, the delimiter tag for the field is defined. The METHOD line indicates whether the field is on a single line or continues to the next field. The DOC_VECTOR line tells the clustering module whether to use this information in the cluster analysis.

The next item designates whether the field should be accessible within the query tools. The CORR line determines whether the contents of the field should be indexed for all possible associations. The next item defines whether the content is case sensitive or not. The following lines describe the behavior of the delimiter tag. `WHOLE_BOUNDARY` indicates whether
5 the tag must be a single word or could be embedded within other text; `LINEPOS` indicates whether the tag must start at the beginning of a line or may be found elsewhere. Similar information would be given about each field in the data. This format file is stored in a directory associated with the
10 view created.

Referring again to Fig. 7b, the numeric engine (752) is executed on the set of columns that the user specified for clustering. The numeric engine (752) performs any number of user defined mathematical operations and creates a record vector that is identical in format to those
15 produced for sequence or text data. In contrast to the text engine (730), which automatically determines the features to use in the record vector, the vector creation in the numeric engine (752) utilizes a user specified set of columns from the users column/row formatted source file.

Once the record vector is created (758), the numeric engine
20 automatically creates a text engine compatible source file (i.e., reverse engineered tagged text file, 754), and corresponding format file (756) from the input column/row formatted table. An example format file produced from the numeric engine is shown in Appendix D. The new tagged text source file and format files (726) are used so that any text, categorical, or

sequence information that may have been embedded within the original column/row files, can be processed by the same programs that operate on text, categorical, or sequence information. This subsequent processing is performed by the text engine (730), which reads the reverse-engineered tagged text source file and indexes the textual and/or categorical data fields within each record (732, 734 and 736). The result is a standardized set of meta data which is related to the user source data and which is available to all tools regardless of data type.

Although the numeric engine processes numerical data, the processing steps of the numeric engine places any of the other data types (text, categorical, or sequence) into an appropriate tagged field in the data file so that the text engine will handle it appropriately.

In summary, if the data input is array data, the array data (column/row formatted tables) is processed by the numeric engine (752). The numeric engine 752 creates a second vector that is identical to the format of the context vectors for sequence and text data produced by the text engine (730). However, in contrast to the text engine, which can automatically determine the features to use in the second vector, the numeric engine 1052 accepts a user defined series of mathematical operations to be performed on specified columns of the array data source file. In order to make the non-numeric contents, such as annotated notes, associated with the array file accessible for subsequent analysis, a format file is produced and a tag text format file is produced for the non-numeric contents associated with the numeric file. The associated non-numeric

contents is used as an input to the text engine and the output is associated with the numeric data. Thus, the textual or categorical data associated with the numeric array data may be indexed and associated with the data as produced for other text data sets that are input to the text engine (730).

- 5 Plain text data should be in a tagged text format and does not require any pre-processing prior to input to the text engine (730).

4. Clustering

Fig. 2c illustrates clustering programs. Three clustering modules or options k-means 224a, cluster-sid 224b, and correlation order 224c are
10 provided. The clustering options may have a set of user definable parameters. The k-means module 224a clusters documents by establishing a user specified number of seed clusters and then iteratively assigns documents to those documents until a user specified number of iterations is reached or the process/algorithm determines that all the
15 documents have been assigned to the clusters.

The k-means module 224a moves documents to minimize the sum of squares between objects and centroids as known by those skilled in the art. The cluster-sid 224b is an agglomerative/hierarchical clustering method that minimizes the maximal between clusters distance (farthest
20 neighbor method). The output of the clustering process is a file containing a correlation ordered list of clusters and the record's IDs of their members. Those skilled in the art will recognize that other clustering algorithms can be used.

Fig. 9 shows a clustering process performed by the processing unit.

A vector file is received from the stored context vector files (step 760) at the cluster implementer (step 904). The user specified clustering parameters are retrieved from stored files (step 906) and the clustering program and parameters associated with the files are determined (step 908). The
5 clustering parameters associated with the clustering program are provided to the cluster implementer (step 904) and the clustering program associated with the vector file of the data set is selected (step 910). The clustering programs are chosen from a k-means clustering program (block 912), a hierarchical clustering program (block 914), or no clustering is
10 selected (block 916). After the clustering program performs its operations (step 910), a cluster assignment file (.hcls) is created (step 920).

5. Projection

Fig. 2d illustrates projection programs 226. Systems consistent with the present invention may apply three separate processes to produce the
15 meta data used to produce visualizations. These processes are carried out by three modules, the PCA-clusters module 226a, a triangulation module 226b, and a document projection module 226c. The PCA-clusters module 226a determines the principle components for each cluster and then determines the two dimensional coordinates for projecting the cluster
20 centroids as known to those skilled in the art. The triangulation module 226b determines the boundaries for the area around each cluster centroid. These boundaries are later used in the doc projection module 226c to take into account the influence of records and neighboring clusters when determining how far from the center and on what side of the cluster

centroid a record will be projected. The doc projection module 226c determines the x,y projection coordinates for each record in the visual analysis.

Referring to Fig. 10, the processes associated with creating a two dimensional projection from the cluster assignment files is illustrated. The cluster assignment file (.hcls) is retrieved from storage (step 1002) and the principle component analysis of the cluster centroid vectors are performed (step 1004). Two dimensional coordinates for the cluster (.clster) are created (step 1008). Delaunay triangulation is performed (step 1010) based on the vector file retrieved from storage (step 1012) that is associated with the data set. Nearest neighbor assignments are associated with the Delaunay triangulation results (step 1014). The projection program determines the two dimensional coordinates for each record (step 1018) based upon the vector files retrieved from storage (step 1012). The projection program also accesses and retrieves the cluster assignment file (.hcls) (step 1020) associated with the data set. The two dimensional coordinates for the group of documents of the data set are stored in a document file (.docpt) (step 1030).

6. Graphic Modules and Tools

Referring to Fig. 2e, the interactive tools and graphics modules are illustrated. The interactive tools and graphics modules 240 include a galaxy module 240a, a master query module 240b, a plot data module 240c, a record viewer module 240d, a query (word) module 240e, a query (number) module 240f, a group module 240g, a gist module 240h, and a

surface map module 240i.

The galaxy module 240g displays records as a scatter plot. The master query module 240b applies a correlation algorithm to all indexed categorical data and creates a two dimensional matrix with values of a category along each axis. At each intersection in the matrix, a rectangle is drawn with sections colored to show the correlation between the categories. The following are analytical tools. The plot data module 240c displays a two dimensional line plot of the n-dimensional vectors created for analysis by the user, this is done for all records in the analysis or just those selected by the user. This module can also be used to examine any ancillary numerical attributes associated with the records. The record viewer module 240d displays a list of the currently selected documents, displays a text of a document, highlights terms selected by other tools, such as the query tool 240e. The query tools 240e and 240f enable the user to input requests to search for information that has been represented by a vector during the processing and analysis of the user's data set. The query tools 240e and 240f compare the user input to vectors representing the processed data set. The query tool 240f performs Boolean or phrase queries in any text or categorical field based on a user's input. The query tool 240f also performs n-space queries based on the user's input and compares the input to the n-dimensional vector used for clustering. Thus, vectors that correspond to the user's input can be identified and highlighted. The numeric query tool 240f performs queries based on numeric values. The group tool 240g enables users to create groups of

records of a data set, based on queries or based on user selections, and colors the groups for display in the galaxy visualization created by the galaxy module 240a. The gist tool 240h determines the most frequently used terms in the currently selected set of records. The surface map
5 module 240i provides a surface map that shows records and a plurality of attributes associated with those records.

Referring to Fig. 11, a table is shown that illustrates meta data files that result from statistical analyses and indexing of the data sets consistent with an embodiment of the present invention. The table also depicts the
10 meta data files that are used for the various interactive tools and graphics modules. All of the meta data files except for the tab delimited column/row file, the tagged text source file(s), and the re-engineered tag text file are defined by the data set name or view name as created by the data set editor 314 or view editor 316 (Fig. 2a) plus an ".extension," such as [data
15 set name].dcat or [view name].cluster. The meta data files include a data set name.dcat file, a data set name.properties file, a view name.clsp file, a view name.cluster file, a view name.corrv file, a view name.dcat file, a view name.docpt file, a view name.docterm file, a view name.docterm index file, a view name.docv(vector) file, a view name.edge file, a view name.fieldoff
20 file, a view name.gif file, a view name.groups file, a view name.fmt file, a view name.hcls file, a view name.headings file, a view name.ifi file, a view name.ifi index file, a view name.properties file, a view name.punc file, a view name.rel file, a view name.repository file, a view name.stop file, a view name.tl file, a view name.topic file, a view name.vocab file, a view

name.vocab index file, a tab delimited column/row file, a tag text source file(s), and a re-engineered tag text file. The table indicates which program modules create, read or update files as indicated by the letters C, R, and U, respectively. For example, the view name.clsp file is created by the view editor 216 (Fig. 2b) and is read by the k-means module 224a and the cluster-sid module 224b (Fig. 2c) and is read by the galaxy module 240a (Fig. 2e). The view name.groups file is updated by the group module 240g. All file access is performed through the API layer (Fig. 2a).

After the clustering and projection processes have been completed, the user may now view the results of the various operations performed on the user's data set. As discussed above, prior methods of visualization do not adequately provide access to relationships among attributes of data records other than those used in creating the visualization and, consequently, do not enable the identification of relationships between attributes of different visualizations or views. A system operating according to the present invention enables a user to identify relationships among different visualizations or views by maintaining all attributes associated with the data record for indexing although all attributes are not used in creating the visualization. Referring to Fig. 12, the processes consistent with an embodiment of the present invention used to link different visualizations or views is discussed. When a user is viewing a particular visualization or view, the user may request to identify the relationships that exist between the attributes used to create the current visualization with the attributes used to create another visualization (step 1202). After the user initiates a

request to explore the data of another view (a target view) an index file associated with the user's current view or data set is accessed (step 1210). After the index file is accessed (step 1210), the process determines whether objects selected by the user in the current view, such as by
5 initiating a query, correspond to objects of a target view based upon all of the attributes contained in the index file (step 1220). If objects of the target view or file correspond to the selected objects of the current view, the objects of the target view are highlighted (step 1230). Therefore, relationships among attributes of data records other than those used in
10 creating the visualization can be used to identify relationships of another visualization as discussed in connection with Fig. 1.

Methods and apparatus consistent with the invention also provide tools that allow a user to display information interactively so that the user can explore the information to discover knowledge. One such tool displays
15 a set of records and their associated attributes in the form of superimposed two-dimensional line charts. The tool can also generate a single two-dimensional line chart that provides the average values for the attributes associated with the set of records. Each of these charts are linked to other views, such that a record selected in the charts is highlighted in the other
20 views, and vice versa.

Another tool generates summary miniplots that may be quickly used by a user to obtain an overview of the attributes associated with a particular group of records. In particular, records shown in a scatter chart are organized into groups. The average values for the attributes associated

with each group of records is used to form a two-dimensional line chart. The line chart is superimposed on the scatter chart, based on the location of the set of records.

As described above, one basic visual tool implemented by the invention for viewing information is a "galaxy view" as produced by the galaxy tool 350a. A galaxy view is shown in window 120 of Fig. 1. The galaxy view is a two-dimensional scatter graph in which records are organized and depicted in groups (or "clusters") based on relationships between one record and another. In addition to this galaxy view tool, the invention provides numerous interactive visual tools that allow a user to explore and discover knowledge.

Fig. 13 describes one method for displaying information interactively, in the form of two-dimensional line charts. The method begins with the user selecting a set of records and a set of attributes associated with those records (stage 1305). The attributes may comprise any of numerous data types, including the following: numeric, text, sequence (e.g., protein or DNA sequences), or categorical. The selected attributes are converted into numerical values, as discussed above.

Next, a two-dimensional line chart is generated to visually depict the records and their associated attributes (stage 1315). Fig. 14 represents an implementation of two-dimensional charts that are consistent with the invention. Fig. 14 contains line chart 1405, and legends 1440 and 1450.

Chart 1405 contains a collection of superimposed line charts that depict a set of records. For example, line chart 1420 depicts one record

within the set, while line chart 1425 depicts another. In the line charts, the x-axis (e.g., as shown by 1410) represents attributes associated with the records, and the y-axis (e.g., as shown by 1415) represents the value of each attribute. The scale of each axis and the colors of the line charts may
5 be modified by the user. Although this description focuses on line charts, other types of charts may be used to depict a set of records, as shown for example by the point chart shown as 1505 in Fig. 15. Legend 1440 contains a text-based description of records. For example, legend 1440 contains a record described as "122C", as shown by 1445. Legend 1450
10 contains a text-based description of attributes.

Methods consistent with the invention can also generate a two-dimensional line chart that shows relationships between the records shown in 1405 (stage 1320). For example, Fig. 14 shows a line chart 1430 that depicts a statistical value corresponding to the set of records shown in
15 1405. In the example shown in Fig. 14, chart 1430 depicts the average attribute value for each record shown in 1405. In alternative implementations, however, chart 1430 may depict other relevant characterizations of the set of records, such as median attribute values, standard deviations (as shown by 1435), etc.

20 In addition to viewing the information in graphical form, the user can interact with the line charts. The invention is capable of receiving input from a user selecting a portion of a chart (stage 1325). This may be achieved, for example, by using a device to point to a portion of map 1405 or by clicking a pointing device on a portion of map 1405. In response to

this user input, the text-based description of the selected record and/or attribute is highlighted in legends 1440 and 1450 (stage 1330). In the example shown in Fig. 14, the user has selected record "122C", as shown by the highlighting in legend 1440. Similarly, the value of a particular attribute being pointed to in charts 1405 or 1430 can be displayed in text format. In the example shown in Fig. 15, the user has selected attribute "RBC", as shown by the highlighting 1515 in the legend and 1520 on the x-axis.

Furthermore, any selections made by the user on charts 1405 or 1430 are propagated to other views. For example, in response to receiving input from a user selecting a record on chart 1405, an index, as discussed above, is analyzed to determine if the record is shown in another view (stage 1335). If the record is shown in another display (stage 1340), the visual representation of that record in the other view is altered (stage 1345). Fig. 16 is a diagram showing both (1) charts 1405 and 1430, and (2) a galaxy view 1605 of records. If a record is selected on map 1405, the record is highlighted in galaxy view 1605, and vice versa. Similarly, the group of records shown on map 1405 may be highlighted in galaxy view 1605 (as shown by 1610), and vice versa.

Fig. 17 describes another method of displaying information interactively, in the form of summary miniplots. The method begins with the user selecting a set of records and a set of attributes associated with those records (stage 1705). The attributes may comprise any of numerous data types, including the following: numeric, text, sequence (e.g., protein or

DNA sequences), or categoric. The selected attributes are converted into numerical values, as discussed above (stage 1710).

Next, a two-dimensional scatter chart is generated to visually depict the records (stage 1715). An example of such a chart is galaxy view 1805 shown in Fig. 18. Galaxy view 1805 contains a collection of records, one example of which is shown as 1810. The records within galaxy view 1805 are organized into groups (or clusters) (stage 1720), based on relationships between one record and another.

For each group shown in galaxy view 1805, a two-dimensional line chart (summary miniplot) is generated that depicts some information about the records contained within that group (stage 1725). Each such summary miniplot is superimposed onto the two-dimensional scatter chart, based on the location of the group of records on the scatter chart (stage 1730). For example, chart 1805 contains a group of records 1815, for which summary miniplot 1820 represents the average attribute values. In the example shown, summary miniplot 1820 is superimposed at the centroid coordinate for the records in group 1815.

In alternate implementations, summary miniplots may be used to represent other groupings of record. For example, the records shown in a scatter chart may be grouped into quadrants of the scatter chart; and four summary miniplots could be used to represent the quadrants. Furthermore, each line charts, such as line chart 1820, can also be coded in a variety of ways (e.g., size, color, thickness of lines, etc.) to represent additional information (e.g., the variability within the group's records, the value of an

unrelated field, etc.).

In addition to viewing the information in graphical form, the user can interact with the summary miniplots. The invention is capable of receiving input from a user selecting a summary miniplot (stage 1735). This may be
5 achieved, for example, by using a device to point to a portion of map 1805 or by clicking a pointing device on a portion of map 1105. In Fig. 18, the user input constitutes selecting group 1825, as shown by the fact that group 1825 is highlighted. In response to this user input, a graph is generated that contains a series of superimposed line charts, with each line
10 chart representing a record (stage 1740). An example of such a graph is shown in Fig. 18 as 1830, which is a series of superimposed line charts that represent attribute values for the records selected by the user in group 1825.

Furthermore, any selections made by the user of a summary
15 miniplot on chart 1805 is propagated to other views. For example, in response to receiving input from a user selecting summary miniplot 1820, an index, as discussed above, is analyzed to determine if the records represented by summary miniplot 1820 are shown in another view (stage 1745). If the records are shown in another display (stage 1750), the visual
20 representation of the records in the other view are altered (stage 1755). Similarly, if a user selects a record in another view, the summary miniplot corresponding to that record can be highlighted.

The preceding visualizations provide the opportunity to query records by attributes represented, e.g., by categorical and numerical values

and by sequence of text content. Because the visualizations support a limited number of queries, the visualizations cannot analyze large associations efficiently. A multiple query tool creates a visualization that provides an overview of a large number of comparisons automatically, presenting the user with information, e.g., about associations and their expectation. Further, the multiple query tool also provides information about associations between clusters and attributes as well as associations between sets of attributes.

Fig. 19 provides an illustration of a multiple query tool visualization according to the present invention. The multiple query tool produces a visualization in the form of an interactive matrix that displays the requested associations and permits access to the underlying information. For example, the multiple query tool can provide links back to other open visualizations and tools, or stand alone as a separate visualization.

Fig. 20 illustrates a process of creating a visualization using the multiple query tool. As shown in step 2010, the user accesses the multiple query in any common manner of a graphical user interface, for example, a tool bar button, a previous visualization menu, a pop-up box, or a main menu.

Visualization of data begins with the selection of a data file. As shown in step 2020, a user selects a data file of interest. Alternatively, the data file can be preselected, when, e.g., the multiple query visualization is linked to another visualization analysis.

After a data set is selected, as shown in step 2030, the user sets the

type of query. As shown in Fig. 21, a dialog box can be displayed to the user with a drop-down menu of query types. While Fig. 21 shows a selection between query types records vs. attributes, attributes vs. attributes, current data vs. historical data, and current data vs. expert data, other query types are within the scope of the invention. Once selected, the drop-down menu is rolled up to display only the selected query.

Upon selection of a query type, a dialog box specific to the query type is displayed so that the user can set the parameters of the query. Figs. 22A-4C display exemplary parameter-setting dialog boxes for query types shown in Fig. 21.

For example, Fig. 22A, a record vs. attributes query dialog box 2200 is displayed. In this query, records are correlated to selected attributes. In one of its aspects, the records can be viewed as clusters of the records, for example, as clusters such as those defined in the galaxy view of a previous visualization or those defined using any other process. Fig. 22A displays four attribute sources, although other sources could be displayed.

In attribute source area 2210, labeled 'Vocabulary Word(s),' of dialog box 2200, the user types in the word or words that serve as attributes. For multiple words, a delimiter, such as a semicolon, could be used to separate entries. Other processing could also intelligently separate the words. Also, logical operators, such as Boolean AND, OR, NOT, could be included to produce a single composite attribute.

Also, the user can identify attribute words by pointing to a text file that contains a list of words. The user can identify the text file in attribute

source area 2220, labeled 'Vocabulary File.' One format for this list would be a single keyword per line or a single phrase per line. With the text file, synonyms can also be identified. Vocabulary files including synonyms may have the following formats in one aspect of the present invention:

5 Format 1
 Keyword1: alt_word1A; alt_word1B
 Keyword2:
 Keyword3: alt_word3A

10 Format 2
 Keyword1
 - alt_word1A
 - alt_word1B
 Keyword2
15 Keyword3
 - alt_word3A

 The processing of the identified text file will operate on files of the format(s) of existing user files, so as to avoid issues of file format
20 conversion.

 Fig. 22A also illustrates attribute source areas 2230 and 2240 for categorical values. In attribute source area 2230, labeled 'Category Field(s),' the user types in the category or categories that serve as attributes. For multiple categories, a delimiter, such as a semicolon, could
25 be used to separate entries. Other processing could also intelligently separate the categories. Also, logical operators, such as Boolean AND, OR, NOT, could be included to act on categories to produce a single composite attribute. 2250 illustrates an area to access selectable menu of categories in the database, in the format of, e.g., a drop-down box. To
30 develop the menu, each record in the database is parsed to identify all possible categorical values.

In attribute source area 2240, labeled 'Category File,' the user can identify attribute categories by pointing to a text file that contains a list of categories. Selecting categories from a file enables the user to specify easily the order in which the categorical values would be displayed in the visualization and to allow the user to specify a hierarchy for those values.

One format for the categorical value file is:

	categorical_value_1	1	(tab delimited lines with value indicating
10	categorical_value_1.1	2	hierarchy level)
	categorical_value_2	1	
	categorical_value_2.1	2	
	categorical_value_2.2	2	
15	categorical_value_2.2.1	3	

Further, to collapse the number of attribute columns, the categories could be combined, similarly to the use of synonyms, or, for hierarchical categorical data, the user could select a maximum hierarchical level. As shown in step 2040 of Fig. 20, after the user selects the attributes, the database is queried using the multiple query. In step 2050, the results of the multiple query are used to create a query matrix.

For example, as shown in Fig. 23, from the attribute words or categories, the multiple query tool creates a query matrix of record rows and attribute columns. The cells of the matrix are set to binary values indicating the presence or absence of the attribute in each record. When a vocabulary file with synonyms is used, a single matrix cell should be created for each keyword, and the cell is marked if either the keyword or any of the alternate forms are found. One method of determining the presence of attribute would be to search the original data file or any indexed files describing the distribution of words or categorical values within the data set.

Following creation of the query matrix, the query matrix is visualized, in step 2060. One visualization is a binary, co-occurrence scheme, as shown in Fig. 24, where cells having a value of "1" are marked in a color or shade, 2410, while cells having a value of "0" are marked in a different color or shade, 2420. The user can select a size of cells, so that more cells or less cells are shown in a display of the visualization.

To minimize the display, the user can select a visualization based on cluster rows. When large numbers of records are to be analyzed, the cluster row visualization could be set as the default.

10 In this case, as shown in Fig. 25, the cells of the visualization matrix are set to indicate the presence or absence of the attribute in each record. To set the cell values, the query matrix is created or processed to create a composite value for a cell, for example, a basic scheme would involve summing the binary co-occurrence scores for a cluster and dividing by the number of records in the cluster.

When the matrix using cluster rows is visualized in step 2060, cells are colored or shaded to indicate their composite values. Fig. 25 shows a binary co-occurrence shading scheme that illustrates the query matrix of Fig. 23, if records 1 and 2, 3 and 4, and 5 and 6 are assumed to be in clusters 1, 2, and 3, respectively. To enhance the interactive nature of the visualization, as shown in Fig. 26, an overall visualization can be displayed as a three-dimensional view of the rows vs. columns vs. values, with the value of each cell represented by a cube at an appropriate height on the Z-axis. The overall visualization is rotatable, so that the user can view 2-D scatter plots corresponding to the rows and columns. A 2-D row scatter plot is shown in Fig. 27.

Another more complex visualization, however, serves as the default

when cluster rows are used. In this alternative visualization of cluster rows, the cells show association probabilities. The scheme of showing association probabilities would be to represent deviations as a difference from an expected value under a random distribution assumption. To
5 calculate expected values, the total number of records containing each attribute, or the sum of the columns of the query matrix, is computed. Lower than expected values could be, for example, cool colors (blue (= -1) to green) and higher than expected will be hot colors (inverted black body with red =1). Deviations from an expected value under a random
10 distribution assumption could also be represented as a ratio. Also, the probability of observing a number of attributes in a cluster of this size given this many total number of attributes are randomly distributed over all the clusters could also be represented. In this case, the values will range from 0 to 1 and the color display would have blue = 0, white = 0.5, and red = 1;
15 for example. To highlight extreme behaviors, the scale could be non-linear so that only the very high and very low probabilities are highlighted.

To compute association probabilities either an exact or approximate method is used for each of the association methods of the present invention. The exact method is precise at the cost of being computationally
20 intensive. The approximate method can reduce the number of computations when the total number of objects and total number of occurrences of the attributes are relatively large. Further, the use of the laws of logarithms to reduce products and quotients to sums and differences, respectively, and exponentiation to a product will also save
25 computing time.

The probability of observing what is observed given a random distribution indicates the possibility of observing certain number of occurrences of an attribute in a given cluster if the attribute is randomly distributed over all clusters. The lower the probability, the further the attribute distribution deviates from randomness. Described below are the exact method and approximate method for calculating this probability.

Equation 1 provides the exact method. Equation 1 is the discrete density function for a random variable having a hypergeometric distribution. The numerator consists of the product of two terms. The first term calculates how many ways to choose exactly m attributes out of M possible for the cluster of interest; the second term calculates the ways to assign the other (n-m) attributes which are not in the cluster of interest to the other clusters collectively. The denominator calculates the total number of ways to assign N objects to a cluster of size n.

$$p = \frac{\binom{M}{m} \binom{N-M}{n-m}}{\binom{N}{n}}$$

Equation 1.

where N : total number of objects in the data set

M : total number of occurrence of the attribute

n : number of objects in the given cluster

m : number of occurrences of the attribute in the given cluster

$$\binom{N}{n} = \frac{N!}{n!(N-n)!} : \text{combination number of } n \text{ out of } N.$$

Equation 2 provides the approximate method. Equation 2 is the discrete density function for a random variable having a binomial distribution, where the probability of a success is M/N and the probability of failure is $(1-M/N)$. When N and M are large, $(N-n)/(N-1)$ is close to one; thus, Equation 2 provides a reasonably good approximation to the hypergeometric distribution. N , M , n , and m denote the same quantities as defined above in Equation 1.

10

$$p = \binom{n}{m} \left(\frac{M}{N}\right)^m \left(1 - \frac{M}{N}\right)^{n-m} \quad \text{Equation 2.}$$

Alternatively, the association probability can be represented as a measure of an unusual number of occurrences, which is a deviation of observed occurrence from the expected occurrence if the attribute is randomly distributed over all clusters. An exact method (Equation 3) or an approximate method (Equation 4) can be used. N , M , n , and m denote the same quantities in Equation 1. Note that the expectation is the sum over the range of the random variable of x of x multiplies $p(x)$. Equation 3 uses hypergeometric distribution and Equation 4 uses a binomial method, similar to Equations 1 and 2, respectively. The exact method is very computationally expensive due to the summation, while summation in the approximate method can be calculated through and written into the simple form of Equation 4.

25

$$E = \sum_{k=1}^n k \frac{\binom{M}{k} \binom{N-M}{n-k}}{\binom{N}{n}}$$

Equation 3.

$$E = n \frac{M}{N}$$

Equation 4.

5

The deviation from expected occurrence can be measured using either ratio or difference of the observed number of occurrences over (or from) the expected number of occurrences. The range of the ratio is between zero and infinity. A ratio value further away from 1 indicates a larger deviation from randomness.

10

$$Dev = \frac{m}{E}$$

Equation 5.

15

Alternatively to make the deviation more comparable for various sizes of clusters, the difference between observed and expected occurrences is divided by the size of the cluster (Equation 6). Therefore, the range of this deviation measure is normalized between -1 and 1. A value further away from zero indicates a larger deviation from randomness.

20

$$Dev = \frac{m - E}{n}$$

Equation 6.

While the order of attributes along the columns and the order of rows or clusters along the columns of the matrix can be selected by the user,

using a menu item or by dragging rows and columns to new positions. For example, the order of the records or the order of the clusters is automatically set to same correlation order as known to those skilled in the art. The default display for attributes is based on correlation order, with the attribute having the highest column sum being on the left-hand side.

Thus, visualizations for the record vs. attributes query type is explained. The processing involved in creating the query matrix and visualization for the remaining query types is similar to the process of records vs. attributes query type.

If the user selects an attribute vs. attributes query type in step 230, as shown in Fig. 22B, an attributes vs. attributes query dialog box 2260 is displayed. The attributes vs. attributes query type is not interested in occurrences with specific records, only in defining the associations among attributes.

Query dialog box 2260 operates similarly to records vs. attribute query dialog box 2200, except that the user will be specifying two sets of attributes (vocabulary words or categories).

When querying the database in step 2040 and creating the query matrix in step 2050, the matrix cell scores are generated as a cumulative measure of the number of records that contain both test attributes. Then, the score should be normalized against the number of records. In other words, for n records, i row attributes, and j column attributes:

```

    for row_attribute = 1 to i
      for column_attribute = 1 to j
        score(i,j)=0
        for record=1 to n
5          if record contains both row_attribute(i) and column_attribute(j),
            then score(i,j)=score(i,j)+1
        next record
        norm_score(i,j)=score(i,j)/n
      next column_attribute
10    next row_attribute

```

Also, the total number of records that have each attribute is counted so that deviation from expected frequency can be calculated.

In step 2060, the attribute vs. attribute visualization follows the same
 15 mechanics as for records vs. attributes, but with a few differences. Specifically, in the default view for the attributes vs. attributes visualization, the default order for both axes would be the correlation order, with the column with the highest total score (e.g., the highest average value) on the top or left, and the default mode for showing associations uses deviation
 20 from expectation using with lower than expected values shown as cool colors (blue (= -1) to green) and higher than expected shown as hot colors (inverted black body with red =1).

Another use of the multiple query tool visualization is rapid
 assessment of the correlation between the current experiment being
 25 analyzed and historical data. Such a visualization points to the similarities or differences for all equivalent data points (record and condition).

As shown in Fig. 22C, a current data vs. historical data query dialog box 2270 is displayed when the user selects such a visualization. A file containing a data matrix is used as the historical data. In other words, the

user would select the files of a prior visualization. Alternatively, a data matrix, similar to those currently used to input data into the numerical engine, could be designated.

In step 2040, the method determines where the current and
5 historical experiments overlap. For example, if the current experiment contains records 1 through 10 and the historical experiment contains records 1 through 5 and records 8 through 12, then correlations would only be performed with the common records 1 to 5 and 8 to 10. Similarly, if the
10 current experiment used conditions (components) A through E (e.g., 5 time points or distinct treatments) and the historical experiment used conditions A, C, D, and F, then the correlation would be calculated only using the common conditions A, C, and D.

In step 2050, a query data matrix would then be created comparing the common entries. For record1, a correlation with the historical data set
15 would be performed using all the common conditions (intersection). In the example given, this would be a correlation between $\text{current_record1}(A,C,D)$ and $\text{historical_record1}(A,C,D)$. A similar score would be derived for each record present in both data sets. For a record in the current data set that is not present in the historical set, the query matrix would be blank (or set to
20 some flag). The calculations would be repeated for each historical set requested.

In step 2060, the query matrix is visualized as follows. The color code in each cell is based on the correlation of that record to its counterpart in the historical data. The correlation values will range from -1 to $+1$ and be

presented using, for example, a modified rainbow with negative correlations being cool colors (blue = -1) and positive correlations being hot colors (red = 1). For records that are not shared with the historical data set, the matrix cell should have no color (or be colored the same as the background) or, 5 alternatively, these cells can be hidden. If the cells not shared with the historical data set are shown, the degree of overlap between the current and the historical data sets can be visualized. This visualization could also be selected as a separate visualization that shows the overlap, for example by using a gray-scale color code in the matrix, where black 10 indicates full overlap with the historical data components and white indicates no overlap. This query type would also be useful with other data mining tools.

Instead of comparisons of the records of the current and historical data, cluster assignments from one experiment to the next, even when the 15 experiment types are quite different, can be compared. For each record in a current data cluster, the method can assess what fraction of other current cluster records exist in the same cluster in the historical set. Then, an average of the results from each current cluster record to is computed to get a score for that cluster. Another example assesses, for each record in 20 a current cluster, what fraction of other current cluster records are found in the historical data within x Euclidean distance. An interactive slider would allow the user to change x and the method would allow viewing of the results dynamically.

When records are combined into clusters, the overall value for the

cluster will be represented as the average or other statistical measure, such as median of the record correlations, based only on those records that are common between the data sets. An indication of variation is provided since a cluster that contains 10 records with a correlation of 0.8 and a
5 cluster that contains 10 records with a correlation of .9 and 1 with a correlation of -1 (both cluster with average of 0.8) may be of different interest to the user. Such an indication can be achieved using multiple visualizations, for example by duplicating the previous query, that simultaneously show the average and the standard deviation, the minimum
10 value or the maximum value.

The default order of clusters and records in this visualization should be the same as in the records vs. attributes query tool. In addition, a row is added that summarizes the comparison of the entire current data against each historical data set. For example, a row labeled "Summary" will be the
15 average of all record correlations.

Alternatively, the user or system could identify specific records to group together at the top of the visualization. For example, all the controls could be grouped together as opposed to in separate clusters. Also, while only one set each of current and historical data is used, several sets data
20 could be visualized contemporaneously. That is, any one of the data sets is treated as the prototype against which others are measured. A slider bar having each visualization would allow the user to run through multiple experiments. The progress through the slider (data sets) could be semiautomated to play like a movie, stopping whenever certain similarities

or dissimilarities are found.

The 'current data vs. literature/expert knowledge' query is similar to the other queries. Correlations between the current data and the literature or expert knowledge are defined either as what records have previously
5 been found to group together or as similarity to actual published/historical values.

Regardless of the query type, the visualization, as shown in Fig. 19, will be displayed in an interactive area of a display screen, so that the user may adapt the visualization to her preferences.

10 For example, to provide commands, the visualization could include a menu bar and a toolbar. A menu bar 1010, with associated sub-menus, of the visualization could include the features shown in Fig. 28.

The Duplicate command in the File menu of menu bar 2810 allows access to previously stored queries, so that the user can either re-run or
15 adjust a previously run multiple query. The other commands in the File order are self-explanatory.

The Row Order menu of menu bar 2810 provides option for organizing the records, clusters, or row attributes. The Cluster from View command results in a correlation ordering for the records and clusters (if
20 correlation ordering was not done for the view, then it is also not done here in the default), as discussed above this ordering is the default for a records vs. attributes query type or a current data vs. historical data query type.

The Correlation with Columns command is an option for recalculating the cluster order based on the values in the query matrix. In a cluster view,

records would remain with their cluster and the clusters are reordered according to correlation ordering. If a cluster was expanded to show records, the records in the cluster would be reordered according to correlation ordering. As discussed above, for an attributes vs. attributes
5 query, correlation with columns is the default.

The Advanced sub-menu of the Row Order menu allows access to the following commands. The Cluster Based on Column Values command recalculates the clustering of the records or the attributes using the scores along the row as the vectors for clustering. The user would have the
10 choice of using any clustering algorithm, such as either the hierarchical or partition methods. The Sum command is an option to order the records or attributes based on the sum of the scores across the row, with the record/attribute with the highest sum being at the top and the lowest being at the bottom, for example. Rows having a value below a predetermined
15 threshold could be placed in a low value row or removed from the visualization matrix. The Sum command is not valid for visualization using clusters and would be deactivated. The File Order sets the order of clusters or attributes to that specified by the user, for example in an input file. If no file is provided or record rows are selected, this option would be
20 deactivated.

The Column Order menu of menu bar 2810 provides analogous options as the Row Order menu for organizing the column attributes, expect that there will be no clustering from the view, as records and clusters do not appear in the columns, in one aspect of the present

invention.

To provide the user the ability to choose a custom coloring scheme, the Color menu of menu bar 2810 permits a selection of display colors within the multiple query tool.

5 A tool bar is also provided in the visualization, either as a separate pop-up area or a bar, for example, located below a status bar, to provide access to functions with a single click. Fig. 29 illustrates examples of functions of a tool bar.

The RecordViewer function displays the currently highlighted record
10 (or records in the highlighted cluster). For a record vs. attribute cell, this shows the single record with the specific attribute highlighted in the record. For a cluster vs. attribute cell, the RecordViewer shows all the records in that cluster with the specific attribute highlighted in the records. For an attribute vs. attribute cell, the RecordViewer would display all records that
15 contain both attributes, with both attributes highlighted. To access the records, the RecordViewer calls a process that parses the data source file in the galaxy cluster view. An interpretation tool, such as the plot data tool, could also be provided. A double click on a cell can also call the RecordViewer function.

20 The Zoom function operates similarly to a zoom in the galaxy visualization. Primarily, the zoom will zoom out, so that an overview of a large multiple query tool can be obtained. The maximum zoom out should be based on the number of records and a user's desired minimum resolution, so that the colors of the visualization will be readily discernable.

A possible default size for a cell in the multiple query tool is 12 by 12 pixels. This is large enough to display text labels at 10 point Helvetica for both rows and columns. Zooming out would provide an overview for large data sets. The Zoom Reset function returns the visualization to its default size.

5 The Pan function takes the form of a hand and allows the user to drag the graphic around the window, so that area hidden by display objects or the physical dimensions of a display screen can be viewed. Scroll bars, as shown in the multiple query tool above, could be employed instead of, or in addition to, the Pan tool. Nevertheless, labels for the rows and columns
10 would always remain visible.

 The Expand Row Clusters and Expand Column Clusters functions open the selected cluster(s) to display all their records or attributes as separate rows. If no clusters are selected, all clusters are expanded. If no clusters are defined (either from the associated view or by having done a
15 cluster ordering within the multiple query tool), these functions are deactivated.

 The Collapse Row Clusters and Collapse Column Clusters functions closes the cluster that contains the selected record(s) or attribute(s). If no record or attribute is selected, all clusters are collapsed. If no clusters are
20 defined (either from the associated view or by having done a cluster ordering within the multiple query tool, these functions are deactivated. Although not illustrated in Fig. 29, a single button could also collapse all row and columns with a deviation from expectation between, e.g., -.5 and +.5 (or other definable range) into a single group or remove rows and

columns that do not have values above a predetermined threshold.

The Orient Rows vs. Values and Orient Columns vs. Values functions orient the visualization so that the view is perpendicular to the row axis or column axis, respectively. This provides views of the 2-D scatterplot, as shown in Fig. 27, for example. The Reset Orientation function orients the visualization to the default 'overhead' view showing rows vs. columns.

The Spacing Toggle function toggles the matrix between the two types of views shown in Figs. 30A and 30B. Providing a grid as shown in Fig. 30A allows viewing of cells as discrete entities, for easier selection. Removing the grid, as shown in Fig. 12B, allows more information to be compressed into the same space and could improve enhance structure distinctions in the visualization matrix.

In addition to the command bars, the visualization area itself, as shown in Fig. 19, consists not only of the colored visualization matrix, but also includes labels for the rows and columns.

When the rows are records, the row labels are the record titles. Since record titles may be long, the initial substantially 20 characters could be displayed with a scroll bar or pop-up function to enable viewing of all of the characters. When collapsed into clusters, the row labels are labeled by cluster number. For attributes, the categorical value or vocabulary word itself serve as the label. In addition to the labels themselves, the rows and columns could have a master label indicating the content. For records as rows, the label would say "RECORDS." For vocabulary words input

directly in the initial dialog box, the label would be "VOCABULARY". For vocabulary words input through a file, the label would be the file name. For categories as attributes, the field name would be shown. If multiple fields were requested, each field name would be shown, centered over its
5 collection of row or column labels. The user could also edit or define the row, column, and major labels.

Rows and columns are selected and highlighted by clicking on the row and column labels using a mouse input device, for example. Shift-clicking and control-clicking can be used to select multiple labels.

10 The visualization is interactive. In addition to highlighting labels for selecting rows and columns, clicking on a cell should display key information regarding the cell. This pop-up information would be context sensitive, depending on the type of query and whether the cell represents an individual record or attribute as opposed to a cluster or group. The
15 following provide suggested formats of the key attributes of a cell of the different groups and query types:

For a cell intersecting a record and attribute in a records vs. attributes query:

20 Row: Record_name
Column: Column_attribute_name
Co-occurrence: 0 (or 1)
Attribute found in ##/total_rows records

25 For a cell intersecting a cluster and attribute in a records vs. attributes query:

Row: Cluster# containing ## members
Column: Column_attribute_name
Co-occurrences: ##
Number of co-occurrences expected: ##
30 Deviation from expected co-occurrence: ##
Probability of observation: ##

For a cell intersecting an attribute and attribute in an attributes vs. attributes query:

5 Row: Row_attribute_name
 Column: Column_attribute_name
 Co-occurrences: ##
 Row attribute found in ##/total_columns columns
 Column attribute found in ##/total_rows rows
 Number of co-occurrences expected: ##
 Deviation from expected co-occurrence: ##
 10 Probability of observation: ##

For the cell intersecting a record and historical data in a current data vs. historical data query:

15 Probability of observation: ##
 Row: Record_name
 Column: historical_experiment_name
 Correlation: ## (if this record does not intersect with historical data, 'no intersection')

20 For the cell intersecting a cluster and historical data in a current data vs. historical data query:

Probability of observation: ##
 Row: Record_name
 25 Column: historical_experiment_name
 Average Correlation: ## (if this cluster does not contain any genes that intersect with historical data this should say 'no intersection')
 Maximum Correlation: ## with record_name
 Minimum Correlation: ## with record_name
 30 Records that do not intersect historical data (could be a scrollable list):
 record_name1
 record_name5...

35 CONCLUSION

Systems and methods consistent with the present invention employ an open architecture that enables different types of data to be used for analysis and visualization.

40 It will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the invention.

Modifications may be made to adapt a particular element, technique, or implementation to the teachings of the present invention without departing from the spirit of the invention. For example, any genetic material, from organism to microbe, could be represented using the context
5 vectors of the present invention. Further, the present invention is not limited to genetic material, and any material or energy could also be represented. Additionally, the rows and columns used in the description are illustrative only, and, for example, records could be placed along the columns. Also, the attributes used are not limited to text and categorical
10 features. Numerical values could be set as attributes, for example using binning where adjacent ranges of numbers are defined. Additionally, for queries against individual records, categorical data could be presented in a single column rather than multiple columns for each categorical value as described above; in this case, the occurrence of a specific categorical value
15 could be represented as a specific color. The resulting matrix could also be dynamically controllable by the user. The order of rows or columns could be adjusted by dragging or sorted according to the information within the row or column.

Moreover, although the described implementation includes software,
20 the invention may be implemented as a combination of hardware and software or in hardware alone. Additionally, although aspects of the present invention are described as being stored in memory, one skilled in the art will appreciate that these aspects can also be stored on other types of computer-readable media, such as secondary storage devices, like hard
25 disks, floppy disks, or CD-ROM; a carrier wave from the Internet; or other forms of memory.

Therefore, it is intended that this invention not be limited to the

particular embodiment and method disclosed herein, but that the invention include all embodiments falling within the scope of the appended claims.

APPENDIX A**Example Data Set Properties File**

```
CORPUS_TYPE=1
5 VIEW=protein.aa\ gene.expression
  source_file_0.com.bmi.vision.api.FastaDataFile.format=
  source_file_class_0=com.bmi.vision.api.FastaDataFile
  source_file_0.
  com.bmi.vision.api.FastaDataFile.fullpath=/home/battelle/omniviz_dat
10 a/sources/yeast.fasta
  number_sources=1
```

APPENDIX B

>MJ0001 aspartate aminotransferase

5 MISSRCKNIKPSAIREIFNLATSDCINLGIGEPDFDTPKHIIEAAKRALDEGKTHYSPNN
 GIPELREEISNKLKDDYNLDVDKDNIIVTCGASEALMLSIMTLIDRGDEVLIIPNPSFVS
 FSLTEFAEGKIKNIDLDENFNIDLEKVKESITKTKKLIIFNSPSNPTGKVYDKETIKGLA
 EIAEDYNLIIVSDEVYDKIIYDKKHYSMPQFTDRCILINGFSKTYAMTGWRIGYLAVSDE
 LNKELDLINMIKIHQYSFACATTFAQYGALAALRGSOQKCVEDMVREFKMRRDLIYNGLK
 10 DIFKVNKPDGAFYIFPDVSEYGDGVEVAKKLIENKVLCPVGVAFGENGANYIRFSYATKY
 EDIEKALGIIKEIFE

>MJ0002

MEIFMEVPPIFVVISGSDLYGIPNPSDVDIRGAHILDRELFIKNCLYKSKEEEVINKMFGK
 CDFVSFELGKFLRELLKPNANFIEIALSDKVLYSSKYHEDVKGIAYNCKICKLYHHWKG
 AKPLQKLCEKESYNNPKTLLYLRAYYQILCLESGEFKSDFSSFRCLDCYDEDIVSYLF
 15 ECKVNKKPVDESYPKKIKSYFYELGVLLDESYKNSNLIDEPSETAKIKATELYKKLYFED
 VRE

>MJ0003

MKGKRIAIIVSHRILNQNSVVNGLERAEGAFNEVEILLKNNGYIIQLPCPELIYLGIDRE
 GKTKEEYDTKEYRELCKKLEPIIKYLQEYKKNYKFIILIGIENSTTCDFKNRGILMEE
 20 FFKEVEKLNIIKAIEYKNEKDYKFKVKTLEKMIK

>MJ0004 activator of (R)-2-hydroxyglutaryl-CoA dehydratase

MILGIDVGSTTTKMVLMEDSKIWIYKIEDIGVVEEDILLKMVKEIEQKYPIDKIVATGY
 GRHKVSFADKIVPEVIALGKGANYFFNEADGVIDIGGQDTKVLKIDKNGKVVDLSDKC
 AAGTGKFLKALDILKIDKNEINKYKSDNIAKISSMCAVFAESEIISLLSKVPKEGILM
 25 GVYESIINRVIPMTNRLKIQNIVFSGGVAKNKVLVEMFEKKLNKKLLIPKEPQIVCCVGA
 ILV

>MJ0005 formate dehydrogenase, beta subunit

MKYVLIQATDNGILRRAECGAVTALFKYLLDKKLVLDGVLALKRGEDVYDGIPTFITNSN
 ELVETAGSLHCAPTNFGKLIKYLADKKIAPPAKPCDAMAIKRELAKLNQINLDNVYMI
 30 NCGGTISPITAMKMIELFYEVNPLDVVKEIDKGFIIELKNGEHKAVKIEELEBKGFGR
 RKNQCRCEIMIPRMADLACGNWGAEGKWTVEICSERGRKLVEDAEKDGYYIKIQPSEKA
 IQVREKIESIMIKLAKKFQKKHLEEEYPSLEKWKYWNRCIKCYGCRDNCPLCFVECSL
 EKDYIEBKGIKPPNPLIFQGIKSHISQSCINCGQCEDACPMDIPLAYIFHRMQLKIRDT
 LGYIPGVDNSLPPLFNIER

>MJ0006 formate dehydrogenase, alpha subunit

MKVVHTICPGCSVCGIDLIVKDDKVVGTYPYKRHPINEGKNCSNGKNSYKIIYHEKRLK
 KPLIKKNGKLVEATWDEALSFAEKLKNYNADITFIASGKCTNEDNYALKKLVDLSLAK
 35 IGHCICNSPKVNYAEVSTTIDDIENAKNIIIGDVPSEHALIGRKVIKAKEKGSKVTIFN
 TEEKEILKLNADDEFVKVDSYLGVDLSNVDKNTIIINAPVNVDEIIKTAKENKAKVLPVA
 KHCNTVGTATLIGIPALNKDEYFELLKNSKFLYIMGENPALVDKDLKNVEFLVVQDIIMT
 40 ETAEMADVLPSTCWAEEKDGTFTINTDKRIQKINKAVNPPGDAMDDWLIKSLAEKLGSD
 GFNSLEDIQQDIHRNKL

>MJ0007 2-hydroxyglutaryl-CoA dehydratase, subunit beta

MMKLKAIEKLMQKFASRKEQLYKQKEEGRKVFGMFCAYVPIEIIAANAIPVGLCGGKND
 45 TIPIAEEDLPRNLCPLIKSSYGFKAKTCPYFEASDIVIGETTCEGKKKMFELMERLVPM
 HIMHLPKMKDEDSLKIWIKEVEKLKELVEKETGNKITEEKLKETVDKVNKVRELFYKLYE
 LRKNKPAPIKGLDVLKLFQFAYLLDIDDITIGILEDLIEELEERVKKGEYEGKRILITGC
 PMVAGNNKIVEIIIEVGGVVVGEESCTGRFFENFVEGYSVEDIAKRYFKIPACRFRKND
 ERVENIKRLVKELDVDGVVYYTLQYCHTFNIEGAKVEEALKEEGIPRIIETDYSSESRE
 50 QLKTRLEAFIEMI

>MJ0008

MFCGSMIAICMRSKEGFLFNNKLMWGLHYNPKIVKDNNIIGYHAPILDLDKKESIIILK
 NIIENIKGRDYLTIIHLNGKYGKINKETLIENLSIVNEFAEKNGIKLCIENLRKGFSSNP
 NNIIIEIADEINCYITFDVGHIPYNRRLEFLEICSDRVYNSHVYEIEVDGKHLPPKNLNNL
 55 KPILDRLLDIKCKMFLIELMDIKEVLRTERMLKDYLEMYR

>MJ0009

MIFNENTPNFIDFKESFKELPLSDETFKIIENGKIKLREIAIGEFSGRDSVAAIIKAIEE

GIDFVLPVVAFTGTDYGNINIFYKNWEIVNKRIKEIDKDKILLPLHFMFEPKLWNALNGR
WVVLSPFKRYGYRRCIGCHAYLRIRIPLAKHLGGKIIISGERLYHNGDFKIDQIEEVLNV
YSKICRDFDVELILPIRYIREGKKIKEIIGEEWEQGEKQFSCVFSGNYRDKDGKVIDKE
GILKMLNEFIYPASVEILKEGYKGNFNLYLNIVKKLI
5 >MJ0010 phosphonopyruvate decarboxylase ~
MRAILILLDGLGDRASEILNNKTPLQFAKTPNLDRLAENGMCGLMTTYKEGIPLGTEVAH
FLLWGYSLEEFPGRGVIEALGEDIEIEKNAIYLRASLGFVKKDEKGFLVIDRRTKDISRE
EIEKLVDLSLPTCVDGYKFELFYSDVHFILKIKERNGWISDKISDSDPFYKNRYVMKVKA
IRELCKSEVEYSKAKDTARALNKYLLNVYKILQNHKINRKRKLEKMPANFLLTKWASRY
10 KRVESFKEKWGMNAVILAESSLFKGLAKFLGMDFIKIESFEEGIDLIPELDYDFIHLHTK
ETDEAAHTKNPLNKVKVIEKIDKLIGNLKLREDDLLITADHSTPSVGNLIHSGESVPIL
FYGKNVRVDNVKEFNEISCSNGHLRIRGEELMHLILNYTDRALLYGLRSGDRLRYIIPKD
DEIDLLEG

APPENDIX C

RECORDKEY

5

TITLE: Effect of metabisulphite on sporulation and alkaline phosphatase in *Bacillus subtilis* and *Bacillus cereus*

DATE: 1990

10

The effect of metabisulphite on spore formation and alkaline phosphatase activity/production in *Bacillus subtilis* and *Bacillus cereus* was investigated both in liquid and semi-solid substrates. While supplementary nutrient broth (SNB) and sporulation medium (SM) were used as the liquid growth media, two brands of powdered milk were used as the food (semi-solid) substrates. Under both aerobic and anaerobic conditions, *B. subtilis* was more resistant to metabisulphite than *B. cereus* while the level of enzyme production and spores formed were generally higher under aerobic than anaerobic conditions. The metabisulphite concentrations required to inhibit spore production as well as alkaline phosphatase synthesis/activity were found to be relatively low and well within safety levels for human consumption. It is concluded that metabisulphite is an effective anti-sporulation agent and a recommendation for its general use in semi-solid and liquid foods is proposed.

25

RECORDKEY

TITLE: Effects of replacing saturated fat with complex carbohydrate in diets of subjects with NIDDM

30

DATE: 1989

This study examined the safety of an isocaloric high-complex carbohydrate low-saturated fat diet (HICARB) in obese patients with non-insulin-dependent diabetes mellitus (NIDDM). Although hypocaloric diets should be recommended to these patients, many find compliance with this diet difficult; therefore, the safety of an isocaloric increase in dietary carbohydrate needs assessment. Lipoprotein cholesterol and triglyceride (TG, mg/dl) concentrations in isocaloric high-fat and HICARB diets were compared in 7 NIDDM subjects (fat 32 +/- 3%, fasting glucose 190 +/- 38 mg/dl) and 6 nondiabetic subjects (fat 33 +/- 5%). They ate a high-fat diet (43% carbohydrate; 42% fat, polyunsaturated to saturated 0.3; fiber 9 g/1000 kcal; cholesterol 550 mg/day) for 7-10 days. Control subjects (3 NIDDM, 3 nondiabetic) continued this diet for 5 wk. The 13 subjects changed to a HICARB diet (65% carbohydrate; 21% fat, polyunsaturated to saturated 1.2; fiber 18 g/1000 kcal; cholesterol 550 mg/day) for 5 wk. NIDDM subjects on the HICARB diet had decreased low-density lipoprotein cholesterol (LDL-chol) concentrations (107 vs. 82, P less than .001), but their high-density lipoprotein cholesterol (HDL-chol) concentrations, glucose, and body weight were unchanged. Changes in total plasma TG concentrations in NIDDM subjects were heterogeneous. Concentrations were either unchanged or had decreased in 5 and increased in 2 NIDDM subjects. Nondiabetic subjects on the HICARB diet had decreased LDL-chol (111 vs. 81, P less than .01) and unchanged HDL-chol and plasma TG concentrations). (ABSTRACT TRUNCATED AT 250 WORDS)

55

RECORDKEY

TITLE: Enteral feeding of dogs and cats: 51 cases (1989-1991)

DATE: 1992

- 5 Feeding commercial enteral diets to critically ill dogs and cats via nasogastric tubes was an appropriate means for providing nutritional support and was associated with few complications. Twenty-six cats and 25 dogs in the intensive care unit of our teaching hospital were evaluated for malnutrition and identified as candidates for nutritional support via nasogastric tube. Four commercial liquid formula diets and one protein supplement designed for use in human beings were fed to the dogs and cats. Outcome variables used to assess efficacy and safety of nutritional support were return to voluntary food intake, maintenance of body weight to within 10% of admission weight, and complications associated with feeding liquid diets. Sixty-three percent of animals experienced no complications with enteral feedings; resumption of food intake began for most animals (52%) while they were still in the hospital. Weight was maintained in 61% of the animals (16 of 26 cats and 15 of 25 dogs). Complications that did occur included vomiting, diarrhea, and inadvertent tube removal. Most problems were resolved by changing the diet or adhering to the recommended feeding protocol. Nutritional support as a component of therapy in small animals often is initiated late in the course of the disease when animals have not recovered as quickly as expected. If begun before the animal becomes nutrient depleted, enteral feeding may better support the animal and avoid serious complications.

- 30 TITLE: Microbiology of fresh and restructured lamb meat: a review
DATE: 1995

- Microbiology of meats has been a subject of great concern in food science and public health in recent years. Although many articles have been devoted to the microbiology of beef, pork, and poultry meats, much less has been written about microbiology of lamb meat and even less on restructured lamb meat. This article presents data on microbiology and shelf-life of fresh lamb meat; restructured meat products, restructured lamb meat products, bacteriology of restructured meat products, and important foodborne pathogens such as Salmonella, Escherichia coli 0157:H7, and Listeria monocytogenes in meats and lamb meats. Also, the potential use of sodium and potassium lactates to control foodborne pathogens in meats and restructured lamb meat is reviewed. This article should be of interest to all meat scientists, food scientists, and public health microbiologists who are concerned with the safety of meats in general and lamb meat in particular.

RECORDKEY

- 50 TITLE: Hyperacute stroke therapy with tissue plasminogen activator
DATE: 1997

- The past year has seen tremendous progress in developing new therapies aimed at reversing the effects of acute stroke. Thrombolytic therapy with various agents has been extensively studied in stroke patients for the past 7 years. Tissue plasminogen activator (t-PA) received formal US Food and Drug Administration approval in June 1996 for use in patients within 3 hours of onset of an ischemic stroke. Treatment with t-PA improves

neurologic outcome and functional disability to such a degree that, for every 100 stroke patients treated with t-PA, an additional 11-13 will be normal or nearly normal 3 months after their stroke. The downside of t-PA therapy is a 6% rate of symptomatic intracerebral hemorrhage (ICH) and a 3% rate of fatal ICH. Studies are under way to determine whether t-PA can be administered with an acceptable margin of safety within 5 hours of stroke, to evaluate the therapeutic benefits of intraarterial pro-urokinase, and to assess the use of magnetic resonance spectroscopy to identify which patients are most likely to benefit from thrombolysis. Combination thrombolytic- neuroprotectant therapy is also being studied. In theory, patients could be given an initial dose of a neuroprotectant by paramedics and receive thrombolytic therapy in the hospital. We are now entering an era of proactive, not reactive, stroke therapies. These treatments may reverse some or all acute stroke symptoms and improve functional outcomes.

RECORDKEY

20 TITLE: A 12-month study of policosanol oral toxicity in Sprague Dawley rats

DATE: 1994

25 Policosanol is a natural mixture of higher aliphatic primary alcohols. Oral toxicity of policosanol was evaluated in a 12-month study in which doses from 0.5 to 500 mg/kg were given orally to Sprague Dawley (SD) rats (20/sex/group) daily. There was no treatment-related toxicity. Thus, effects on body weight gain, food consumption, clinical observations, blood biochemistry, hematology, organ weight ratios and histopathological findings were similar in control and treated groups. This study supports the wide safety margin of policosanol when administered chronically.

30

APPENDIX D

```

NAME= NumericEngine
DESC= Format for source file produced by numeric engine.
END_DESC
5  DELIMITER= RECORDKEY

||F0
  NAME= Title
  TYPE= STRING
10  TAG= TITLE:
  METHOD= LINES:1
  DOC_VECTOR= TRUE
  SEARCH= TRUE
  CORR= FALSE
15  CASE_SENSITIVE= TRUE
  WHOLE_BOUNDARY= FALSE
  LINEPOS= FLOAT
||F1
  NAME= Components
20  TYPE= STRING
  TAG= COMPONENTS:
  METHOD= LINES:1
  DOC_VECTOR= TRUE
  SEARCH= FALSE
25  CORR= FALSE
  CASE_SENSITIVE= TRUE
  WHOLE_BOUNDARY= FALSE
  LINEPOS= FLOAT
||F2
30  NAME= ChipData
  TYPE= NUMERIC
  TAG= ChipData:
  METHOD= LINES:1
  DOC_VECTOR= FALSE
35  SEARCH= FALSE
  CORR= FALSE
  CASE_SENSITIVE= FALSE
  WHOLE_BOUNDARY= FALSE
  LINEPOS= FLOAT
40  ||F3
  NAME= SGD_Name
  TYPE= STRING
  TAG= SGD_Name:
  METHOD= NEXT_TAG
45  DOC_VECTOR= TRUE
  SEARCH= TRUE
  CORR= FALSE
  CASE_SENSITIVE= TRUE
  WHOLE_BOUNDARY= FALSE
50  LINEPOS= FLOAT
||F4
  NAME= Description
  TYPE= STRING
  TAG= Description:
55  METHOD= NEXT_TAG
  DOC_VECTOR= TRUE

```

```
SEARCH= TRUE
CORR= FALSE
CASE_SENSITIVE= TRUE
WHOLE_BOUNDARY= FALSE
5 LINEPOS= FLOAT
  ||F5
    NAME= Location
    TYPE= STRING
    TAG= Location:
10  METHOD= NEXT_TAG
    DOC_VECTOR= TRUE
    SEARCH= TRUE
    CORR= FALSE
    CASE_SENSITIVE= TRUE
15  WHOLE_BOUNDARY= FALSE
    LINEPOS= FLOAT
  ||F6
    NAME= Deletion
    TYPE= STRING
20  TAG= Deletion:
    METHOD= NEXT_TAG
    DOC_VECTOR= TRUE
    SEARCH= TRUE
    CORR= TRUE
25  CASE_SENSITIVE= TRUE
    WHOLE_BOUNDARY= FALSE
    LINEPOS= FLOAT
  ||F7
    NAME= Peak
30  TYPE= STRING
    TAG= Peak:
    METHOD= NEXT_TAG
    DOC_VECTOR= TRUE
    SEARCH= TRUE
35  CORR= TRUE
    CASE_SENSITIVE= TRUE
    WHOLE_BOUNDARY= FALSE
    LINEPOS= FLOAT
  ||F8
40  NAME= MCB_sites
    TYPE= STRING
    TAG= MCB_sites:
    METHOD= NEXT_TAG
    DOC_VECTOR= TRUE
45  SEARCH= TRUE
    CORR= TRUE
    CASE_SENSITIVE= TRUE
    WHOLE_BOUNDARY= FALSE
    LINEPOS= FLOAT
50  ||F9
    NAME= SFF_sites
    TYPE= STRING
    TAG= SFF_sites:
55  METHOD= NEXT_TAG
    DOC_VECTOR= TRUE
    SEARCH= TRUE
    CORR= TRUE
```

```

CASE_SENSITIVE= TRUE
WHOLE_BOUNDARY= FALSE
LINEPOS= FLOAT
||F10
5  NAME= Swi5e_sites
   TYPE= STRING
   TAG= Swi5e_sites:
   METHOD= NEXT_TAG
   DOC_VECTOR= TRUE
10 SEARCH= TRUE
   CORR= TRUE
   CASE_SENSITIVE= TRUE
   WHOLE_BOUNDARY= FALSE
   LINEPOS= FLOAT
15 ||F11
   NAME= Sequence_
   TYPE= STRING
   TAG= Sequence_:
   METHOD= NEXT_TAG
20 DOC_VECTOR= TRUE
   SEARCH= TRUE
   CORR= FALSE
   CASE_SENSITIVE= TRUE
   WHOLE_BOUNDARY= FALSE
25 LINEPOS= FLOAT
```

V. WHAT IS CLAIMED IS:

1. A method for analyzing data for different data types,
comprising:

5 selecting a set of attributes associated with an object, the
attributes selection from the group consisting of any of the text, numerical,
categorical, or sequence data types;

transforming the selected attributes into n-dimensional
vectors;

10 applying transformation operations to the selected attributes;
indexing the n-dimensional vector, certain attributes, and a
result of the transformation operations; and

displaying a representation of the object based on the
selected attributes.

2. A computer-implementing method of analyzing various data
15 types, comprising the steps of:

defining a uniform data structure for representing objects of
different data types;

20 segmenting certain attributes of a plurality of different objects
of different data types into elements that are representable in said uniform
data structure; and

operating on said certain attributes to produce at least one
representation of said objects based on said uniform data structure.

3. The method of claim 2 wherein said plurality of different data
types comprises a combination of any two of numeric, sequence string,

categorical, or text data types.

4. The method of claim 3 wherein said plurality of different data types comprise a combination of any three of numeric, reference string, categorical, in text data types.

5 5. The method of claim 4 wherein said data types comprise numeric, sequence string, categorical and text data types.

6. The method of claim 2 wherein said step of operating on said selected attributes produces a vector representation of said objects in correspondence with said uniform data structure.

10 7. The method of claim 2 further comprising producing an index that includes second representations of non-selected attributes of a particular object and associating the non-selected attributes with a particular representation of said first representations.

8. The method of claim 6 wherein said first and second
15 representations are vector representations.

9. The method of claim 2 further comprising using a first set of said selected attributes associated with a first set of objects to determine the relationships among the first set of objects of a particular data type and using non-selected attributes associated with said first set of selected
20 attributes to correlate objects represented by said first set of selected attributes with a second set of objects represented by a second set of selected attributes.

10. The method of claim 9 further comprising identifying, using said non-selected attributes, at least one object of said second set of

objects that corresponds to a selected object or objects of said first set of objects.

11. The method of claim 10 further comprising displaying said first and second set of objects in first and second windows on a display screen and highlighting said second set of objects that corresponds to said selected object or objects.

12. The method of claim 2 wherein said step of segmenting comprises creating a plurality of said elements from a sequence of string sequence data.

13. The method of claim 12 wherein said step of segmenting comprises selecting words of a text document that meet certain preselected criteria.

14. The method of claim 2 further comprises using said first representation to identify cluster groups of related objects.

15. The method of claim 2 further comprising creating two dimensional projections of cluster groups for two dimensional visualizations.

16. A method of identifying relationships among different visualizations of data sets, comprising the steps of:

displaying first graphical results of a first type analysis performed on selected attributes of on a first set of objects;

displaying second graphical results of a second type analysis performed on selected attributes of a second set of objects;

selecting certain objects represented in said first graphical

results; and

highlighting corresponding objects represented by said
second graphical results that correspond to said certain objects.

17. The method of claim 16 wherein said step of highlighting is
5 based on attributes not used for creating said first graphical results.

18. The method of claim 17 wherein said first and second set of
objects is the same.

19. A system for producing visualizations for various data types,
comprising:

10 a first data processing engine operative to receive different
types of data;

a second data processing engine operative to modify a first
type of said data to conform said data to a standardized format that is used
in identifying relationships among attributes of objects contained in said
15 data; and

a third processing engine for creating a first high dimensional
vector for a second type of data and for creating a second high dimensional
vector for the modified data, each data type being an input into said engine,
wherein said high dimensional vectors are operative to be compared to
20 identify relationships that exist between the first and second data type.

20. A method of interactively displaying records and their
corresponding attributes, comprising:

generating a first 2-D chart for a first record, wherein at least
two attributes associated with the first record are shown along one axis,

and wherein the values of the attributes are shown along the other axis;

receiving input from a user selecting the first record on the
first 2-D chart;

analyzing an index to determine if the first record is shown in
5 another view; and

if the first record is shown in another view, altering the
visual representation of the first record in the another view based on the
user input.

21. The method of claim 20, wherein the first 2-D chart is a line
10 chart.

22. The method of claim 20, wherein the first 2-D chart is a
scatter chart.

23. The method of claim 20, wherein the user can select the
scale of the axes.

15 24. The method of claim 20, wherein the another view comprises
a galaxy view of groups of records.

25. The method of claim 20, further comprising generating a
second 2-D chart for a second record, wherein at least two attributes
associated with the second record are shown along one axis, and wherein
20 the values of the attributes are shown along the other axis.

26. The method of claim 25, wherein the first 2-D chart is shown
in a first color and the second 2-D chart is shown in a second color.

27. The method of claim 25 wherein the second 2-D chart is
superimposed upon the first 2-D chart.

28. The method of claim 25, further comprising:
displaying text-based descriptions of the first and second
records;
receiving input from the user selecting a text-based
5 description; and
highlighting the 2-D chart of the record corresponding to the
selected description.
29. The method of claim 25, further comprising:
displaying text-based descriptions of each attribute shown in
10 the first and second 2-D charts;
receiving input from the user selecting a text-based
description; and
highlighting the attributes and values in the 2-D chart that
correspond to the description.
- 15 30. The method of claim 25, further comprising generating a third
2-D chart, wherein at least two attributes associated with the first and
second records are shown along one axis, and wherein statistical values of
the attributes are shown along the other axis.
- 20 31. The method of claim 30, wherein the statistical values
comprise average values.
32. The method of claim 30, wherein the statistical values
comprise median values.
33. The method of claim 20, further comprising displaying a text-
based identification of the record selected by the user.

34. The method of claim 33, further comprising:
receiving input from a user pointing to a portion of the 2-D
chart; and
displaying a text-based identification of the attribute and value
5 corresponding to the pointed portion.
35. The method of claim 20, further comprising:
receiving input from a user selecting a record in another view;
analyzing an index to determine if the record is shown in the
2-D line chart; and
10 if the record is shown in the 2-D line chart, altering the visual
representation of the record in the 2-D line chart.
36. A method of interactively displaying records and their
corresponding attributes, comprising:
selecting a record and its associated attributes, wherein the
15 associated attributes are any combination of numeric, categoric, sequence,
and text information;
converting the associated attributes into numeric values; and
generating a 2-D chart for the record, wherein at least two
attributes associated with the record are shown along one axis, and
20 wherein the values of the attributes are shown along the other axis.
37. A method of interactively displaying records and their
corresponding attributes, comprising:
generating a 2-D scatter chart that depicts a plurality of
records;

generating a 2-D line chart for a group of records contained in a portion of the 2-D scatter chart, wherein at least two attributes associated with the group of records are shown along one axis, and wherein a statistical value for each of the at least two attributes is shown along the other axis; and

superimposing the 2-D line chart at a location on the 2-D scatter chart that is based on the location of the group of records on the 2-D scatter chart.

38. The method of claim 37, wherein the statistical value is an average value.

39. The method of claim 37, wherein the statistical value is a median value.

40. The method of claim 37, wherein the portion is a quadrant.

41. The method of claim 37, wherein the portion is a cluster.

42. The method of claim 37, further comprising selecting a color for the 2-D line chart based on user-defined criteria.

43. The method of claim 37, further comprising selecting a size for the 2-D line chart based on user-defined criteria.

44. A method of interactively displaying records and their corresponding attributes, comprising:

selecting a set of records and their associated attributes, wherein the associated attributes are any combination of numeric, categoric, sequence, and text information;

converting the associated attributes into numeric values;

generating a first chart that depicts the set of records;
generating a second chart for a subset of records depicted in
the first chart, wherein at least two attributes associated with the subset of
records are shown along one axis, and wherein a statistical value for each
5 of the at least two attributes is shown along the other axis; and
superimposing the second chart at a location on the first chart
that is based on the location of the subset of records on the first chart.

45. A method for visualization of multiple queries to a database,
comprising:

10 selecting multiple queries to a database;
querying records in the database based on the multiple
queries;
creating a query matrix indexed based on the selecting; and
populating the query matrix based on the querying.

15 46. A method according to claim 45, wherein selecting includes
defining a query of an attribute of a record versus a record in the database.

47. A method according to claim 46, wherein the creating
includes indexing the query matrix using a cluster corresponding to a
plurality of records.

20 48. A method according to claim 47, wherein the populating
includes statistically combining query results for the plurality of records
corresponding to the cluster.

49. A method according to claim 45, wherein the selecting
includes defining a query of a first attribute of a record versus a second

attribute of a record.

50. A method according to claim 45, wherein the selecting includes defining a query of current data versus historical data.

51. A method according to claim 45, wherein the selecting
5 includes defining a query of experimental data versus expert data.

52. A method according to claim 45, furthering including visualizing the populated query matrix.

53. A method according to claim 51, wherein the visualization includes creating a visualization matrix indexed based on the selecting,
10 wherein the visualization matrix is populated using a scale of color corresponding to values of the populated query matrix.

54. A method according to claim 53, further including:
detecting a user selection of a portion of the visualization matrix; and
15 displaying features of records in the database corresponding to the portion of the visualization matrix selected by the user.

55. An apparatus for visualization of multiple queries to a database, comprising:
an input device which permits a user to select multiple
20 queries to a database;
an database tool to query records in the database based on the multiple queries;
a calculation device which creates a query matrix indexed based on the selecting and populates the query matrix based on the

querying.

56. An apparatus according to claim 55, wherein the multiple queries include a query of an attribute of a record versus a record in the database.

5 57. An apparatus according to claim 56, wherein a cluster indexes the query matrix, a cluster including a plurality of records.

58. An apparatus according to claim 57, wherein query results for the plurality of records corresponding to the cluster are statistically combined.

10 59. An apparatus according to claim 55, wherein the multiple queries include a query of a first attribute of a record versus a second attribute of a record.

60. An apparatus according to claim 55, wherein the multiple queries include a query of a current data versus historical data.

15 61. An apparatus according to claim 55, wherein the multiple queries include a query of experimental data versus expert data.

62. An apparatus according to claim 55, furthering including a display that visualizes the populated query matrix.




Fig. 1




Fig. 2a




Fig. 2b




Fig. 2c




Fig. 2d




Fig. 2e






FIG. 3








FIG. 5a




FIG. 5b




FIG. 5c






FIG. 5d




1

—




New Visual Analysis: apoptosis disease

4. Preparation



639

634



New Visual Analysis: ge775

5. Processing

OperationSet1

OperationSet2

OperationSet1


OperationSet2

OperationSet1


OperationSet2

OperationSet1


OperationSet2



[illegible]



New Visual Analysis: apoptosis disease	
1. Preparation	
2. Preparation	
3. Preparation	
4. Preparation	
5. Preparation	
6. Preparation	
7. Preparation	
8. Preparation	
9. Preparation	
10. Preparation	
11. Preparation	
12. Preparation	
13. Preparation	
14. Preparation	
15. Preparation	
16. Preparation	
17. Preparation	
18. Preparation	
19. Preparation	
20. Preparation	
21. Preparation	
22. Preparation	
23. Preparation	
24. Preparation	
25. Preparation	
26. Preparation	
27. Preparation	
28. Preparation	
29. Preparation	
30. Preparation	
31. Preparation	
32. Preparation	
33. Preparation	
34. Preparation	
35. Preparation	
36. Preparation	
37. Preparation	
38. Preparation	
39. Preparation	
40. Preparation	
41. Preparation	
42. Preparation	
43. Preparation	
44. Preparation	
45. Preparation	
46. Preparation	
47. Preparation	
48. Preparation	
49. Preparation	
50. Preparation	
51. Preparation	
52. Preparation	
53. Preparation	
54. Preparation	
55. Preparation	
56. Preparation	
57. Preparation	
58. Preparation	
59. Preparation	
60. Preparation	
61. Preparation	
62. Preparation	
63. Preparation	
64. Preparation	
65. Preparation	
66. Preparation	
67. Preparation	
68. Preparation	
69. Preparation	
70. Preparation	
71. Preparation	
72. Preparation	
73. Preparation	
74. Preparation	
75. Preparation	
76. Preparation	
77. Preparation	
78. Preparation	
79. Preparation	
80. Preparation	
81. Preparation	
82. Preparation	
83. Preparation	
84. Preparation	
85. Preparation	
86. Preparation	
87. Preparation	
88. Preparation	
89. Preparation	
90. Preparation	
91. Preparation	
92. Preparation	
93. Preparation	
94. Preparation	
95. Preparation	
96. Preparation	
97. Preparation	
98. Preparation	
99. Preparation	
100. Preparation	






FIG. 7a




FIG. 7b

804

```

NAME= xprot-ano           : corpus name
DESC= SwissProt annotations : corpus description
END_DESC
DELIMITER=//              : Record delimiter tag

#FO
NAME= Title                : Field Number
TYPE= STRING               : Name of the Field
TAG= DE                    : Data Type of this Field (String, Numeric, Sequence)
METHOD= LINES:1            : Field Tag as it appears in the source file
DOC_VECTOR= FALSE          : Data is on a single line
SEARCH= TRUE               : DONT use this field for the document vector
CORR= TRUE                 : Make this field searchable
CASE_SENSITIVE= TRUE       : Use this field to make categories
WHOLE_BOUNDARY= TRUE       : Case Sensitive
LINEPOS= START             : The title tag must be a word (white space delimited)
IFI                          : The field tag always starts at the beginning of a line
...
IF ...

```

Fig. 8




FIG. 9




FIG. 10

29 / 50

Create Read Update

File Name	Setup		Processing Programs								Interactive Tools and Graphics								
	DataSet Editor	View Editor	Vector Create		Cluster		Projection				Galaxy	Surface Map	Master Query	Plot Data	Record Viewer	Query (word)	Query (Number)	Group	Gist
			Numeric engine	Text engine	K_means	Cluster_std	CorrelationOrder	PCA_Clusters	Triangle	DocProjection									
<datasetname>.dcat	C														R				
<datasetname>.properties	C										R								
<viewname>.clsp		C			R	R					R								
<viewname>.cluster								C		C									
<viewname>.corr			C										R						
<viewname>.dcat			C												R				
<viewname>.docpt										C	R								
<viewname>.docterm			C													R			R
<viewname>.docterm_index			C													R			R
<viewname>.docv (vector)			C	R	R	R				R	R	R		R			R		
<viewname>.edge									C	R									
<viewname>.field off			C										R	R	R	R			
<viewname>.gif			C								R								
<viewname>.groups																		U	
<viewname>.hml			C	R									R	R	R	R	R		
<viewname>.hcls					C	C	R			R	R	R	R		R				
<viewname>.headings			C								R	R		R			R		
<viewname>.ifi			C													R			
<viewname>.ifi_index			C																
<viewname>.properties	U	U	U	U	U	U	U	U	U	U	R	R							
<viewname>.punc			C	R												R	R		
<viewname>.rel			C														R		
<viewname>.repository											R	R	R	R	R	R	R	R	R
<viewname>.stop			C	R													R		
<viewname>.tl			C								R	R	R	R	R	R			
<viewname>.topic			C														R		
<viewname>.vocab			C													R			R
<viewname>.vocab_index			C																
Tab Delimited Column/Row source			R																
Tagged Text Source File(s)			C	R											R				
ReEngineered Tagged Text Source	C	R	R												R				

FIG. 11




Fig. 12





FIG. 13






FIG. 15




Fig. 16

35 / 50




FIG. 17




Fig. 18




Fig. 19






Fig. 20

**Fig. 21**



Records vs attributes

Attribute Sources

☒ Vocabulary Word(s)
☐ Vocabulary File
☐ Category Field(s)
☐ Category File

Type in words, separated by semicolon.

Browse

Add

Drop down list of fields


Browse

Clear

Cancel

Done

Fig. 22A



Attributes vs attributes

Row Attribute

☒ Vocabulary Word(s) Type in words, separated by

☐ Vocabulary File

☐ Category Field(s)

☐ Category File

Column Attribute

☒ Vocabulary Word Type in words, separated by

☐ Vocabulary File

☐ Category Field

☐ Category File

Fig. 22B

2260

Current data vs historical data

Historical data for comparison

☒ Previous Visualization

☐ Data matrix file(s)

Fig. 22C

2270

	Attribute_1	Attribute_2	Attribute_3	Attribute_4	Attribute_5	Attribute_6
Record_1	1	1	1	1	0	0
Record_2	0	1	1	1	1	0
Record_3	0	1	1	1	0	0
Record_4	1	0	1	1	0	0
Record_5	1	1	1	0	1	1
Record_6	0	1	0	1	0	0

Fig. 23

	Attribute1	Attribute2	Attribute3	Attribute4	Attribute5	Attribute6
Record_1	Black	Black	Black	Black	White	White
Record_2	White	Black	Black	Black	White	White
Record_3	White	Black	Black	Black	White	White
Record_4	Black	White	Black	Black	White	White
Record_5	Black	White	Black	Black	White	White
Record_6	White	Black	Black	Black	White	White

Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29



Fig. 30A Fig. 30B

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/024060 A2

(51) International Patent Classification⁷: **G06F 17/30**

(21) International Application Number: PCT/US00/26964

(22) International Filing Date:
29 September 2000 (29.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/410,367 30 September 1999 (30.09.1999) US

(71) Applicant: **BATTELLE MEMORIAL INSTITUTE**
[US/US]; 505 King Avenue, Columbus, OH 43201-2693
(US).

(72) Inventors: **SAFFER, Jeffrey, D.**; 202 Hartwood Street,
Richland, WA 99352 (US). **CALAPRISTI, Augustin,**
J.; 3104 Mount Granite Court W., Richland, WA 99353
(US). **MILLER, Nancy, E.**; 4919 Brookburn Drive,
San Diego, CA 92130 (US). **SCARBERRY, Randall,**
E.; 2224 Benton Avenue, Richland, WA 99352 (US).
THURSTON, Sarah, J.; 221 Douglass Avenue, Richland,
WA 99352 (US). **HAVRE, Susan, L.**; 300 Rockwood
Drive, Richland, WA 99352 (US). **DECKER, Scott, D.**;
1309 Buena Court, Richland, WA 99352 (US). **PAYNE,**
Deborah, A.; 1968 Newhaven Loop, Richland, WA 99352
(US). **SOFIA, Heidi, J.**; 383 S. Palouse, Walla Walla, WA
99362 (US). **THOMAS, Gregory, S.**; 93006 East Reata
Road, Kennewick, WA 99338 (US). **CHEN, Guang;**
1329 Goethals Drive, Apt. 9, Richland, WA 99352 (US).
CROW, Vernon, L.; 415 South Grant, Kennewick, WA
99336 (US). **ALBRIGHT, Cory, L.**; 1110 McPherson,
Richland, WA 99352 (US). **ZABRISKI, Sean, J.**; 8943
W. Canyon Place, Richland, WA 99352 (US). **GROCH,**
Kevin, M.; 2433 George Washington Way, Suite 6105,

Richland, WA 99352 (US). **MALARD, Joel, M.**; 1312
RocheFontaine, Richland, WA 99352 (US). **NOWELL,**
Lucille, T.; 40 Edgewood Drive, Richland, WA 99352
(US).

(74) Agents: **GOLDSTEIN, Steven, J.** et al.; Frost Brown
Todd LLC, 2500 PNC Center, 201 East Fifth Street, Cincin-
nati, OH 45202 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished
upon receipt of that report*

(48) Date of publication of this corrected version:
5 December 2002

(15) Information about Correction:
see PCT Gazette No. 49/2002 of 5 December 2002, Sec-
tion II

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: DATA PROCESSING, ANALYSIS, AND VISUALIZATION SYSTEM FOR USE WITH DISPARATE DATA TYPES

(57) Abstract: A system or method consistent with an embodiment of the present invention is useful in analyzing large volumes of different types of data, such as textual data, numeric data, categorical data, or sequential string data, for use in identifying relationships among the data types or different operations that have been performed on the data. A system or method consistent with the present invention determines and displays the relative content and context of related information and is operative to aid in identifying relationships among disparate data types. Various data types, such as numerical data, protein and DNA sequence data, categorical information, and textual information, such as annotations associated with the numerical data or research papers may be correlated for visual analysis. A variety of user-selectable views may be correlated for user interaction to identify relationships that exist among the different types of data or various operations performed on the data. Furthermore, the user may explore the information contained in sets of records and their associated attributes through the use of interactive 2-D line charts and interactive summary miniplots.

WO 01/024060 A2

**Data Processing, Analysis, and Visualization System
For Use with Disparate Data Types**

5 RELATED APPLICATIONS

The following identified U.S. patent applications are relied upon and are incorporated by reference in this application:

10 U.S. Patent Application Ser. No. _____, entitled "METHOD AND APPARATUS FOR EXTRACTING ATTRIBUTES FROM SEQUENCE STRINGS AND BIOPOLYMER MATERIALS," filed on the same date herewith by Jeffrey Saffer, et al.;

15 U.S. Patent Application Ser. No. 08/695,455, entitled "THREE-DIMENSIONAL DISPLAY OF DOCUMENT SET," filed on August 12, 1996; and

20 U.S. Patent Application Ser. No. 08/713,313, entitled "SYSTEM FOR INFORMATION DISCOVERY," filed on September 13, 1996.

The disclosures of each of these applications are herein incorporated by reference in their entirety.

TECHNICAL FIELD

25 This invention relates to data mining and visualization. In particular, the invention relates to methods for analyzing text, numerical, categorical, and sequence data within a single framework. The invention also relates to an integrated approach for interactively linking and visualizing disparate data types.

30 BACKGROUND OF THE INVENTION

A problem today for many practitioners, particularly in the science disciplines, is the scarcity of time to review the large volumes of information that are being collected. For example, modern methods in the life and

chemical sciences are producing data at an unprecedented pace. This data may include not only text information, but also DNA sequences, protein sequences, numerical data (e.g., from gene chip assays), and categoric data.

- 5 Effective and timely use of this array of information is no longer possible using traditional approaches, such as lists, tables, or even simple graphs. Furthermore, it is clear that more valuable hypotheses can be derived by simultaneous consideration of multiple types of experimental data (e.g., protein sequence in addition to gene expression data), a
- 10 process that is currently problematic with large amounts of data.

- Visualization-based tools for analyzing data are discussed in, for example, Nielson GM, Hagen H, Müller H, eds., (1997) Scientific Visualization, IEEE Computer Society, Los Alamitos); (Becker RA, Cleveland WS (1987) *Brushing Scatterplots*, Technometrics 29:127-142;
- 15 Cleveland WS (1993) Visualizing Data, Hobart Press, Summit, NJ); (Bertin J (1983) Seminology of Graphics, University of Wisconsin Press, London; Cleveland WS (1993) Visualizing Data, Hobart Press, Summit, NJ). These tools have focused largely on data characterization, and have provided limited user interactivity. For example, the user may gain access to
- 20 underlying information by selecting an item with a pointer.

 These tools, however, have significant drawbacks. Although current tools can handle certain data types (e.g., text, or numerical data), they do not allow a user to interact with disparate data types (i.e., text, numerical, categoric, and sequence data) within an integrated data analysis, mining,

and visualization framework. Furthermore, these tools do not allow a user to interact well between different visualizations in the manner required to gain knowledge.

What is needed, therefore, is a tool that allows a user to analyze,
5 mine, link, and visualize information of disparate data types within an integrated framework.

SUMMARY OF THE INVENTION

Systems and methods consistent with the present invention aid a
10 user in analyzing large volumes of information that contain different types of data, such as textual data, numeric data, categorical data, or sequential string data. Such systems and methods determine and display the relative content and context of information and aid in identifying relationships among disparate data types.

15 More specifically, one such method defines a uniform data structure for representing the content of an object of different data types, selects attributes of different objects of a variety of different data types that may be represented in the uniform data structure and operates on the selected attributes to produce first representations of the objects in correspondence
20 with the uniform data structure.

The data types may include numeric, sequence string, categorical and text data types. An index may be produced that includes second representations of non-selected attributes of a particular object and that associates the non-selected attributes with a particular first representation.

The first and second representations may be vector representations. A first set of the selected attributes associated with a first set of objects may be used to determine the relationships among the first set of objects of a particular data type and non-selected attributes associated with the first set of selected attributes may be used to correlate objects represented by the first set of selected attributes with a second set of objects represented by a second set of selected attributes. The first and second set of objects may be displayed in first and second windows on a display screen and the second set of objects that corresponds to the selected object or objects may be highlighted.

A method consistent with the present invention identifies relationships among different visualizations of data sets and includes displaying first graphical results of a first type analysis performed on selected attributes of a first set of objects and displaying second graphical results of a second type analysis performed on selected attributes of a second set of objects. Certain objects represented in the first graphical results may be selected and corresponding objects represented by the second graphical results that correspond to the certain objects are highlighted. The highlighting may be based on attributes not used for creating the first graphical results.

Another aspect of the present invention is directed to a system and a method for visualization of multiple queries to a database that includes selecting multiple queries to a database, querying records in the database based on the multiple queries, creating a query matrix indexed based on.

the selecting, and populating the query matrix based on the querying.

Another method consistent with the present invention interactively displays records and their corresponding attributes and includes generating a first 2-D chart for a first record, where at least two attributes associated with the first record are shown along one axis, and the values of the attributes are shown along the other axis. Input is received from a user selecting the first record on the first 2-D chart and an index is analyzed to determine if the first record is shown in another view. If the first record is shown in another view, the visual representation of the first record is altered in the another view based on the user input.

Another method consistent with the present invention interactively displays records and their corresponding attributes and includes generating a 2-D scatter chart that depicts a plurality of records. A 2-D line chart is generated for a group of records contained in a portion of the 2-D scatter chart. At least two attributes associated with the group of records are shown along one axis, and a statistical value for each of the at least two attributes is shown along the other axis. A 2-D line chart is superimposed at a location on the 2-D scatter chart that is based on the location of the group of records on the 2-D scatter chart.

20

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in, and constitute a part of, this specification illustrate at least one embodiment of the invention and, together with the description, serve to explain the

advantages and principles of the invention. In the drawings,

FIG. 1 is a block diagram of visualizations screens or views that are consistent with the present invention;

FIG. 2a is a block diagram of a computer system and program
5 modules consistent with the present invention;

Figs. 2b, 2c, 2d and 2e are block diagrams of program modules consistent with the present invention;

FIG. 3 is a flow diagram of a processes associated with a data editor consistent with the present invention;

10 Figs. 4a and 4b are screen shots associated with a data editor consistent with the present invention;

FIG. 5a - 5d are flow diagrams of a processes associated with a view editor consistent with the present invention;

Figs. 6a - 6m are screen shots associated with a view editor
15 consistent with the present invention;

FIG. 7a and 7b are flow diagrams of processes associated with an analysis processing module consistent with the present invention;

FIG. 8 is an example file format consistent with an embodiment of the present invention;

20 FIG. 9 is a flow diagram of a clustering process consistent with the present invention;

FIG. 10 is a flow diagram of a projection process consistent with the present invention;

FIG. 11 is table that identifies operations of program modules used

in conjunction the meta data consistent with the present invention;

FIG. 12 is a flow diagram of a visualization linking process
consistent with the present invention;

FIG. 13 a flow diagram of a method consistent with the invention for
5 displaying information interactively by using 2-D charts;

FIG. 14 is a representative user interface screen showing 2-D line
charts consistent with the invention;

FIG. 15 is another representative user interface screen showing 2-D
point charts consistent with the invention;

10 FIG. 16 is another representative user interface screen showing 2-D
line charts linked to a galaxy view consistent with the invention;

FIG. 17 a flow diagram of a method consistent with the invention for
displaying information interactively by using summary miniplots;

FIG. 18 is a representative user interface screen showing the use of
15 summary miniplots in a galaxy view;

FIG. 19 provides an illustration of a multiple query tool visualization
according to the present invention;

FIG. 20 illustrates a process of creating a visualization using the
multiple query tool;

20 FIG. 21 illustrates a dialog box to set the type of query;

Figs. 22A-22C display exemplary parameter-setting dialog boxes for
query types shown in FIG. 21;

FIG. 23 illustrates a query matrix according to an aspect of the
present invention;

FIG. 24 illustrates a visualization of the query matrix of FIG. 23 indexed by records;

FIG. 25 illustrates a visualization of the query matrix of FIG. 23 indexed by clusters;

5 FIG. 26 illustrates a visualization as a three-dimensional view;

FIG. 27 illustrates a two-dimensional scatter plot of rows vs. values;

FIG. 28 illustrates the contents of a menu bar, with associated sub-menus, of the visualization of FIG. 19;

FIG. 29 illustrates examples of functions of a tool bar associated
10 with the visualization of FIG. 19; and

Figs. 30A and 30B illustrates views of a visualization matrix having a grid and not having a grid, respectively.

DETAILED DESCRIPTION

15 Reference will now be made in detail to one or more embodiments of the present invention as illustrated in the accompanying drawings. The same reference numbers may be used throughout the drawings and the following description to refer to the same or like parts.

A. Overview

20 Systems and methods consistent with the present invention are useful in analyzing information that contains different types of data and presenting the information to the user in an interactive visual format that allows the user to discover relationships among the different data types. Such methods and systems include high-dimensional context vector

creation for representing elements of a dataset, visualization techniques for representing elements of a dataset including methods for indicating relationships among objects in a proximity map, and interaction among datasets including linking the visualizations and a common set of
5 interactive tools. In an embodiment, the interactions, regardless of data type, among the visualizations and the common set of tools for the interactions is enabled by maintaining meta data, as discussed herein, in a common set of file structures (or database).

Methods and systems consistent with the present invention may
10 include various visualization tools for representing information. A tool for visualizing multiple queries to a database is provided. In another visualization tool, if a first record of a 2-D chart of one view is shown in a second view, the visual representation of the first record is altered in the second view based on the user input. In another visualization tool, a 2-D
15 line chart is superimposed at a location on a 2-D scatter chart that is based on the location of a group of records on the 2-D scatter chart. Other tools consistent with the present invention may be used in conjunction with the methods and systems described herein.

As used herein, a record (or object) generally refers to an individual
20 element of a data set. The characteristics associated with records are generally referred to herein as attributes. A data set containing records is generally processed as follows. First, the information represented by the records (including text, numeric, categoric, and sequence/string data) are received in electronic form. Second, the records are analyzed to produce a

high-dimensional vector for each record. Third, the high-dimensional vectors may be grouped in space (i.e. a coordinate system) to identify relationships, such as clustering among the various records of the data set. Fourth, the high-dimensional vectors are converted to a two-dimensional representation for viewing purposes. The two-dimensional representation of the high-dimensional vectors is generally referred to herein as "projection." Fifth, the projections may be viewed in different formats according to user-selected options, as shown by the four views (110, 120, 130, and 140) on display monitor 100 in Fig. 1.

Systems and methods consistent with the present invention enable a user to select a record in view 110 and cause the corresponding record in another view to be highlighted. For example, selecting a particular record in view 110 causes the corresponding records 122 and 132 to be highlighted in views 120 and 130, respectively. The highlighted points may represent different analyses performed on the same records or may represent different data types associated with the records.

B. Architecture

Fig. 2a depicts a computer system 200 consistent with the present invention. Computer programs used to implement methods consistent with the present invention are generally located in a memory unit 210, and the processes of the present invention are carried out through the use of a central processing unit (CPU) 280 in conjunction with application programs or modules. Those skilled in the art will appreciate that memory unit 210 is representative of read-only, random access memory, and other memory

elements used in a computer system. For simplicity, many components of a computer system have not been illustrated, such as address buffers and other standard control circuits; these elements are well known in the art.

Memory unit 210 contains databases, tables, and files that are used
5 in carrying out the processes associated with the present invention. CPU 280, in combination with computer software and an operating system, controls the operations of the computer system. Memory unit 210, CPU 280, and other components of the computer system communicate via a bus 284. Data or signals resulting from the processes of the present invention
10 are output from the computer system via an input/output (I/O) interface 290.

The computer program modules and data used by methods and systems consistent with the present invention include visualization set up programs 212, processing programs 220, meta data files 230, interactive graphics and tools programs 240, and an application interface 250. The
15 visualization set up programs 212 determine the name to be used for a collection of records identified by a user, determine the formats to be used for reading files associated with the records, identify formatting conventions for storing and indexing the records, and determine parameters to be used for analysis and viewing of the records. The processing programs 220
20 transform the raw data of the identified records into meta data, which in turn is used by the interactive visualization tools. The meta data files 230 include the results of statistical feature extraction, n-space representation, clustering, indexing and other information used to construct and interact among the different views. The interactive graphics and tools programs

240 enable the user to explore and interact with various views to identify the relationships among records. The application programming interface (API) 250 enables the components 212, 220, 230, and 240 to exchange and interface information as needed for use in analysis and visual display.

5 The visualization setup programs 212 further include a data set editor 214 and a view editor 216. The processing programs 220 further include vector programs 222, cluster programs 224, and projection programs 226. The meta data files 230 are a subset of databases and files 260.

10 The data set editor 212 enables the user to define the collection of records (i.e., a data set) to be analyzed, identifies the data type, and creates directories for use in organizing the data of the data set. The view editor 216 sets up the user's raw data for viewing by the interactive tools and graphics. Vector programs 222 create high-dimensional context
15 vectors that represent attributes of the records of the data set. Cluster program 224 groups related records near each other in a given space (cluster) to enable a user to visually determine relationships. Projection programs 226 convert high-dimensional representations of the records of a data set to a two-dimensional or three-dimensional representation that is
20 used for display. The databases and files 260 contain data used in conjunction with the present invention, such as the meta data 230.

C. Architectural Operation

1. Data Collection (Data Set Editor)

Fig. 3 illustrates an implementation of processes performed to define

and enable the formatting of a selected data set, as performed by the data set editor 212. A data file to be used as the source for the subsequent analysis is requested (step 302). After a file name, data type and directory location is entered (step 304), the process determines and validates the data type indicated by the user (step 310). The validation process first determines whether the data of the source data file is in a common sequence data format (step 312). If the data is not one of the common sequence data formats, the process determines whether the data is an array of data consisting of numeric, categoric, sequence, or text (step 314). If the data is not a data array, the process determines whether the data is free form text (step 316). If the data is not free form text (step 316), an error message is generated (step 320).

If the validation process determines that the data is sequence data, such as genome sequence data (step 312), the process determines whether the sequence data is in FastA file format (step 322) or whether the sequence data is in a SwissProt file format (step 324). An example FastA input file is provided in Appendix B. The operations and data associated with processing sequence data is discussed in more detail in U.S. Patent application serial no. _____, entitled "Method and Apparatus for Extracting Attributes from Sequence Strings and Biopolymer Materials" filed on the same day herewith by Jeffrey Saffer, et al. If the sequence data is not in one of these formats, an error message is generated (step 320). If, however, the data is either a FASTA file (step 322) or a SwissProt file (step 324), the appropriate formats and delimiters, as discussed herein, are

determined to be used for the respective FASTA file or SwissProt file (step 330). After the appropriate format/delimiters for the data type are determined (step 330), the corresponding format file/record delimiters are established (step 340). The format file/record delimiters specify the valid
5 formats for reading the files and identifies the meta data files that are to be used for subsequent processing of the data set as discussed herein.

A file directory 360 is created for storing the meta data files associated with the data set (step 350). The file directory 360 includes a document catalog file (DCAT) 362 and a data set properties file 364. The
10 DCAT file 362 is used as a master index for all records in the data set. The indexes stored in the DCAT file are used to integrate the information associated with the various views selected for the data set. For example, the DCAT file 362 contains indexes that associate all the data of a data set with a particular view, although only a subset of the data set is used to
15 create the view. The properties file 364 is also produced and stored in the file directory and contains information about the source data files for the view, including their type (corpus type), the number and full path (location) for the source files, the format used, and the date created. In addition, the properties file keeps track of subsequently processed views including the
20 subdirectory where those views reside. An example properties file is provided in Appendix A.

Figs. 4a and 4b depict exemplary screen shots presented on a display monitor to a user for defining a new data set (i.e., collection of records) using data set editor 212. A user names and defines a data set

using the data set editor 212. When the data set editor is selected, a graphical interface screen 400 is presented to a user for use in defining options or parameters associated with the data set. For example, graphical interface screen 400 is presented to a user when the user selects the
5 sources tab 410.

The user may enter a name for the data set in a field 412 and may specify the data set type as indicated by the selection options 414, such as array data, protein or nucleotide sequences, or text. The source of this data set may be specified in the field 418 as indicated by the directory and
10 subdirectory specification 420. The user may select the add, view, or delete options 424 to perform the function indicated by the name on the data set source. The user may save the data as indicated by the option 426 or continue to a new view as indicated by the option 428.

By selecting the format tab 440, the user may specify how fields
15 contained within the source file are delimited by selection of a field delimiter option 442. The field delimiter options illustrated include an option to delimit the field by a colon, comma, space, tab, or a user defined delimiter.

2. Analysis and View Setup (View Editor)

Fig. 5a illustrates an implementation of a process used for creating
20 parameters when defining the type of analyses or views for a data set, as performed by view editor 216. The user may enter this information using a graphical interface as depicted in Fig. 6a, which shows source file tab 604, format tab 610, preparation tab 630, processing tab 660, clustering tab 680, and projection tab 690, respectively.

The user is first requested to name the view (step 510) and also is requested to identify the directory locations of the source files (step 520). The user is requested to specify the format of the source data (step 530). Fig. 6b is a screen display showing the options presented to a user when the format tab 610 is selected. The user may provide in the format file field 610, a file to use for formatting the view such as medline 31.fmt. The user may also specify a stop words file such as the default text stop file shown in the field 614. This stop words file is a list of words that the text engine will ignore during analysis. The user may input a file to specify the default punctuation of the file as indicated by the default.punc file indicated in the field 616. The punctuation file tells the text engine how to handle non-alphabet characters. For each of the files requested, the user may use the default file specified by the system or choose another. The user may select or view any of the files of the format screen of Fig. 6b by selecting the select option 620 or the view option 622.

The user is also requested to provide preparation parameters (step 540). The processes associated with step 540 are discussed in more detail in Fig. 5b. The user may specify vector creation, cluster, and projection parameters to be used in constructing a view (steps 550, 560, and 570, respectively). The projection parameters include cluster cohesion, cluster area, and cluster spread. Vector creation and clustering parameter processes are discussed in more detail in Figs. 5c and 5d, respectively.

Referring to Fig. 5b, the view editor processes are discussed. The view editor first checks the data type (step 541) by evaluating whether the

data is sequence data (step 542). If the data is sequence data, sequence specific preparation information is requested (step 543), such as requesting number and length of n grams, SEG parameters, substitution filter values, and motif pattern file parameters (step 544). If the data is not sequence
5 data (step 542), the process determines whether the data is numeric data (step 545). If the data is not numeric data, no preprocessing or preparation information is required for text information (step 546). If the data is numeric data, a display screen that requests numeric data and preparation information from a user (step 547) is presented. The numeric preparation
10 data request may include column/row specifications, operation sets, and clustering fields (step 548).

Fig. 5c illustrates an implementation of the processes associated with gathering vector creation parameters within the view editor 216 (Fig. 2). The view editor 216 first checks the data type (step 551). If the data is
15 sequence data (step 552), sequence specific text engine parameters are requested or obtained for the particular data set (step 553). The text engine parameters requested may include the number of topics/cross terms, topicality settings, use association t/f parameters, associated matrix threshold parameters, and record filter ranges (step 554).

20 If the data is not sequence data (step 552), the view editor determines whether the data is text data (step 555). If the data is text data, text specific text engine parameters are requested from the user (step 556) such as the text engine parameters discussed above (step 554). If the data is not text data (step 555), no user specified parameters are needed and

default parameters may be used (step 557). The text engine parameters may be used if desired (step 554).

Fig. 5d illustrates an implementation of a process for specifying clustering parameters. Various types of clustering may be used such as k-means or hierarchical clustering as known to those skilled in the art. The view editor 216 presents a display screen to the user for the user to specify the clustering choice (step 561). The process determines whether k-means clustering has been chosen (step 562). If k-means clustering is requested (step 562), k-means clustering parameters are requested from a user or obtained (step 563) such as the number of clusters, the number of iterations, the cluster seed method or whether correlation order is to be used (step 564). If k-means clustering is not requested (step 562), the process determines whether the user desires hierarchical clustering (step 565), and displays or gets hierarchical clustering parameters (step 566). The hierarchical clustering parameters may include determining the number of clusters or cluster coherence values to be used and whether the user desires correlation order for the clusters may be determined (step 567). If hierarchical clustering is not desired (step 565), no parameters are required (step 568).

Referring to Fig. 6c, when the preparation tab 630 is selected, the user is presented with a data specification option 632, an operation set option 640 and a clustering selection option 650. The user may enter a value for the columns in the field 634. For the data set specified, the user may identify the type of data, such as numeric data, categorical data,

sequence data, or text data by selecting a data type 635. The user may specify the columns 636 in which that data type is located and may specify a field name for that specific data as indicated under the field name 637. A predefined selection field 638 may be used to specify the types of data for
5 the field name and columns provided.

A user may perform any number of mathematical manipulations on the numeric data (one or more manipulations or transformations of the data is referred to as an operation set). These options include various logarithmic operations, methods for normalizing data, methods for filling
10 missing data points, and all algebraic functions. Referring to Fig. 6d, for example, the reciprocal or the value for each numeric data item may be requested and then the logarithm taken for that reciprocal, creating a new field 642 called Operation Set1.

Fig. 6e shows the screen displayed if the clustering selection tab
15 650 is selected. The user is presented with a set of field/trench forms 652 for which clustering operations may be applied. In the example illustrated, operation set 1, or numeric field name 1 may be chosen for clustering.

Referring to Fig. 6f, for a sequence, the user may have motifs/n-grams, complexity filtering, exclusions, and amino acid substitutions
20 options from which to select. Operation on or with sequence data is discussed in more detail in U.S. patent application entitled "Method and Apparatus for Extracting Attributes from Sequence Strings and Biopolymer Materials" filed concurrently herewith and is expressly incorporated herein by reference. If the user wants to represent the sequence as a high-

dimensional vector based on the occurrence of functional or structural motifs, a file is specified which defines those motifs. The user can have that vector based on the number of occurrences of each motif or, if desired, have the vector based on a binary format (the motif is either there or not) by checking the single motif output option. Alternatively, or in addition, the user may specify any combination of overlapping n-grams to be created to represent the sequence in field 654. The user also has the option to specify whether the n-gram should be included based on number of occurrences within the sequence. If neither motif nor n-gram options are selected, the program will analyze the text (e.g., annotations) associated with the sequence records. The complexity filtering options provide the user the ability to include the entire sequence or eliminate regions of low or high complexity, for example, using the public domain tool SEG. The user may also specify certain records to be excluded, for example, based on sequence length, or title, by selecting options in the exclusion interface. Finally, the use of amino acid or nucleotide substitutions can be defined in the Amino Acid Substitution interface.

Referring to Fig. 6g, the options provided to the user for processing data is illustrated. The user may use a sliding scale to specify the magnitude or weight to give to associations as indicated by the association field 672. The user may enter the number of topics to be used in the field 674. The topics are the features that describe the vectors. For text, these are the vocabulary words that best describe the thematic content of the records; for sequences, the topics are the n-gram vocabulary words that

best distinguish one sequence from another. The user may specify the requested number of cross terms as indicated in the field 676. Cross terms are the vocabulary words that are not topics. The user may specify the number of times that the topics may appear in a record before being
5 identified as a topic and an upper limit may be included as well as indicated in the fields 678a and 678b. In the field 679a and 679b, the user may specify the number of times that the terms must appear in other documents by specifying a lower limit in field 679a and an upper limit in field 679b. These fields are used as filtering fields for processing. The topicality
10 method for Fig. 6g is 'Specify the settings by the number of terms.'

Referring to Fig. 6h, the topicality method for the processing option is specified as 'Specify the settings by threshold.' The user may use the sliding scale field 680 to specify the number of associations needed. The user may use a sliding scale input for identifying the minimum topicality for
15 topics weight and the minimum topicality for cross terms as indicated by the fields 682 and 684, respectively. The user may specify upper and lower limits for defining the number of appearances to trigger identification for topics and cross terms, as indicated by the fields 686a, 686b, 688a, and 688b.

20 Referring to Fig. 6i, the user may specify a topicality method that automatically calculates the setting for the view all indicated in the display screen illustrated. The user may use a sliding scale selection field that specifies the weights of association as indicated by the field 689. Referring to Fig. 6j, the user may specify the weights of association for the topicality

method that automatically calculates the settings with emphasis on local topics.

Referring to Fig. 6k, when a user selects the clustering tab 690, the user may specify a clustering method such as hierarchical or k-means.

- 5 When hierarchical clustering is chosen, the user may select an option to compute clusters based on coherence. The user may indicate the number of clusters, and the cluster coherence. The user may also select whether to correlate the order after clustering.

- Referring to Fig. 6l, the graphical interface used for specifying the
- 10 parameters of the k-means is illustrated. The user may specify the number of clusters or the number of iterations to be used for the k-means. When k-means is used, the user may select the cluster seeding parameters such as using random seeding or using dimensional seeding. The seeding may also occur by using the computer's internal clock (system time) to seed
 - 15 random number generator. The user may alternatively specify a value for the random generator seed.

- Referring to Fig. 6m, the user may select the type of projection to use by selecting the projection tab 695. The user may select cluster cohesion, cluster area, or cluster spread. When the user selects either of
- 20 these options, the user may use a weighted scale for each of the options to identify the weight to be associated with each projection option.

3. Common Formatting, Vector Creation, and Index Creation

Fig. 2b illustrates vector creation engines consistent with the present invention. In an implementation, vector creation programs 222 include a

numeric engine 222a, and a text engine 222b.

Referring to Fig. 7a, the general processes performed by the processing programs are discussed. Certain types of data, such as sequence data, is preprocessed (step 702) prior to data being input into the text engine. The sequence data is modified to a form that is acceptable to the text engine for generating the high-dimensional context vectors.

High-dimensional context vectors are created based upon the attributes of the objects or records to be used for a view and vector indices that correspond to the particular view are created and stored in a vector file associated with the data set (step 706). The vectors are clustered using known clustering programs based upon information from the vector files (step 708). The cluster assignment file (.hcls), as discussed below, is created (step 708). Two dimensional coordinates of the records and centroids are calculated for creating a two dimensional projection of the clustered vectors (step 710). Two dimensional coordinate files are created (.docpt) for each document.

i. Vector Creation and Formatting

The visualizations discussed herein are based on high-dimensional context vector representations of the data. Thus, each type of data is represented in that manner. For purely numeric data, the vector representation is simply the values associated with each record attribute. For categorical data, the vector representation can be based on any method that translates categorical values or the distances between values as a number. For text data, the vector representation can be derived by

latent semantic indexing as known to those skilled in the art or by related methods, such as described in U.S. patent application serial number No. 08/713,313, entitled "System for Information Discovery," filed on September 13, 1996. For sequence data, the context vector can be derived from any
5 combination of numerical or categorical attributes of the sequence or by methods described herein. In addition, a user skilled in the art will recognize that the vectors created for each record do not have to be created from a single data type. Rather, the vectors can be created from mixed mode data, such as combined numeric and text data.

10 Not only are high-dimensional vectors created for each record of a data type, but also a common method is used to store that information about the records and their vectors so that later processes can access the data. Methods consistent with the present invention create a group of meta data files through the action of a series of computational steps (collectively
15 referred to as the numeric engine) alone, or in conjunction with another series of computational steps, referred to as the text engine. The files that are produced are binary, for reasons of access speed and storage compactness. The files produced during vector creation are discussed below in more detail.

20 Unless otherwise noted, the files discussed below have the following characteristics: (1) Files are binary, and remain within a directory established for the analysis; (2) IDs and positions are 0-based; (3) Terms have been converted to lowercase, and are listed in ascending lexical order; (4) Record IDs are listed in ascending order; (5) Index files

(.<x>_index) contain cumulative counts of records written to the file they are indexing (<x>). This cumulative count is for the current record and all previous records. This cumulative count is equivalent to the record no. of the next record; and (6) Internal Numerical representations in a Sun

5 Microsystem Operating System are:

10 TermID (4 bytes)
 TermCount (4)
 DocID (4)
 DocCount (4)
 streampos (4)
 double (8)

 Although the examples provided refer to flat file storage of the relevant information, one skilled in the art will recognize that a database
 15 could equally serve as the method for storing and retrieving the meta data.

 The files produced during vector creation are:

20 **.dcat (document catalog)**
 number of records in the source file
 for each record (line number-2 is the record id)
 Source file id
 Starting byte offset with the source file
 Length (in bytes) of the record

25 **.tl (title file)**
 for each record (line number-1 is the record id)
 title field

30 **.docv (vector file)**
 no. of records in view
 no. of dimensions for vectors (= no. of topics)
 for each record
 for each dimension
 coordinate value (float)

35

ii. Visualization and Formatting

The visualization methods keep track of the location of the record representation and may use an object-oriented design. One type of visualization that is especially effective with high-dimensional data is a proximity map or a galaxy view. This and related visualizations can take advantage of methods to group the records in the high-dimensional space (clustering) and to project the arrangement of objects in high-dimensional space to two or three dimensions (projection).

Clustering can be by any of a number of methods including partition methods (such as k-means) or hierarchical methods (such as complete linkage). Any of these type methods can be used with the present invention. Despite the different methods, the computational processes that carry out the clustering create a common set of meta files that allow the chosen visualization method to access the clustering information, regardless of original data type.

The files produced during cluster analysis are:

.hcls (cluster assignment file)

This file contains the assignments for each record to a cluster. The format of the file is as follows :

Number of total Clusters

For each cluster (in correlation order)

Cluster ID

Cluster vector as determined by taking the average of the record vectors assigned to the cluster

Number of Records in the Cluster

The record id's of the records assigned to the cluster

After the .hcls file is produced, it may be resorted in correlation order (a user-definable option).

An example .hcls file:

```

9  (number of clusters)
6  (cluster ID)
0.0457451 0.0399342 0.0864002 0.0652852 0.0635923 0.0429373 0.0650352
0.0661765 0.0487868 0.0885645 0.10 0173 0.0482019 0.048553 0.091455
0.0991594 (cluster vector)
4  (number of records in the cluster)
7  (record ID)
4  (record ID)
3  (record ID)
5  (record ID)

5
0.0392523 0.0364486 0.0897196 0.0626168 0.0598131 0.0364486 0.0616822
0.0794393 0.0448598 0.0925234 0.11
215 0.0429907 0.0420561 0.0962617 0.103738
1
6
1
0.0341207 0.0209974 0.0918635 0.0682415 0.0603675 0.0314961 0.0629921
0.0656168 0.0393701 0.11811 0.1049
87 0.0393701 0.0393701 0.112861 0.110236
1
8
3
0.0587949 0.0578231 0.0739416 0.0695847 0.0651338 0.0544486 0.0705118
0.0665825 0.0739358 0.0612976 0.07
11892 0.0697833 0.0711892 0.0645948 0.0711892
3
12
13
2

```

iii. Projection and Formatting

5 Projection can also be by any number of methods, for example,
multidimensional scaling. Like cluster analysis, a specific projection method
is not required for use with the present invention. However, as with
clustering, the results of that projection are stored in a common format so
that the visualization operations can retrieve the data independent of the
10 original data type.

Files created during projection from high-dimensional space to 2 or 3 dimensions are:

.cluster (2-D coordinates for the cluster centroids)

This file contains the 2-D coordinates for placing the cluster centroid on a galaxy view). For each cluster, a single line in the file contains:

Cluster ID
X coordinate
Y coordinate

An example .cluster file:

```
6 0.770783 0.831761
5 1 1
1 0.920542 0.989886
3 0.073888 0.210541
7 0.0206639 0.109404
4 0 0.13854
0 0.0187581 0.153266
2 0.139079 0.0695485
8 0.374849 0
```

.docpt (2-D coordinates for the individual records)

This file contains the 2-D coordinates for placing the records on the Galaxy

For each record, a single line in the file contains

Record ID
X coordinate
Y coordinate
Cluster ID that the record belongs to

Example of a .docpt file

```
0 0.374849 -4.46282e-07 8
1 0.0300137 0.145639 0
2 0.0890008 0.222 3
3 0.861783 0.90898 6
4 0.745403 0.813245 6
5 0.84583 0.896318 6
6 1 1 5
7 0.630116 0.708499 6
8 0.920542 0.989886 1
9 0.0206639 0.109405 7
10 0.0206639 0.109405 7
11 -4.91018e-08 0.1385 4
```

Note that the X and Y coordinates in the .cluster and .docpt files are represented by a number between 0 and 1 inclusive. Also note that analogous file structures would be used for a 3D projection.

iv. Data Linkage and Formatting

5 Advantageously, the present invention enables linkage among all visualizations and data types (text, categorical, numerical, or sequence). Prior methods enabled linkage between views of the same data visualized using different attributes or visualizations. In addition to the attributes used to create the visualization, other attributes or descriptors for each data
10 record are linked and readily available for interaction. These interactions are possible with any of the data types. That is, additional attributes related to a record, as well as those used for vector creation, are equally available regardless of data type. This is accomplished through the use of a
15 common set of file or database structures created by the numeric or text engines. These files store information about each record attribute, which itself can be any of the data types. These files are created during an initial processing of the data and are independent of the specific visualization method to be employed. These files provide a common framework that can
20 be addressed by any visualization or interactive tool through an API.

20 The files created to store and manage the ancillary data, such as data not used in creating a view, are:

.headings (used for data input through a matrix array only)

25 for each record (line number-1 is the record id)
 name of the column heading

.vocab (text)

for each term in the view
term (i.e., a word)

.vocab_index

for each term in the view
cumulative no. of chars written to .vocab (including \n's);

.field_off

for each record
for each field defined in the format file
starting position (in bytes) of the field from the start of the
record and the number bytes in the field

.corr_v

for each correlatable field defined in the format file
number of unique values of field
for each unique value of the field
number of records that contain the unique value
record id's of the records that contain the value

.ifi (inverted file index)

for each term in the view
for each record containing that term
doc ID
frequency of term within the record

.ifi_index

for each term in the view
cumulative no. of records written to .ifi

.docterm (document term file)

for each record
for each term in the record
term ID
frequency of term within the record

.docterm_index

for each record
cumulative no. of records written to .docterm

.topic (topic file)

no. of topics
minimum topicality for topics
minimum no. of docs containing a topic
maximum no. of docs containing a topic
no. of cross terms
minimum topicality for cross terms
minimum no. of docs containing a cross term

maximum no. of docs containing a cross term
 for each major term (topic or cross term)
 term ID
 topicality
 5 no. of docs containing the term
 term strength (4 bytes; 0=MINOR_TERM,
 1=CROSS_TERM, 2=TOPIC_TERM)

.rel (Association matrix file)
 no. of major terms
 10 no. of topics
 conditional correction
 for each major term
 for each topic
 relation value of major term to topic (values are encoded as
 15 four-bits and packed into bytes)
 four zero bits to pad last byte for major term, if needed

In each of the above files, "terms" refer to text vocabulary words;
 "topics" refer to text vocabulary words deemed by statistical analysis to be
 most likely to convey the thematic meaning of the text; and "crossterms"
 20 refer to text vocabulary words that provide some meaningful description of
 the text content but are not topics. U.S. Patent Application Ser. No.
 08/713,313, entitled "System for Information Discovery," filed on September
 13, 1996 discusses topics and crossterms in more detail.

Many of the binary files are paired, with the first file holding the
 25 information, and the second providing an easily accessed index into the
 first. For example, the inverted file index consists of .ifi and .ifi_index files.
 Each index is a list of the cumulative number of records in the data file.

Together these files provide indexing of and access to the textual
 information associated with each record including the distribution of
 30 keywords within each record and co-occurrences of those keywords.
 Furthermore, the files provide a catalog of all the categorical data including

the distribution of the values. For numerical attributes not used in the actual vector representation, additional files are created using the .docv format so that this type of ancillary information will also be readily available to establish interaction among the various views.

5 The processes associated with producing the series of common files described above are depicted in Fig. 7b. Referring to Fig. 7b, the text engine (730) creates the files associated with text or categorical fields. The expected input for the text engine (block 730) is a tagged formatted file. For text data sets, the input is either the original format for the input or the
10 result of a processing step to identify the beginning and end of each record along with special information, such as the record title. An example original input file to the text engine is provided in Appendix C.

For sequence data in the commonly used formats FASTA (720) or SwissProt (722), a software module (724) reformats the input file to contain
15 a series of fields that delineate the initial input and meta data created for the vector representation (726). The reformatting and processing of sequence data is discussed in more detail in the U.S. patent application entitled "Method and Apparatus for Extracting Attributes from Sequence Strings and Biopolymer Materials" filed concurrently herewith and
20 incorporated herein by reference. Once in this tagged format (726), the text engine (730) is able to create all the required meta data files.

Numerical data, or any other data presented in a data matrix, (750) is received at the numeric engine (752). The data in the input file can be tab delimited or use any other delimiter. The numeric engine (752) creates

the record vectors for data presented in a data matrix instead of the text engine. In addition to the numerical columns, the user may specify other columns within the table that can contain textual, sequence, or categorical information or additional numerical data that will not be used for the vector
5 created. Usually, each row in the table becomes a record; however, the user can choose to make each column the record. Each user-defined set of columns becomes an attribute (also called fields) within the record. A set of numeric columns is specified by the user for subsequent clustering. The other fields, which can be numeric, text, categorical, or sequence, will
10 become attributes of the record that can be queried, listed, or otherwise made available within the interactive tools.

If categorical data is specified by the file format (Fig. 8), as indicated by the index 804 for the view used, categorical data is processed during the text engine processing steps for all types of data. The categorical data
15 shown in Fig. 8 records where each unique character strain and the categorical field occurs in the data set. Thus, subsequent categorical tools are enabled to correlate various records based upon the categorical values.

Each field expected in the input file is defined by a section beginning with ||F followed by the field number (e.g., ||F0). For each field, the name is
20 defined (in this case, title). Then the type of field is defined; this could be string (text or categorical), numeric, or sequence. Next, the delimiter tag for the field is defined. The METHOD line indicates whether the field is on a single line or continues to the next field. The DOC_VECTOR line tells the clustering module whether to use this information in the cluster analysis.

The next item designates whether the field should be accessible within the query tools. The CORR line determines whether the contents of the field should be indexed for all possible associations. The next item defines whether the content is case sensitive or not. The following lines describe the behavior of the delimiter tag. WHOLE_BOUNDARY indicates whether the tag must be a single word or could be embedded within other text; LINEPOS indicates whether the tag must start at the beginning of a line or may be found elsewhere. Similar information would be given about each field in the data. This format file is stored in a directory associated with the view created.

Referring again to Fig. 7b, the numeric engine (752) is executed on the set of columns that the user specified for clustering. The numeric engine (752) performs any number of user defined mathematical operations and creates a record vector that is identical in format to those produced for sequence or text data. In contrast to the text engine (730), which automatically determines the features to use in the record vector, the vector creation in the numeric engine (752) utilizes a user specified set of columns from the users column/row formatted source file.

Once the record vector is created (758), the numeric engine automatically creates a text engine compatible source file (i.e., reverse engineered tagged text file, 754), and corresponding format file (756) from the input column/row formatted table. An example format file produced from the numeric engine is shown in Appendix D. The new tagged text source file and format files (726) are used so that any text, categorical, or

sequence information that may have been embedded within the original column/row files, can be processed by the same programs that operate on text, categorical, or sequence information. This subsequent processing is performed by the text engine (730), which reads the reverse-engineered tagged text source file and indexes the textual and/or categorical data fields within each record (732, 734 and 736). The result is a standardized set of meta data which is related to the user source data and which is available to all tools regardless of data type.

Although the numeric engine processes numerical data, the processing steps of the numeric engine places any of the other data types (text, categorical, or sequence) into an appropriate tagged field in the data file so that the text engine will handle it appropriately.

In summary, if the data input is array data, the array data (column/row formatted tables) is processed by the numeric engine (752). The numeric engine 752 creates a second vector that is identical to the format of the context vectors for sequence and text data produced by the text engine (730). However, in contrast to the text engine, which can automatically determine the features to use in the second vector, the numeric engine 1052 accepts a user defined series of mathematical operations to be performed on specified columns of the array data source file. In order to make the non-numeric contents, such as annotated notes, associated with the array file accessible for subsequent analysis, a format file is produced and a tag text format file is produced for the non-numeric contents associated with the numeric file. The associated non-numeric

contents is used as an input to the text engine and the output is associated with the numeric data. Thus, the textual or categorical data associated with the numeric array data may be indexed and associated with the data as produced for other text data sets that are input to the text engine (730).

- 5 Plain text data should be in a tagged text format and does not require any pre-processing prior to input to the text engine (730).

4. Clustering

Fig. 2c illustrates clustering programs. Three clustering modules or options k-means 224a, cluster-sid 224b, and correlation order 224c are provided. The clustering options may have a set of user definable parameters. The k-means module 224a clusters documents by establishing a user specified number of seed clusters and then iteratively assigns documents to those documents until a user specified number of iterations is reached or the process/algorithm determines that all the documents have been assigned to the clusters.

The k-means module 224a moves documents to minimize the sum of squares between objects and centroids as known by those skilled in the art. The cluster-sid 224b is an agglomerative/hierarchical clustering method that minimizes the maximal between clusters distance (farthest neighbor method). The output of the clustering process is a file containing a correlation ordered list of clusters and the record's IDs of their members. Those skilled in the art will recognize that other clustering algorithms can be used.

Fig. 9 shows a clustering process performed by the processing unit.

A vector file is received from the stored context vector files (step 760) at the cluster implementer (step 904). The user specified clustering parameters are retrieved from stored files (step 906) and the clustering program and parameters associated with the files are determined (step 908). The

5 clustering parameters associated with the clustering program are provided to the cluster implementer (step 904) and the clustering program associated with the vector file of the data set is selected (step 910). The clustering programs are chosen from a k-means clustering program (block 912), a hierarchical clustering program (block 914), or no clustering is

10 selected (block 916). After the clustering program performs its operations (step 910), a cluster assignment file (.hcls) is created (step 920).

5. Projection

Fig. 2d illustrates projection programs 226. Systems consistent with the present invention may apply three separate processes to produce the

15 meta data used to produce visualizations. These processes are carried out by three modules, the PCA-clusters module 226a, a triangulation module 226b, and a document projection module 226c. The PCA-clusters module 226a determines the principle components for each cluster and then determines the two dimensional coordinates for projecting the cluster

20 centroids as known to those skilled in the art. The triangulation module 226b determines the boundaries for the area around each cluster centroid. These boundaries are later used in the doc projection module 226c to take into account the influence of records and neighboring clusters when determining how far from the center and on what side of the cluster

centroid a record will be projected. The doc projection module 226c determines the x,y projection coordinates for each record in the visual analysis.

Referring to Fig. 10, the processes associated with creating a two dimensional projection from the cluster assignment files is illustrated. The cluster assignment file (.hcls) is retrieved from storage (step 1002) and the principle component analysis of the cluster centroid vectors are performed (step 1004). Two dimensional coordinates for the cluster (.clster) are created (step 1008). Delaunay triangulation is performed (step 1010) based on the vector file retrieved from storage (step 1012) that is associated with the data set. Nearest neighbor assignments are associated with the Delaunay triangulation results (step 1014). The projection program determines the two dimensional coordinates for each record (step 1018) based upon the vector files retrieved from storage (step 1012). The projection program also accesses and retrieves the cluster assignment file (.hcls) (step 1020) associated with the data set. The two dimensional coordinates for the group of documents of the data set are stored in a document file (.docpt) (step 1030).

6. Graphic Modules and Tools

Referring to Fig. 2e, the interactive tools and graphics modules are illustrated. The interactive tools and graphics modules 240 include a galaxy module 240a, a master query module 240b, a plot data module 240c, a record viewer module 240d, a query (word) module 240e, a query (number) module 240f, a group module 240g, a gist module 240h, and a

surface map module 240i.

The galaxy module 240g displays records as a scatter plot. The master query module 240b applies a correlation algorithm to all indexed categorical data and creates a two dimensional matrix with values of a category along each axis. At each intersection in the matrix, a rectangle is drawn with sections colored to show the correlation between the categories. The following are analytical tools. The plot data module 240c displays a two dimensional line plot of the n-dimensional vectors created for analysis by the user, this is done for all records in the analysis or just those selected by the user. This module can also be used to examine any ancillary numerical attributes associated with the records. The record viewer module 240d displays a list of the currently selected documents, displays a text of a document, highlights terms selected by other tools, such as the query tool 240e. The query tools 240e and 240f enable the user to input requests to search for information that has been represented by a vector during the processing and analysis of the user's data set. The query tools 240e and 240f compare the user input to vectors representing the processed data set. The query tool 240f performs Boolean or phrase queries in any text or categorical field based on a user's input. The query tool 240f also performs n-space queries based on the user's input and compares the input to the n-dimensional vector used for clustering. Thus, vectors that correspond to the user's input can be identified and highlighted. The numeric query tool 240f performs queries based on numeric values. The group tool 240g enables users to create groups of

records of a data set, based on queries or based on user selections, and colors the groups for display in the galaxy visualization created by the galaxy module 240a. The gist tool 240h determines the most frequently used terms in the currently selected set of records. The surface map
5 module 240i provides a surface map that shows records and a plurality of attributes associated with those records.

Referring to Fig. 11, a table is shown that illustrates meta data files that result from statistical analyses and indexing of the data sets consistent with an embodiment of the present invention. The table also depicts the
10 meta data files that are used for the various interactive tools and graphics modules. All of the meta data files except for the tab delimited column/row file, the tagged text source file(s), and the re-engineered tag text file are defined by the data set name or view name as created by the data set editor 314 or view editor 316 (Fig. 2a) plus an ".extension," such as [data
15 set name].dcat or [view name].cluster. The meta data files include a data set name.dcat file, a data set name.properties file, a view name.clsp file, a view name.cluster file, a view name.corrv file, a view name.dcat file, a view name.docpt file, a view name.docterm file, a view name.docterm index file, a view name.docv(vector) file, a view name.edge file, a view name.fieldoff
20 file, a view name.gif file, a view name.groups file, a view name.fmt file, a view name.hcls file, a view name.headings file, a view name.ifi file, a view name.ifi index file, a view name.properties file, a view name.punc file, a view name.rel file, a view name.repository file, a view name.stop file, a view name.tl file, a view name.topic file, a view name.vocab file, a view

name.vocab index file, a tab delimited column/row file, a tag text source file(s), and a re-engineered tag text file. The table indicates which program modules create, read or update files as indicated by the letters C, R, and U, respectively. For example, the view name.clsp file is created by the view editor 216 (Fig. 2b) and is read by the k-means module 224a and the cluster-sid module 224b (Fig. 2c) and is read by the galaxy module 240a (Fig. 2e). The view name.groups file is updated by the group module 240g. All file access is performed through the API layer (Fig. 2a).

After the clustering and projection processes have been completed, the user may now view the results of the various operations performed on the user's data set. As discussed above, prior methods of visualization do not adequately provide access to relationships among attributes of data records other than those used in creating the visualization and, consequently, do not enable the identification of relationships between attributes of different visualizations or views. A system operating according to the present invention enables a user to identify relationships among different visualizations or views by maintaining all attributes associated with the data record for indexing although all attributes are not used in creating the visualization. Referring to Fig. 12, the processes consistent with an embodiment of the present invention used to link different visualizations or views is discussed. When a user is viewing a particular visualization or view, the user may request to identify the relationships that exist between the attributes used to create the current visualization with the attributes used to create another visualization (step 1202). After the user initiates a

request to explore the data of another view (a target view) an index file associated with the user's current view or data set is accessed (step 1210). After the index file is accessed (step 1210), the process determines whether objects selected by the user in the current view, such as by
5 initiating a query, correspond to objects of a target view based upon all of the attributes contained in the index file (step 1220). If objects of the target view or file correspond to the selected objects of the current view, the objects of the target view are highlighted (step 1230). Therefore, relationships among attributes of data records other than those used in
10 creating the visualization can be used to identify relationships of another visualization as discussed in connection with Fig. 1.

Methods and apparatus consistent with the invention also provide tools that allow a user to display information interactively so that the user can explore the information to discover knowledge. One such tool displays
15 a set of records and their associated attributes in the form of superimposed two-dimensional line charts. The tool can also generate a single two-dimensional line chart that provides the average values for the attributes associated with the set of records. Each of these charts are linked to other views, such that a record selected in the charts is highlighted in the other
20 views, and vice versa.

Another tool generates summary miniplots that may be quickly used by a user to obtain an overview of the attributes associated with a particular group of records. In particular, records shown in a scatter chart are organized into groups. The average values for the attributes associated

with each group of records is used to form a two-dimensional line chart. The line chart is superimposed on the scatter chart, based on the location of the set of records.

As described above, one basic visual tool implemented by the invention for viewing information is a "galaxy view" as produced by the galaxy tool 350a. A galaxy view is shown in window 120 of Fig. 1. The galaxy view is a two-dimensional scatter graph in which records are organized and depicted in groups (or "clusters") based on relationships between one record and another. In addition to this galaxy view tool, the invention provides numerous interactive visual tools that allow a user to explore and discover knowledge.

Fig. 13 describes one method for displaying information interactively, in the form of two-dimensional line charts. The method begins with the user selecting a set of records and a set of attributes associated with those records (stage 1305). The attributes may comprise any of numerous data types, including the following: numeric, text, sequence (e.g., protein or DNA sequences), or categoric. The selected attributes are converted into numerical values, as discussed above.

Next, a two-dimensional line chart is generated to visually depict the records and their associated attributes (stage 1315). Fig. 14 represents an implementation of two-dimensional charts that are consistent with the invention. Fig. 14 contains line chart 1405, and legends 1440 and 1450.

Chart 1405 contains a collection of superimposed line charts that depict a set of records. For example, line chart 1420 depicts one record

within the set, while line chart 1425 depicts another. In the line charts, the x-axis (e.g., as shown by 1410) represents attributes associated with the records, and the y-axis (e.g., as shown by 1415) represents the value of each attribute. The scale of each axis and the colors of the line charts may
5 be modified by the user. Although this description focuses on line charts, other types of charts may be used to depict a set of records, as shown for example by the point chart shown as 1505 in Fig. 15. Legend 1440 contains a text-based description of records. For example, legend 1440 contains a record described as "122C", as shown by 1445. Legend 1450
10 contains a text-based description of attributes.

Methods consistent with the invention can also generate a two-dimensional line chart that shows relationships between the records shown in 1405 (stage 1320). For example, Fig. 14 shows a line chart 1430 that depicts a statistical value corresponding to the set of records shown in
15 1405. In the example shown in Fig. 14, chart 1430 depicts the average attribute value for each record shown in 1405. In alternative implementations, however, chart 1430 may depict other relevant characterizations of the set of records, such as median attribute values, standard deviations (as shown by 1435), etc.

20 In addition to viewing the information in graphical form, the user can interact with the line charts. The invention is capable of receiving input from a user selecting a portion of a chart (stage 1325). This may be achieved, for example, by using a device to point to a portion of map 1405 or by clicking a pointing device on a portion of map 1405. In response to

this user input, the text-based description of the selected record and/or attribute is highlighted in legends 1440 and 1450 (stage 1330). In the example shown in Fig. 14, the user has selected record "122C", as shown by the highlighting in legend 1440. Similarly, the value of a particular attribute being pointed to in charts 1405 or 1430 can be displayed in text format. In the example shown in Fig. 15, the user has selected attribute "RBC", as shown by the highlighting 1515 in the legend and 1520 on the x-axis.

Furthermore, any selections made by the user on charts 1405 or 1430 are propagated to other views. For example, in response to receiving input from a user selecting a record on chart 1405, an index, as discussed above, is analyzed to determine if the record is shown in another view (stage 1335). If the record is shown in another display (stage 1340), the visual representation of that record in the other view is altered (stage 1345). Fig. 16 is a diagram showing both (1) charts 1405 and 1430, and (2) a galaxy view 1605 of records. If a record is selected on map 1405, the record is highlighted in galaxy view 1605, and vice versa. Similarly, the group of records shown on map 1405 may be highlighted in galaxy view 1605 (as shown by 1610), and vice versa.

Fig. 17 describes another method of displaying information interactively, in the form of summary miniplots. The method begins with the user selecting a set of records and a set of attributes associated with those records (stage 1705). The attributes may comprise any of numerous data types, including the following: numeric, text, sequence (e.g., protein or

DNA sequences), or categoric. The selected attributes are converted into numerical values, as discussed above (stage 1710).

Next, a two-dimensional scatter chart is generated to visually depict the records (stage 1715). An example of such a chart is galaxy view 1805 shown in Fig. 18. Galaxy view 1805 contains a collection of records, one example of which is shown as 1810. The records within galaxy view 1805 are organized into groups (or clusters) (stage 1720), based on relationships between one record and another.

For each group shown in galaxy view 1805, a two-dimensional line chart (summary miniplot) is generated that depicts some information about the records contained within that group (stage 1725). Each such summary miniplot is superimposed onto the two-dimensional scatter chart, based on the location of the group of records on the scatter chart (stage 1730). For example, chart 1805 contains a group of records 1815, for which summary miniplot 1820 represents the average attribute values. In the example shown, summary miniplot 1820 is superimposed at the centroid coordinate for the records in group 1815.

In alternate implementations, summary miniplots may be used to represent other groupings of record. For example, the records shown in a scatter chart may be grouped into quadrants of the scatter chart; and four summary miniplots could be used to represent the quadrants. Furthermore, each line charts, such as line chart 1820, can also be coded in a variety of ways (e.g., size, color, thickness of lines, etc.) to represent additional information (e.g., the variability within the group's records, the value of an

unrelated field, etc.).

In addition to viewing the information in graphical form, the user can interact with the summary miniplots. The invention is capable of receiving input from a user selecting a summary miniplot (stage 1735). This may be
5 achieved, for example, by using a device to point to a portion of map 1805 or by clicking a pointing device on a portion of map 1105. In Fig. 18, the user input constitutes selecting group 1825, as shown by the fact that group 1825 is highlighted. In response to this user input, a graph is generated that contains a series of superimposed line charts, with each line
10 chart representing a record (stage 1740). An example of such a graph is shown in Fig. 18 as 1830, which is a series of superimposed line charts that represent attribute values for the records selected by the user in group 1825.

Furthermore, any selections made by the user of a summary
15 miniplot on chart 1805 is propagated to other views. For example, in response to receiving input from a user selecting summary miniplot 1820, an index, as discussed above, is analyzed to determine if the records represented by summary miniplot 1820 are shown in another view (stage 1745). If the records are shown in another display (stage 1750), the visual
20 representation of the records in the other view are altered (stage 1755). Similarly, if a user selects a record in another view, the summary miniplot corresponding to that record can be highlighted.

The preceding visualizations provide the opportunity to query records by attributes represented, e.g., by categorical and numerical values

and by sequence of text content. Because the visualizations support a limited number of queries, the visualizations cannot analyze large associations efficiently. A multiple query tool creates a visualization that provides an overview of a large number of comparisons automatically, presenting the user with information, e.g., about associations and their expectation. Further, the multiple query tool also provides information about associations between clusters and attributes as well as associations between sets of attributes.

Fig. 19 provides an illustration of a multiple query tool visualization according to the present invention. The multiple query tool produces a visualization in the form of an interactive matrix that displays the requested associations and permits access to the underlying information. For example, the multiple query tool can provide links back to other open visualizations and tools, or stand alone as a separate visualization.

Fig. 20 illustrates a process of creating a visualization using the multiple query tool. As shown in step 2010, the user accesses the multiple query in any common manner of a graphical user interface, for example, a tool bar button, a previous visualization menu, a pop-up box, or a main menu.

Visualization of data begins with the selection of a data file. As shown in step 2020, a user selects a data file of interest. Alternatively, the data file can be preselected, when, e.g., the multiple query visualization is linked to another visualization analysis.

After a data set is selected, as shown in step 2030, the user sets the

type of query. As shown in Fig. 21, a dialog box can be displayed to the user with a drop-down menu of query types. While Fig. 21 shows a selection between query types records vs. attributes, attributes vs. attributes, current data vs. historical data, and current data vs. expert data, other query types are within the scope of the invention. Once selected, the drop-down menu is rolled up to display only the selected query.

Upon selection of a query type, a dialog box specific to the query type is displayed so that the user can set the parameters of the query. Figs. 22A-4C display exemplary parameter-setting dialog boxes for query types shown in Fig. 21.

For example, Fig. 22A, a record vs. attributes query dialog box 2200 is displayed. In this query, records are correlated to selected attributes. In one of its aspects, the records can be viewed as clusters of the records, for example, as clusters such as those defined in the galaxy view of a previous visualization or those defined using any other process. Fig. 22A displays four attribute sources, although other sources could be displayed.

In attribute source area 2210, labeled 'Vocabulary Word(s),' of dialog box 2200, the user types in the word or words that serve as attributes. For multiple words, a delimiter, such as a semicolon, could be used to separate entries. Other processing could also intelligently separate the words. Also, logical operators, such as Boolean AND, OR, NOT, could be included to produce a single composite attribute.

Also, the user can identify attribute words by pointing to a text file that contains a list of words. The user can identify the text file in attribute

source area 2220, labeled 'Vocabulary File.' One format for this list would be a single keyword per line or a single phrase per line. With the text file, synonyms can also be identified. Vocabulary files including synonyms may have the following formats in one aspect of the present invention:

5 Format 1
Keyword1: alt_word1A; alt_word1B
Keyword2:
Keyword3: alt_word3A

10 Format 2
Keyword1
- alt_word1A
- alt_word1B
Keyword2
15 Keyword3
- alt_word3A

The processing of the identified text file will operate on files of the format(s) of existing user files, so as to avoid issues of file format
20 conversion.

Fig. 22A also illustrates attribute source areas 2230 and 2240 for categorical values. In attribute source area 2230, labeled 'Category Field(s),' the user types in the category or categories that serve as attributes. For multiple categories, a delimiter, such as a semicolon, could
25 be used to separate entries. Other processing could also intelligently separate the categories. Also, logical operators, such as Boolean AND, OR, NOT, could be included to act on categories to produce a single composite attribute. 2250 illustrates an area to access selectable menu of categories in the database, in the format of, e.g., a drop-down box. To
30 develop the menu, each record in the database is parsed to identify all possible categorical values.

In attribute source area 2240, labeled 'Category File,' the user can identify attribute categories by pointing to a text file that contains a list of categories. Selecting categories from a file enables to the user to specify easily the order in which the categorical values would be displayed in the visualization and to allow the user to specify a hierarchy for those values. One format for the categorical value file is:

	categorical_value_1	1	(tab delimited lines with value indicating
10	categorical_value_1.1	2	hierarchy level)
	categorical_value_2	1	
	categorical_value_2.1	2	
	categorical_value_2.2	2	
15	categorical_value_2.2.1	3	

Further, to collapse the number of attribute columns, the categories could be combined, similarly to the use of synonyms, or, for hierarchical categorical data, the user could select a maximum hierarchical level. As shown in step 2040 of Fig. 20, after the user selects the attributes, the database is queried using the multiple query. In step 2050, the results of the multiple query are used to create a query matrix.

For example, as shown in Fig. 23, from the attribute words or categories, the multiple query tool creates a query matrix of record rows and attribute columns. The cells of the matrix are set to binary values indicating the presence or absence of the attribute in each record. When a vocabulary file with synonyms is used, a single matrix cell should be created for each keyword, and the cell is marked if either the keyword or any of the alternate forms are found. One method of determining the presence of attribute would be to search the original data file or any indexed files describing the distribution of words or categorical values within the data set.

Following creation of the query matrix, the query matrix is visualized, in step 2060. One visualization is a binary, co-occurrence scheme, as shown in Fig. 24, where cells having a value of "1" are marked in a color or shade, 2410, while cells having a value of "0" are marked in a different color or shade, 2420. The user can select a size of cells, so that more cells or less cells are shown in a display of the visualization.

To minimize the display, the user can select a visualization based on cluster rows. When large numbers of records are to be analyzed, the cluster row visualization could be set as the default.

10 In this case, as shown in Fig. 25, the cells of the visualization matrix are set to indicate the presence or absence of the attribute in each record. To set the cell values, the query matrix is created or processed to create a composite value for a cell, for example, a basic scheme would involve summing the binary co-occurrence scores for a cluster and dividing by the
15 number of records in the cluster.

When the matrix using cluster rows is visualized in step 2060, cells are colored or shaded to indicate their composite values. Fig. 25 shows a binary co-occurrence shading scheme that illustrates the query matrix of Fig. 23, if records 1 and 2, 3 and 4, and 5 and 6 are assumed to be in
20 clusters 1, 2, and 3, respectively. To enhance the interactive nature of the visualization, as shown in Fig. 26, an overall visualization can be displayed as a three-dimensional view of the rows vs. columns vs. values, with the value of each cell represented by a cube at an appropriate height on the Z-axis. The overall visualization is rotatable, so that the user can view 2-D
25 scatter plots corresponding to the rows and columns. A 2-D row scatter plot is shown in Fig. 27.

Another more complex visualization, however, serves as the default

when cluster rows are used. In this alternative visualization of cluster rows, the cells show association probabilities. The scheme of showing association probabilities would be to represent deviations as a difference from an expected value under a random distribution assumption. To
5 calculate expected values, the total number of records containing each attribute, or the sum of the columns of the query matrix, is computed. Lower than expected values could be, for example, cool colors (blue (= -1) to green) and higher than expected will be hot colors (inverted black body with red = 1). Deviations from an expected value under a random
10 distribution assumption could also be represented as a ratio. Also, the probability of observing a number of attributes in a cluster of this size given this many total number of attributes are randomly distributed over all the clusters could also be represented. In this case, the values will range from 0 to 1 and the color display would have blue = 0, white = 0.5, and red = 1;
15 for example. To highlight extreme behaviors, the scale could be non-linear so that only the very high and very low probabilities are highlighted.

To compute association probabilities either an exact or approximate method is used for each of the association methods of the present invention. The exact method is precise at the cost of being computationally
20 intensive. The approximate method can reduce the number of computations when the total number of objects and total number of occurrences of the attributes are relatively large. Further, the use of the laws of logarithms to reduce products and quotients to sums and differences, respectively, and exponentiation to a product will also save
25 computing time.

The probability of observing what is observed given a random distribution indicates the possibility of observing certain number of occurrences of an attribute in a given cluster if the attribute is randomly distributed over all clusters. The lower the probability, the further the attribute distribution deviates from randomness. Described below are the exact method and approximate method for calculating this probability.

Equation 1 provides the exact method. Equation 1 is the discrete density function for a random variable having a hypergeometric distribution. The numerator consists of the product of two terms. The first term calculates how many ways to choose exactly m attributes out of M possible for the cluster of interest; the second term calculates the ways to assign the other (n-m) attributes which are not in the cluster of interest to the other clusters collectively. The denominator calculates the total number of ways to assign N objects to a cluster of size n.

$$p = \frac{\binom{M}{m} \binom{N-M}{n-m}}{\binom{N}{n}}$$

Equation 1.

where N : total number of objects in the data set

M : total number of occurrence of the attribute

n : number of objects in the given cluster

m : number of occurrences of the attribute in the given cluster

$$\binom{N}{n} = \frac{N!}{n!(N-n)!} : \text{combination number of } n \text{ out of } N.$$

Equation 2 provides the approximate method. Equation 2 is the discrete density function for a random variable having a binomial distribution, where the probability of a success is M/N and the probability of failure is $(1-M/N)$. When N and M are large, $(N-n)/(N-1)$ is close to one; thus, Equation 2 provides a reasonably good approximation to the hypergeometric distribution. N , M , n , and m denote the same quantities as defined above in Equation 1.

10

$$p = \binom{n}{m} \left(\frac{M}{N}\right)^m \left(1 - \frac{M}{N}\right)^{n-m} \quad \text{Equation 2.}$$

Alternatively, the association probability can be represented as a measure of an unusual number of occurrences, which is a deviation of observed occurrence from the expected occurrence if the attribute is randomly distributed over all clusters. An exact method (Equation 3) or an approximate method (Equation 4) can be used. N , M , n , and m denote the same quantities in Equation 1. Note that the expectation is the sum over the range of the random variable of x of x multiplies $p(x)$. Equation 3 uses hypergeometric distribution and Equation 4 uses a binomial method, similar to Equations 1 and 2, respectively. The exact method is very computationally expensive due to the summation, while summation in the approximate method can be calculated through and written into the simple form of Equation 4.

25

$$E = \sum_{k=1}^n k \frac{\binom{M}{k} \binom{N-M}{n-k}}{\binom{N}{n}}$$

Equation 3.

$$E = n \frac{M}{N}$$

Equation 4.

5

The deviation from expected occurrence can be measured using either ratio or difference of the observed number of occurrences over (or from) the expected number of occurrences. The range of the ratio is between zero and infinity. A ratio value further away from 1 indicates a larger deviation from randomness.

10

$$Dev = \frac{m}{E}$$

Equation 5.

15

Alternatively to make the deviation more comparable for various sizes of clusters, the difference between observed and expected occurrences is divided by the size of the cluster (Equation 6). Therefore, the range of this deviation measure is normalized between -1 and 1. A value further away from zero indicates a larger deviation from randomness.

20

$$Dev = \frac{m - E}{n}$$

Equation 6.

While the order of attributes along the columns and the order of rows or clusters along the columns of the matrix can be selected by the user,

using a menu item or by dragging rows and columns to new positions. For example, the order of the records or the order of the clusters is automatically set to same correlation order as known to those skilled in the art. The default display for attributes is based on correlation order, with the attribute having the highest column sum being on the left-hand side.

Thus, visualizations for the record vs. attributes query type is explained. The processing involved in creating the query matrix and visualization for the remaining query types is similar to the process of records vs. attributes query type.

10 If the user selects an attribute vs. attributes query type in step 230, as shown in Fig. 22B, an attributes vs. attributes query dialog box 2260 is displayed. The attributes vs. attributes query type is not interested in occurrences with specific records, only in defining the associations among attributes.

15 Query dialog box 2260 operates similarly to records vs. attribute query dialog box 2200, except that the user will be specifying two sets of attributes (vocabulary words or categories).

When querying the database in step 2040 and creating the query matrix in step 2050, the matrix cell scores are generated as a cumulative measure of the number of records that contain both test attributes. Then, the score should be normalized against the number of records. In other words, for n records, i row attributes, and j column attributes:

```

    for row_attribute = 1 to i
      for column_attribute = 1 to j
        score(i,j)=0
        for record=1 to n
5          if record contains both row_attribute(i) and column_attribute(j),
            then score(i,j)=score(i,j)+1
          next record
        norm_score(i,j)=score(i,j)/n
        next column_attribute
10      next row_attribute

```

Also, the total number of records that have each attribute is counted so that deviation from expected frequency can be calculated.

In step 2060, the attribute vs. attribute visualization follows the same
 15 mechanics as for records vs. attributes, but with a few differences.

Specifically, in the default view for the attributes vs. attributes visualization, the default order for both axes would be the correlation order, with the column with the highest total score (e.g., the highest average value) on the top or left, and the default mode for showing associations uses deviation
 20 from expectation using with lower than expected values shown as cool colors (blue (= -1) to green) and higher than expected shown as hot colors (inverted black body with red =1).

Another use of the multiple query tool visualization is rapid assessment of the correlation between the current experiment being
 25 analyzed and historical data. Such a visualization points to the similarities or differences for all equivalent data points (record and condition).

As shown in Fig. 22C, a current data vs. historical data query dialog box 2270 is displayed when the user selects such a visualization. A file containing a data matrix is used as the historical data. In other words, the

user would select the files of a prior visualization. Alternatively, a data matrix, similar to those currently used to input data into the numerical engine, could be designated.

In step 2040, the method determines where the current and
5 historical experiments overlap. For example, if the current experiment contains records 1 through 10 and the historical experiment contains records 1 through 5 and records 8 through 12, then correlations would only be performed with the common records 1 to 5 and 8 to 10. Similarly, if the current experiment used conditions (components) A through E (e.g., 5 time
10 points or distinct treatments) and the historical experiment used conditions A, C, D, and F, then the correlation would be calculated only using the common conditions A, C, and D.

In step 2050, a query data matrix would then be created comparing the common entries. For record1, a correlation with the historical data set
15 would be performed using all the common conditions (intersection). In the example given, this would be a correlation between $\text{current_record1}(A,C,D)$ and $\text{historical_record1}(A,C,D)$. A similar score would be derived for each record present in both data sets. For a record in the current data set that is not present in the historical set, the query matrix would be blank (or set to
20 some flag). The calculations would be repeated for each historical set requested.

In step 2060, the query matrix is visualized as follows. The color code in each cell is based on the correlation of that record to its counterpart in the historical data. The correlation values will range from -1 to $+1$ and be

presented using, for example, a modified rainbow with negative correlations being cool colors (blue = -1) and positive correlations being hot colors (red = 1). For records that are not shared with the historical data set, the matrix cell should have no color (or be colored the same as the background) or, alternatively, these cells can be hidden. If the cells not shared with the historical data set are shown, the degree of overlap between the current and the historical data sets can be visualized. This visualization could also be selected as a separate visualization that shows the overlap, for example by using a gray-scale color code in the matrix, where black indicates full overlap with the historical data components and white indicates no overlap. This query type would also be useful with other data mining tools.

Instead of comparisons of the records of the current and historical data, cluster assignments from one experiment to the next, even when the experiment types are quite different, can be compared. For each record in a current data cluster, the method can assess what fraction of other current cluster records exist in the same cluster in the historical set. Then, an average of the results from each current cluster record is computed to get a score for that cluster. Another example assesses, for each record in a current cluster, what fraction of other current cluster records are found in the historical data within x Euclidean distance. An interactive slider would allow the user to change x and the method would allow viewing of the results dynamically.

When records are combined into clusters, the overall value for the

cluster will be represented as the average or other statistical measure, such as median of the record correlations, based only on those records that are common between the data sets. An indication of variation is provided since a cluster that contains 10 records with a correlation of 0.8 and a
5 cluster that contains 10 records with a correlation of .9 and 1 with a correlation of -1 (both cluster with average of 0.8) may be of different interest to the user. Such an indication can be achieved using multiple visualizations, for example by duplicating the previous query, that simultaneously show the average and the standard deviation, the minimum
10 value or the maximum value.

The default order of clusters and records in this visualization should be the same as in the records vs. attributes query tool. In addition, a row is added that summarizes the comparison of the entire current data against each historical data set. For example, a row labeled "Summary" will be the
15 average of all record correlations.

Alternatively, the user or system could identify specific records to group together at the top of the visualization. For example, all the controls could be grouped together as opposed to in separate clusters. Also, while only one set each of current and historical data is used, several sets data
20 could be visualized contemporaneously. That is, any one of the data sets is treated as the prototype against which others are measured. A slider bar having each visualization would allow the user to run through multiple experiments. The progress through the slider (data sets) could be semiautomated to play like a movie, stopping whenever certain similarities

or dissimilarities are found.

The 'current data vs. literature/expert knowledge' query is similar to the other queries. Correlations between the current data and the literature or expert knowledge are defined either as what records have previously
5 been found to group together or as similarity to actual published/historical values.

Regardless of the query type, the visualization, as shown in Fig. 19, will be displayed in an interactive area of a display screen, so that the user may adapt the visualization to her preferences.

10 For example, to provide commands, the visualization could include a menu bar and a toolbar. A menu bar 1010, with associated sub-menus, of the visualization could include the features shown in Fig. 28.

The Duplicate command in the File menu of menu bar 2810 allows access to previously stored queries, so that the user can either re-run or
15 adjust a previously run multiple query. The other commands in the File order are self-explanatory.

The Row Order menu of menu bar 2810 provides option for organizing the records, clusters, or row attributes. The Cluster from View command results in a correlation ordering for the records and clusters (if
20 correlation ordering was not done for the view, then it is also not done here in the default), as discussed above this ordering is the default for a records vs. attributes query type or a current data vs. historical data query type. The Correlation with Columns command is an option for recalculating the cluster order based on the values in the query matrix. In a cluster view,

records would remain with their cluster and the clusters are reordered according to correlation ordering. If a cluster was expanded to show records, the records in the cluster would be reordered according to correlation ordering. As discussed above, for an attributes vs. attributes query, correlation with columns is the default.

The Advanced sub-menu of the Row Order menu allows access to the following commands. The Cluster Based on Column Values command recalculates the clustering of the records or the attributes using the scores along the row as the vectors for clustering. The user would have the choice of using any clustering algorithm, such as either the hierarchical or partition methods. The Sum command is an option to order the records or attributes based on the sum of the scores across the row, with the record/attribute with the highest sum being at the top and the lowest being at the bottom, for example. Rows having a value below a predetermined threshold could be placed in a low value row or removed from the visualization matrix. The Sum command is not valid for visualization using clusters and would be deactivated. The File Order sets the order of clusters or attributes to that specified by the user, for example in an input file. If no file is provided or record rows are selected, this option would be deactivated.

The Column Order menu of menu bar 2810 provides analogous options as the Row Order menu for organizing the column attributes, expect that there will be no clustering from the view, as records and clusters do not appear in the columns, in one aspect of the present

invention.

To provide the user the ability to choose a custom coloring scheme, the Color menu of menu bar 2810 permits a selection of display colors within the multiple query tool.

5 A tool bar is also provided in the visualization, either as a separate pop-up area or a bar, for example, located below a status bar, to provide access to functions with a single click. Fig. 29 illustrates examples of functions of a tool bar.

The RecordViewer function displays the currently highlighted record
10 (or records in the highlighted cluster). For a record vs. attribute cell, this shows the single record with the specific attribute highlighted in the record. For a cluster vs. attribute cell, the RecordViewer shows all the records in that cluster with the specific attribute highlighted in the records. For an attribute vs. attribute cell, the RecordViewer would display all records that
15 contain both attributes, with both attributes highlighted. To access the records, the RecordViewer calls a process that parses the data source file in the galaxy cluster view. An interpretation tool, such as the plot data tool, could also be provided. A double click on a cell can also call the RecordViewer function.

20 The Zoom function operates similarly to a zoom in the galaxy visualization. Primarily, the zoom will zoom out, so that an overview of a large multiple query tool can be obtained. The maximum zoom out should be based on the number of records and a user's desired minimum resolution, so that the colors of the visualization will be readily discernable.

A possible default size for a cell in the multiple query tool is 12 by 12 pixels. This is large enough to display text labels at 10 point Helvetica for both rows and columns. Zooming out would provide an overview for large data sets. The Zoom Reset function returns the visualization to its default size.

5 The Pan function takes the form of a hand and allows the user to drag the graphic around the window, so that area hidden by display objects or the physical dimensions of a display screen can be viewed. Scroll bars, as shown in the multiple query tool above, could be employed instead of, or in addition to, the Pan tool. Nevertheless, labels for the rows and columns
10 would always remain visible.

 The Expand Row Clusters and Expand Column Clusters functions open the selected cluster(s) to display all their records or attributes as separate rows. If no clusters are selected, all clusters are expanded. If no clusters are defined (either from the associated view or by having done a
15 cluster ordering within the multiple query tool), these functions are deactivated.

 The Collapse Row Clusters and Collapse Column Clusters functions closes the cluster that contains the selected record(s) or attribute(s). If no record or attribute is selected, all clusters are collapsed. If no clusters are
20 defined (either from the associated view or by having done a cluster ordering within the multiple query tool, these functions are deactivated. Although not illustrated in Fig. 29, a single button could also collapse all row and columns with a deviation from expectation between, e.g., -.5 and +.5 (or other definable range) into a single group or remove rows and

columns that do not have values above a predetermined threshold.

The Orient Rows vs. Values and Orient Columns vs. Values functions orient the visualization so that the view is perpendicular to the row axis or column axis, respectively. This provides views of the 2-D scatterplot, as shown in Fig. 27, for example. The Reset Orientation function orients the visualization to the default 'overhead' view showing rows vs. columns.

The Spacing Toggle function toggles the matrix between the two types of views shown in Figs. 30A and 30B. Providing a grid as shown in Fig. 30A allows viewing of cells as discrete entities, for easier selection. Removing the grid, as shown in Fig. 12B, allows more information to be compressed into the same space and could improve enhance structure distinctions in the visualization matrix.

In addition to the command bars, the visualization area itself, as shown in Fig. 19, consists not only of the colored visualization matrix, but also includes labels for the rows and columns.

When the rows are records, the row labels are the record titles. Since record titles may be long, the initial substantially 20 characters could be displayed with a scroll bar or pop-up function to enable viewing of all of the characters. When collapsed into clusters, the row labels are labeled by cluster number. For attributes, the categorical value or vocabulary word itself serve as the label. In addition to the labels themselves, the rows and columns could have a master label indicating the content. For records as rows, the label would say "RECORDS." For vocabulary words input

directly in the initial dialog box, the label would be "VOCABULARY". For vocabulary words input through a file, the label would be the file name. For categories as attributes, the field name would be shown. If multiple fields were requested, each field name would be shown, centered over its
5 collection of row or column labels. The user could also edit or define the row, column, and major labels.

Rows and columns are selected and highlighted by clicking on the row and column labels using a mouse input device, for example. Shift-clicking and control-clicking can be used to select multiple labels.

10 The visualization is interactive. In addition to highlighting labels for selecting rows and columns, clicking on a cell should display key information regarding the cell. This pop-up information would be context sensitive, depending on the type of query and whether the cell represents an individual record or attribute as opposed to a cluster or group. The
15 following provide suggested formats of the key attributes of a cell of the different groups and query types:

For a cell intersecting a record and attribute in a records vs. attributes query:

20 Row: Record_name
Column: Column_attribute_name
Co-occurrence: 0 (or 1)
Attribute found in ###/total_rows records

25 For a cell intersecting a cluster and attribute in a records vs. attributes query:

Row: Cluster# containing ## members
Column: Column_attribute_name
Co-occurrences: ##
Number of co-occurrences expected: ##
30 Deviation from expected co-occurrence: ##
Probability of observation: ##

For a cell intersecting an attribute and attribute in an attributes vs. attributes query:

Row: Row_attribute_name
 Column: Column_attribute_name
 Co-occurrences: ##
 Row attribute found in ##/total_columns columns
 Column attribute found in ##/total_rows rows
 Number of co-occurrences expected: ##
 Deviation from expected co-occurrence: ##
 Probability of observation: ##

For the cell intersecting a record and historical data in a current data vs. historical data query:

Probability of observation: ##
 Row: Record_name
 Column: historical_experiment_name
 Correlation: ## (if this record does not intersect with historical data, 'no intersection')

For the cell intersecting a cluster and historical data in a current data vs. historical data query:

Probability of observation: ##
 Row: Record_name
 Column: historical_experiment_name
 Average Correlation: ## (if this cluster does not contain any genes that intersect with historical data this should say 'no intersection')
 Maximum Correlation: ## with record_name
 Minimum Correlation: ## with record_name
 Records that do not intersect historical data (could be a scrollable list):
 record_name1
 record_name5...

CONCLUSION

Systems and methods consistent with the present invention employ an open architecture that enables different types of data to be used for analysis and visualization.

It will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the invention.

Modifications may be made to adapt a particular element, technique, or implementation to the teachings of the present invention without departing from the spirit of the invention. For example, any genetic material, from organism to microbe, could be represented using the context
5 vectors of the present invention. Further, the present invention is not limited to genetic material, and any material or energy could also be represented. Additionally, the rows and columns used in the description are illustrative only, and, for example, records could be placed along the columns. Also, the attributes used are not limited to text and categorical
10 features. Numerical values could be set as attributes, for example using binning where adjacent ranges of numbers are defined. Additionally, for queries against individual records, categorical data could be presented in a single column rather than multiple columns for each categorical value as described above; in this case, the occurrence of a specific categorical value
15 could be represented as a specific color. The resulting matrix could also be dynamically controllable by the user. The order of rows or columns could be adjusted by dragging or sorted according to the information within the row or column.

Moreover, although the described implementation includes software,
20 the invention may be implemented as a combination of hardware and software or in hardware alone. Additionally, although aspects of the present invention are described as being stored in memory, one skilled in the art will appreciate that these aspects can also be stored on other types of computer-readable media, such as secondary storage devices, like hard
25 disks, floppy disks, or CD-ROM; a carrier wave from the Internet; or other forms of memory.

Therefore, it is intended that this invention not be limited to the

particular embodiment and method disclosed herein, but that the invention include all embodiments falling within the scope of the appended claims.

APPENDIX A**Example Data Set Properties File**

```
CORPUS_TYPE=1
5 VIEW=protein.aa\ gene.expression
  source_file_0.com.bmi.vision.api.FastaDataFile.format=
  source_file_class_0=com.bmi.vision.api.FastaDataFile
  source_file_0.
  com.bmi.vision.api.FastaDataFile.fullpath=/home/battelle/omniviz_dat
10 a/sources/yeast.fasta
  number_sources=1
```

APPENDIX B

>MJ0001 aspartate aminotransferase

5 MISSRCKNIKPSAIREIFNLATSDCINLGIGEPDFDTPKHII EAAKRALDEGKTHYSPNN
GIPELREEISNKLKDDYNLDVDKDNII VTCGASEALMLSIMTLIDRGDEVLPNPSFVS
FSLTEFAEGKIKNIDLDENFNIDLEKVKESITKTKLIIFNPSNPTGKVYDKETIKGLA
EIAEDYNLIIVSDEVYDKIIYDKKHYSMPQFTDRCILINGFSKTYAMTGWRIGYLAVSDE
LNKELDLINMIKIHQYSFACATTFAQYGALAALRGSQKCVEDMVREFKMRRDLIYNGLK
DIFKVNKPDGAFYIFPDVSEYGDGVEVAKKLIENKVLCPGVAFGENGANYIRFSYATKY
10 EDIEKALGIIKEIFE

>MJ0002

MEIFMEVPFVVISGSDLYGIPNPSDVIDIRGAHILDRELFKKNCLYKSKEEEVINKMPGK
CDFVSFELGKFLRELLKPNANFIEIALSDKVLYSSKYHEDVKGIAYNICCKLYHHWKGF
AKPLQKLCEKESYNNPKTLLYILRAYYQGILCLESGEFKSDFSSFRCLDCYDEDIVSYLF
15 ECKVNKKPVDES YKKIKSYFYELGVLLDESYKNSNLIDEPSETAKIKAIELYKKLYFED
VRE

>MJ0003

MKGKRIAIVSHRILNQNSVVNGLERAEGAFNEVVEILLKNNGYIIQLPCPELIYLGIDRE
GKTKEEYDTKEYRELCKKLEPIIKYLQYKKNYKFILIGIENSTTCDIFKNRGILMEE
20 FPKVEKLNIIKAIEYKNEKDYNKFVKTLEKMIK

>MJ0004 activator of (R)-2-hydroxyglutaryl-CoA dehydratase

MILGIDVGSTTTKMVLMEDSKIIWYKIEDIGVVEEDILLKMVKEIEQKYPIDKIVATGY
GRHKVSFADKIVPEVIALGKGANYFFNEADGVIDIGQDTKVLKIDKNGKVVDFILSDKC
AAGTGKFLKALDILKIDKNEINKYKSDNIAKISSMCAVFAESEIISLLSKKVPKEGILM
25 GYYESIINRVIPMTNRLKIQNIVFSGGVAKNKVLVEMFEKKNLKKLLIPKEPQIVCCVGA
ILV

>MJ0005 formate dehydrogenase, beta subunit

MKYVLIQATDNGILRRAECGGAVTALFKYLLDKKLV DGV LALKRGEDVYDGIPTFITNSN
ELVETAGSLHCAPT NFGLIAKY LADKKI AVPAKPCDAMAI RELAKLNQINLDNVYMIGL
30 NCGGTISPITAMKMIELFYEVNPLDVVKEEIDKGKPIIELKNGEHKAVKIEELEEKGFGR
RKNCQRC EIMIPRMADLACGNWGAEGWTFVEICSERGRKLVEDAEKDG YIKIKQPSEKA
IQVREKIESIMIKLAKKFQKKHLEEEYPSLEKWKKYWNRCIKCYGCRDNCPLCFVCECSL
EKDYIEEKGKIPPNPLIFQIRLSHISQSCINCGQCEDACPM DIPLAYIFHRMQLKIRDT
LGYIPGV DNSLPPLFNIER

35 >MJ0006 formate dehydrogenase, alpha subunit

MKVVHTICPGCSVGGIDLIVKDDKVVGTYPYKRHPINEGKNCSNGKNSYKIIYHEKRLK
KPLIKKNGKLVEATWDEALS FIAEKLKNYNADDITFIASGKCTNEDNYALKKLVD SLKAK
IGHCICNSPKVNYAEVSTTIDDIENAKNIIIGDVFSEHALIGRKVIKAKEKGSKVTIFN
TEEKEILKLN ADEFVKVDSYLGVDLSNV DKN TIIINAPVNVDEI IKTAKENKAKVLPVA
40 KHCNTVGATLIGIPALNKDEYFELLKNSKFLYIMGENPALVDKDVLKNVEFLVVQDIIMT
ETAEMADVVL PSTCWA EKDGTFINTDKRIQKINKAVNPPGDAMDDWLI IKS LAEKLGS DL
GFNSLEDIQQDIHRNKLL

>MJ0007 2-hydroxyglutaryl-CoA dehydratase, subunit beta

MMKLKAIEKLMQKFASRKEQLYKQKEEGRKVFGMFCAYVPIEII LAANAIPVGLCGGKND
45 TIPIAEEDLPRNLCP LIKSSYGFKA KATCPYFEASDIVIGETTCEGKKMFELMERLVPM
HIMHLPHMKDEDSLKIWIKEVEKLKELVEKETGNKITEEKLKETVDKVNKVRELFYKLYE
LRKNKPAPIKGLDVLKLFQFAYLLDIDDTIGILEDLIEELEERVKKGEGYEGKRILITGC
PMVAGNNKIVEIIIEVGGVVVGEESCTGTRFFENFVEGYSVEDIAKRYFKIPACACRFKND
ERVENIKRLVKELDVG VVYTLQYCHTFNIEGAKVEEALKEEGIP IIRIETDYS ES DRE
50 QLKTRLEAFIEMI

>MJ0008

MFCGSMIAICMRSKEGFLFNKLM DWGLHYNPKIVKDNNIIGYHAPILDLDKKESIIILK
NIIENIKGRDYLTIIHLNGKYGKINKETLIENLSIVNEFAEKNGIKLCIENLRKGFSSNP
NNIEIADEINCYITFDVGHIPYNNRLEFLEICSDRVYN SHVYEIEVDGKHLPPKNLNL
55 KPILDRLLDIKCKMFLIELMDIKEVLRTERMLKDYLEMYR

>MJ0009

MIFNENTPNFIDFKESFKELPLSDETFKIIENG IKLREIAIGEFSGRDSVA AIKAIEE

GIDFVLPVVAFTGTDYGNINIFYKNWEIVNKRIKEIDKDKILLPLHFMFEPKLWNALNGR
WVLSFKRYGYRRCIGCHAYLRIIRIPLAKHLGGKIISGERLYHNGDFKIDQIEEVLNV
YSKICRDFDVELILPIRYIREGKKIKEIIGEEWEQGEKQFSCVFSGNYRDKDGKVIDKE
GILKMLNEFIYPASVEILKEGYKGNFNLYLNIVKKLI
5 >MJ0010 phosphonopyruvate decarboxylase ~
MRAILILLDGLGDRASEILNNKTPLOFAKTPNLDRLAENGMCGLMTTYKEGIPLGTEVAH
FLLWGYSLEEFPGRGVIEALGEDIEIEKNAIYLRASLGFVKKDEKGFLVIDRRTKDISRE
EIEKLVDSLPTCVDGYKFELFYSDVHFILKIKERNGWISDKISDSDPFYKNRYVMKVKA
IRELCKSEVEYSKAKDTARALNKYLLNVYKILQNHKINRKRKLEKMPANFLLTKWASRY
10 KRVESFKEKWGMNAVILAESSLFKGLAKFLGMDFIKIESFEEGIDLIPELDYDFIHLHTK
ETDEAAHTKNPLNKVKVIEKIDKLIGNLKLREDDLLIITADHSTPSVGNLIHSGESVPIL
FYGKNVRVDNVKEFNEISCSNGHLRIRGEELMHLILNYTDRALLYGLRSGDRLRYIIPKD
DEIDLLEG

APPENDIX C

RECORDKEY

TITLE: Effect of metabisulphite on sporulation and alkaline phosphatase in *Bacillus subtilis* and *Bacillus cereus*

DATE: 1990

The effect of metabisulphite on spore formation and alkaline phosphatase activity/production in *Bacillus subtilis* and *Bacillus cereus* was investigated both in liquid and semi-solid substrates. While supplementary nutrient broth (SNB) and sporulation medium (SM) were used as the liquid growth media, two brands of powdered milk were used as the food (semi-solid) substrates. Under both aerobic and anaerobic conditions, *B. subtilis* was more resistant to metabisulphite than *B. cereus* while the level of enzyme production and spores formed were generally higher under aerobic than anaerobic conditions. The metabisulphite concentrations required to inhibit spore production as well as alkaline phosphatase synthesis/activity were found to be relatively low and well within safety levels for human consumption. It is concluded that metabisulphite is an effective anti-sporulation agent and a recommendation for its general use in semi-solid and liquid foods is proposed.

RECORDKEY

TITLE: Effects of replacing saturated fat with complex carbohydrate in diets of subjects with NIDDM

DATE: 1989

This study examined the safety of an isocaloric high-complex carbohydrate low-saturated fat diet (HICARB) in obese patients with non-insulin-dependent diabetes mellitus (NIDDM). Although hypocaloric diets should be recommended to these patients, many find compliance with this diet difficult; therefore, the safety of an isocaloric increase in dietary carbohydrate needs assessment. Lipoprotein cholesterol and triglyceride (TG, mg/dl) concentrations in isocaloric high-fat and HICARB diets were compared in 7 NIDDM subjects (fat 32 +/- 3%, fasting glucose 190 +/- 38 mg/dl) and 6 nondiabetic subjects (fat 33 +/- 5%). They ate a high-fat diet (43% carbohydrate; 42% fat, polyunsaturated to saturated 0.3; fiber 9 g/1000 kcal; cholesterol 550 mg/day) for 7-10 days. Control subjects (3 NIDDM, 3 nondiabetic) continued this diet for 5 wk. The 13 subjects changed to a HICARB diet (65% carbohydrate; 21% fat, polyunsaturated to saturated 1.2; fiber 18 g/1000 kcal; cholesterol 550 mg/day) for 5 wk. NIDDM subjects on the HICARB diet had decreased low-density lipoprotein cholesterol (LDL-chol) concentrations (107 vs. 82, P less than .001), but their high-density lipoprotein cholesterol (HDL-chol) concentrations, glucose, and body weight were unchanged. Changes in total plasma TG concentrations in NIDDM subjects were heterogeneous. Concentrations were either unchanged or had decreased in 5 and increased in 2 NIDDM subjects. Nondiabetic subjects on the HICARB diet had decreased LDL-chol (111 vs. 81, P less than .01) and unchanged HDL-chol and plasma TG concentrations). (ABSTRACT TRUNCATED AT 250 WORDS)

RECORDKEY

TITLE: Enteral feeding of dogs and cats: 51 cases (1989-1991)

DATE: 1992

- 5 Feeding commercial enteral diets to critically ill dogs and cats via nasogastric tubes was an appropriate means for providing nutritional support and was associated with few complications. Twenty-six cats and 25 dogs in the intensive care unit of our teaching hospital were evaluated for malnutrition and identified as candidates for nutritional support via nasogastric tube. Four commercial liquid formula diets and one protein supplement designed for use in human beings were fed to the dogs and cats. Outcome variables used to assess efficacy and safety of nutritional support were return to voluntary food intake, maintenance of body weight to within 10% of admission weight, and complications associated with feeding liquid diets. Sixty-three percent of animals experienced no complications with enteral feedings; resumption of food intake began for most animals (52%) while they were still in the hospital. Weight was maintained in 61% of the animals (16 of 26 cats and 15 of 25 dogs). Complications that did occur included vomiting, diarrhea, and inadvertent tube removal. Most problems were resolved by changing the diet or adhering to the recommended feeding protocol. Nutritional support as a component of therapy in small animals often is initiated late in the course of the disease when animals have not recovered as quickly as expected. If begun before the animal becomes nutrient depleted, enteral feeding may better support the animal and avoid serious complications.

- 30 TITLE: Microbiology of fresh and restructured lamb meat: a review
DATE: 1995

- Microbiology of meats has been a subject of great concern in food science and public health in recent years. Although many articles have been devoted to the microbiology of beef, pork, and poultry meats, much less has been written about microbiology of lamb meat and even less on restructured lamb meat. This article presents data on microbiology and shelf-life of fresh lamb meat; restructured meat products, restructured lamb meat products, bacteriology of restructured meat products, and important foodborne pathogens such as Salmonella, Escherichia coli 0157:H7, and Listeria monocytogenes in meats and lamb meats. Also, the potential use of sodium and potassium lactates to control foodborne pathogens in meats and restructured lamb meat is reviewed. This article should be of interest to all meat scientists, food scientists, and public health microbiologists who are concerned with the safety of meats in general and lamb meat in particular.

RECORDKEY

- 50 TITLE: Hyperacute stroke therapy with tissue plasminogen activator
DATE: 1997

- The past year has seen tremendous progress in developing new therapies aimed at reversing the effects of acute stroke. Thrombolytic therapy with various agents has been extensively studied in stroke patients for the past 7 years. Tissue plasminogen activator (t-PA) received formal US Food and Drug Administration approval in June 1996 for use in patients within 3 hours of onset of an ischemic stroke. Treatment with t-PA improves

neurologic outcome and functional disability to such a degree that, for every 100 stroke patients treated with t-PA, an additional 11-13 will be normal or nearly normal 3 months after their stroke. The downside of t-PA therapy is a 6% rate of symptomatic intracerebral hemorrhage (ICH) and a 3% rate of fatal ICH. Studies are under way to determine whether t-PA can be administered with an acceptable margin of safety within 5 hours of stroke, to evaluate the therapeutic benefits of intraarterial pro-urokinase, and to assess the use of magnetic resonance spectroscopy to identify which patients are most likely to benefit from thrombolysis. Combination thrombolytic- neuroprotectant therapy is also being studied. In theory, patients could be given an initial dose of a neuroprotectant by paramedics and receive thrombolytic therapy in the hospital. We are now entering an era of proactive, not reactive, stroke therapies. These treatments may reverse some or all acute stroke symptoms and improve functional outcomes.

RECORDKEY

TITLE: A 12-month study of policosanol oral toxicity in Sprague Dawley rats
DATE: 1994
Policosanol is a natural mixture of higher aliphatic primary alcohols. Oral toxicity of policosanol was evaluated in a 12-month study in which doses from 0.5 to 500 mg/kg were given orally to Sprague Dawley (SD) rats (20/sex/group) daily. There was no treatment-related toxicity. Thus, effects on body weight gain, food consumption, clinical observations, blood biochemistry, hematology, organ weight ratios and histopathological findings were similar in control and treated groups. This study supports the wide safety margin of policosanol when administered chronically.

APPENDIX D

```

NAME= NumericEngine
DESC= Format for source file produced by numeric engine.
END_DESC
5  DELIMITER= RECORDKEY

||F0
  NAME= Title
  TYPE= STRING
10  TAG= TITLE:
  METHOD= LINES:1
  DOC_VECTOR= TRUE
  SEARCH= TRUE
  CORR= FALSE
15  CASE_SENSITIVE= TRUE
  WHOLE_BOUNDARY= FALSE
  LINEPOS= FLOAT
||F1
  NAME= Components
20  TYPE= STRING
  TAG= COMPONENTS:
  METHOD= LINES:1
  DOC_VECTOR= TRUE
  SEARCH= FALSE
25  CORR= FALSE
  CASE_SENSITIVE= TRUE
  WHOLE_BOUNDARY= FALSE
  LINEPOS= FLOAT
||F2
30  NAME= ChipData
  TYPE= NUMERIC
  TAG= ChipData:
  METHOD= LINES:1
  DOC_VECTOR= FALSE
35  SEARCH= FALSE
  CORR= FALSE
  CASE_SENSITIVE= FALSE
  WHOLE_BOUNDARY= FALSE
  LINEPOS= FLOAT
40  ||F3
  NAME= SGD_Name
  TYPE= STRING
  TAG= SGD_Name:
  METHOD= NEXT_TAG
45  DOC_VECTOR= TRUE
  SEARCH= TRUE
  CORR= FALSE
  CASE_SENSITIVE= TRUE
  WHOLE_BOUNDARY= FALSE
50  LINEPOS= FLOAT
||F4
  NAME= Description
  TYPE= STRING
  TAG= Description:
55  METHOD= NEXT_TAG
  DOC_VECTOR= TRUE

```



```
SEARCH= TRUE
CORR= FALSE
CASE_SENSITIVE= TRUE
WHOLE_BOUNDARY= FALSE
5 LINEPOS= FLOAT
||F5
NAME= Location
TYPE= STRING
TAG= Location:
10 METHOD= NEXT_TAG
DOC_VECTOR= TRUE
SEARCH= TRUE
CORR= FALSE
CASE_SENSITIVE= TRUE
15 WHOLE_BOUNDARY= FALSE
LINEPOS= FLOAT
||F6
NAME= Deletion
TYPE= STRING
20 TAG= Deletion:
METHOD= NEXT_TAG
DOC_VECTOR= TRUE
SEARCH= TRUE
CORR= TRUE
25 CASE_SENSITIVE= TRUE
WHOLE_BOUNDARY= FALSE
LINEPOS= FLOAT
||F7
NAME= Peak
30 TYPE= STRING
TAG= Peak:
METHOD= NEXT_TAG
DOC_VECTOR= TRUE
SEARCH= TRUE
35 CORR= TRUE
CASE_SENSITIVE= TRUE
WHOLE_BOUNDARY= FALSE
LINEPOS= FLOAT
||F8
40 NAME= MCB_sites
TYPE= STRING
TAG= MCB_sites:
METHOD= NEXT_TAG
DOC_VECTOR= TRUE
45 SEARCH= TRUE
CORR= TRUE
CASE_SENSITIVE= TRUE
WHOLE_BOUNDARY= FALSE
LINEPOS= FLOAT
50 ||F9
NAME= SFF_sites
TYPE= STRING
TAG= SFF_sites:
METHOD= NEXT_TAG
55 DOC_VECTOR= TRUE
SEARCH= TRUE
CORR= TRUE
```

```

    CASE_SENSITIVE= TRUE
    WHOLE_BOUNDARY= FALSE
    LINEPOS= FLOAT
||F10
5    NAME= Swi5e_sites
    TYPE= STRING
    TAG= Swi5e_sites:
    METHOD= NEXT_TAG
    DOC_VECTOR= TRUE
10   SEARCH= TRUE
    CORR= TRUE
    CASE_SENSITIVE= TRUE
    WHOLE_BOUNDARY= FALSE
    LINEPOS= FLOAT
15   ||F11
    NAME= Sequence_
    TYPE= STRING
    TAG= Sequence_:
    METHOD= NEXT_TAG
20   DOC_VECTOR= TRUE
    SEARCH= TRUE
    CORR= FALSE
    CASE_SENSITIVE= TRUE
    WHOLE_BOUNDARY= FALSE
25   LINEPOS= FLOAT
```

V. WHAT IS CLAIMED IS:

1. A method for analyzing data for different data types,
comprising:
 - selecting a set of attributes associated with an object, the
5 attributes selection from the group consisting of any of the text, numerical,
categorical, or sequence data types;
 - transforming the selected attributes into n-dimensional
vectors;
 - applying transformation operations to the selected attributes;
 - 10 indexing the n-dimensional vector, certain attributes, and a
result of the transformation operations; and
 - displaying a representation of the object based on the
selected attributes.
2. A computer-implementing method of analyzing various data
15 types, comprising the steps of:
 - defining a uniform data structure for representing objects of
different data types;
 - segmenting certain attributes of a plurality of different objects
of different data types into elements that are representable in said uniform
20 data structure; and
 - operating on said certain attributes to produce at least one
representation of said objects based on said uniform data structure.
3. The method of claim 2 wherein said plurality of different data
types comprises a combination of any two of numeric, sequence string,

categorical, or text data types.

4. The method of claim 3 wherein said plurality of different data types comprise a combination of any three of numeric, reference string, categorical, in text data types.

5 5. The method of claim 4 wherein said data types comprise numeric, sequence string, categorical and text data types.

6. The method of claim 2 wherein said step of operating on said selected attributes produces a vector representation of said objects in correspondence with said uniform data structure.

10 7. The method of claim 2 further comprising producing an index that includes second representations of non-selected attributes of a particular object and associating the non-selected attributes with a particular representation of said first representations.

8. The method of claim 6 wherein said first and second
15 representations are vector representations.

9. The method of claim 2 further comprising using a first set of said selected attributes associated with a first set of objects to determine the relationships among the first set of objects of a particular data type and using non-selected attributes associated with said first set of selected
20 attributes to correlate objects represented by said first set of selected attributes with a second set of objects represented by a second set of selected attributes.

10. The method of claim 9 further comprising identifying, using said non-selected attributes, at least one object of said second set of

objects that corresponds to a selected object or objects of said first set of objects.

11. The method of claim 10 further comprising displaying said first and second set of objects in first and second windows on a display screen and highlighting said second set of objects that corresponds to said
5 selected object or objects.

12. The method of claim 2 wherein said step of segmenting comprises creating a plurality of said elements from a sequence of string sequence data.

10 13. The method of claim 12 wherein said step of segmenting comprises selecting words of a text document that meet certain preselected criteria.

14. The method of claim 2 further comprises using said first representation to identify cluster groups of related objects.

15 15. The method of claim 2 further comprising creating two dimensional projections of cluster groups for two dimensional visualizations.

16. A method of identifying relationships among different visualizations of data sets, comprising the steps of:

20 displaying first graphical results of a first type analysis performed on selected attributes of on a first set of objects;

displaying second graphical results of a second type analysis performed on selected attributes of a second set of objects;

selecting certain objects represented in said first graphical

results; and

highlighting corresponding objects represented by said
second graphical results that correspond to said certain objects.

17. The method of claim 16 wherein said step of highlighting is
5 based on attributes not used for creating said first graphical results.

18. The method of claim 17 wherein said first and second set of
objects is the same.

19. A system for producing visualizations for various data types,
comprising:

10 a first data processing engine operative to receive different
types of data;

a second data processing engine operative to modify a first
type of said data to conform said data to a standardized format that is used
in identifying relationships among attributes of objects contained in said
15 data; and

a third processing engine for creating a first high dimensional
vector for a second type of data and for creating a second high dimensional
vector for the modified data, each data type being an input into said engine,
wherein said high dimensional vectors are operative to be compared to
20 identify relationships that exist between the first and second data type.

20. A method of interactively displaying records and their
corresponding attributes, comprising:

generating a first 2-D chart for a first record, wherein at least
two attributes associated with the first record are shown along one axis,

and wherein the values of the attributes are shown along the other axis;

receiving input from a user selecting the first record on the
first 2-D chart;

analyzing an index to determine if the first record is shown in
5 another view; and

if the first record is shown in another view, altering the
visual representation of the first record in the another view based on the
user input.

21. The method of claim 20, wherein the first 2-D chart is a line
10 chart.

22. The method of claim 20, wherein the first 2-D chart is a
scatter chart.

23. The method of claim 20, wherein the user can select the
scale of the axes.

15 24. The method of claim 20, wherein the another view comprises
a galaxy view of groups of records.

25. The method of claim 20, further comprising generating a
second 2-D chart for a second record, wherein at least two attributes
associated with the second record are shown along one axis, and wherein
20 the values of the attributes are shown along the other axis.

26. The method of claim 25, wherein the first 2-D chart is shown
in a first color and the second 2-D chart is shown in a second color.

27. The method of claim 25 wherein the second 2-D chart is
superimposed upon the first 2-D chart.

28. The method of claim 25, further comprising:
displaying text-based descriptions of the first and second
records;
receiving input from the user selecting a text-based
5 description; and
highlighting the 2-D chart of the record corresponding to the
selected description.
29. The method of claim 25, further comprising:
displaying text-based descriptions of each attribute shown in
10 the first and second 2-D charts;
receiving input from the user selecting a text-based
description; and
highlighting the attributes and values in the 2-D chart that
correspond to the description.
- 15 30. The method of claim 25, further comprising generating a third
2-D chart, wherein at least two attributes associated with the first and
second records are shown along one axis, and wherein statistical values of
the attributes are shown along the other axis.
31. The method of claim 30, wherein the statistical values
20 comprise average values.
32. The method of claim 30, wherein the statistical values
comprise median values.
33. The method of claim 20, further comprising displaying a text-
based identification of the record selected by the user.

34. The method of claim 33, further comprising:
receiving input from a user pointing to a portion of the 2-D
chart; and
displaying a text-based identification of the attribute and value
5 corresponding to the pointed portion.

35. The method of claim 20, further comprising:
receiving input from a user selecting a record in another view;
analyzing an index to determine if the record is shown in the
2-D line chart; and
10 if the record is shown in the 2-D line chart, altering the visual
representation of the record in the 2-D line chart.

36. A method of interactively displaying records and their
corresponding attributes, comprising:
selecting a record and its associated attributes, wherein the
15 associated attributes are any combination of numeric, categoric, sequence,
and text information;
converting the associated attributes into numeric values; and
generating a 2-D chart for the record, wherein at least two
attributes associated with the record are shown along one axis, and
20 wherein the values of the attributes are shown along the other axis.

37. A method of interactively displaying records and their
corresponding attributes, comprising:
generating a 2-D scatter chart that depicts a plurality of
records;

generating a 2-D line chart for a group of records contained in a portion of the 2-D scatter chart, wherein at least two attributes associated with the group of records are shown along one axis, and wherein a statistical value for each of the at least two attributes is shown along the
5 other axis; and

superimposing the 2-D line chart at a location on the 2-D scatter chart that is based on the location of the group of records on the 2-D scatter chart.

38. The method of claim 37, wherein the statistical value is an
10 average value.

39. The method of claim 37, wherein the statistical value is a median value.

40. The method of claim 37, wherein the portion is a quadrant.

41. The method of claim 37, wherein the portion is a cluster.

15 42. The method of claim 37, further comprising selecting a color for the 2-D line chart based on user-defined criteria.

43. The method of claim 37, further comprising selecting a size for the 2-D line chart based on user-defined criteria.

44. A method of interactively displaying records and their
20 corresponding attributes, comprising:

selecting a set of records and their associated attributes, wherein the associated attributes are any combination of numeric, categoric, sequence, and text information;

converting the associated attributes into numeric values;

generating a first chart that depicts the set of records;
generating a second chart for a subset of records depicted in
the first chart, wherein at least two attributes associated with the subset of
records are shown along one axis, and wherein a statistical value for each
5 of the at least two attributes is shown along the other axis; and
superimposing the second chart at a location on the first chart
that is based on the location of the subset of records on the first chart.

45. A method for visualization of multiple queries to a database,
comprising:

10 selecting multiple queries to a database;
querying records in the database based on the multiple
queries;
creating a query matrix indexed based on the selecting; and
populating the query matrix based on the querying.

15 46. A method according to claim 45, wherein selecting includes
defining a query of an attribute of a record versus a record in the database.

47. A method according to claim 46, wherein the creating
includes indexing the query matrix using a cluster corresponding to a
plurality of records.

20 48. A method according to claim 47, wherein the populating
includes statistically combining query results for the plurality of records
corresponding to the cluster.

49. A method according to claim 45, wherein the selecting
includes defining a query of a first attribute of a record versus a second

attribute of a record.

50. A method according to claim 45, wherein the selecting includes defining a query of current data versus historical data.

51. A method according to claim 45, wherein the selecting
5 includes defining a query of experimental data versus expert data.

52. A method according to claim 45, furthering including visualizing the populated query matrix.

53. A method according to claim 51, wherein the visualization includes creating a visualization matrix indexed based on the selecting,
10 wherein the visualization matrix is populated using a scale of color corresponding to values of the populated query matrix.

54. A method according to claim 53, further including:
detecting a user selection of a portion of the visualization
matrix; and
15 displaying features of records in the database corresponding to the portion of the visualization matrix selected by the user.

55. An apparatus for visualization of multiple queries to a database, comprising:
an input device which permits a user to select multiple
20 queries to a database;
an database tool to query records in the database based on the multiple queries;
a calculation device which creates a query matrix indexed based on the selecting and populates the query matrix based on the

querying.

56. An apparatus according to claim 55, wherein the multiple queries include a query of an attribute of a record versus a record in the database.

5 57. An apparatus according to claim 56, wherein a cluster indexes the query matrix, a cluster including a plurality of records.

58. An apparatus according to claim 57, wherein query results for the plurality of records corresponding to the cluster are statistically combined.

10 59. An apparatus according to claim 55, wherein the multiple queries include a query of a first attribute of a record versus a second attribute of a record.

60. An apparatus according to claim 55, wherein the multiple queries include a query of a current data versus historical data.

15 61. An apparatus according to claim 55, wherein the multiple queries include a query of experimental data versus expert data.

62. An apparatus according to claim 55, furthering including a display that visualizes the populated query matrix.









FIG. 1

2/48


**FIG. 2A**

3/48

FIG. 2B**FIG. 2C****FIG. 2D****FIG. 2E**

4/48

FIG. 3



5/48

410
NEW DATA SET
400

1. SOURCES

2. FORMAT

DATA SET NAME:

DATA SET TYPE: ☒ ARRAY DATA ☐ PROTEIN OR NUCLEOTIDE SEQUENCES ☐ TEXT

424

DATA SET SOURCES:

/HOME/BATTELLE/OMNIVIZ_DATA/SOURCES/YEAST.CELL.CYCLE/CC.PROT.785.FASTA

420

426

FIG. 4A

6/48

440

NEW DATA SET

1. SOURCES 2. FORMAT

FIELD DELIMITER:

☐ COLON

☐ COMMA

☐ SPACE

☒ TAB


☐ USER DEFINED USER DEFINED DELIMITER:

442


CANCEL SAVE DATA SET CONTINUE TO NEW VIEW HELP

FIG. 4B


7/48

**FIG. 5A**


8/48

**FIG. 5B**

9/48

**FIG. 5C**

10/48

**FIG. 5D**

11/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE

1. VIEW NAME: NEW VIEW 1

2. SOURCE FILES 3. FORMAT 4. PREPARATION 5. PROCESSING 6. CLUSTERING 7. PROJECTION 610

FORMAT FILE:

/HOME/BATTELLE/OMNIVIZ_DATA/FORMATS/MEDLINE31.FMT

SELECT... 620 VIEW... 622

STOPWORDS FILE:

/HOME/BATTELLE/OMNIVIZ_DATA/STOPWORDS/DEFAULTTEXT.STOP

SELECT... VIEW...

PUNCTUATION FILE:

/HOME/BATTELLE/OMNIVIZ_DATA/PUNC/DEFAULT.PUNC

SELECT... VIEW...

CANCEL << PREVIOUS NEXT >> PROCESS LATER PROCESS NOW HELP

FIG. 6A




FIG. 6B

13/48

NEW VISUAL ANALYSIS: GE.775

1. VIEW NAME: NEW VIEW

2. SOURCE FILES 3. FORMAT 4. PREPARATION 5. PROCESSING 6. CLUSTERING 7. PROJECTION

4.1 DATA SPECIFICATION 4.2 OPERATION SET 4.3 CLUSTERING SELECTION — 650

☐ 640 ☐ TRANPOSE DATA FILES

RECORD TITLE COLUMNS: 0

FIELD NAME	COLUMN(S)	DATA TYPE
NUMERIC FIELD NAME1	1-3	NUMERIC
CATEGORICAL FIELD NAME2	11-12	CATEGORICAL
SEQUENCE	10	SEQUENCE
TEXT FIELD NAME2	4-5	TEXT

☒ USE SINGLE COLUMN HEADING FOR FIELD NAMES

FIG. 6C

14/48

NEW VISUAL ANALYSIS: GE.775

1. VIEW NAME: NEWVIEW

2. SOURCE FILES 3. FORMAT 4. PREPARATION 5. PROCESSING 6. CLUSTERING 7. PROJECTION

4.1 DATA SPECIFICATION 4.2 OPERATION SET 643 4.3 CLUSTERING SELECTION

OPERATION SET NAME	NUMERIC FIELD	OPERATIONS
OPERATION SET1	NUMERIC FIELD NAME	RECIPROCAL LOG(10)
OPERATION SET2		NEW OPERATION SET REMOVE OPERATION SET

644

ADD OP REMOVE OP

AVAILABLE OPERATIONS 645

LOG(10)
IN
LOG(2)
ANTILOG(10)
ANTILOG(2)
ANTIIN

CURRENT OPERATION SEQUENCE 646

RECIPROCAL LOG(10)

CANCEL << PREVIOUS NEXT >> PROCESS LATER PROCESS NOW HELP

FIG. 6D

15/48

NEW VISUAL ANALYSIS: GE.775

1. VIEW NAME: NEW VIEW

2. SOURCE FILES

3. FORMAT

4. PREPARATION

5. PROCESSING

6. CLUSTERING

7. PROJECTION

4.1 DATA SPECIFICATION

4.2 OPERATION SET

4.3 CLUSTERING SELECTION

650

PLEASE SELECT WHICH FIELD/TRANSFORM ON WHICH TO CLUSTER

OPERATION SET1

OPERATION SET1

NUMERIC FIELD NAME1

CANCEL

<< PREVIOUS

NEXT >>

PROCESS LATER

PROCESS NOW

HELP

FIG. 6E

16/48

NEW VISUAL ANALYSIS: YEAST CELL CYCLE

1. VIEW NAME:

2. SOURCE FILES 3. FORMAT 4. PREPARATION 5. PROCESSING 6. CLUSTERING 7. PROJECTION

4.1 MOTIFS NGRAMS 4.2 COMPLEXITY FILTERING 4.3 EXCLUSIONS 4.4 AMINO ACID SUBSTITUTIONS

MOTIF PARAMETERS

☒ SINGLE MOTIF OUTPUT

MOTIF PATTERN FILES

ADD DELETE

NGRAM LENGTHS/MINIMUM FREQUENCIES

<input type="checkbox"/> 1	<input type="checkbox"/> 6	<input type="checkbox"/> 1	<input type="checkbox"/> 1
<input type="checkbox"/> 2	<input type="checkbox"/> 7	<input type="checkbox"/> 1	<input type="checkbox"/> 1
<input type="checkbox"/> 3	<input type="checkbox"/> 8	<input type="checkbox"/> 1	<input type="checkbox"/> 1
<input type="checkbox"/> 4	<input type="checkbox"/> 9	<input type="checkbox"/> 1	<input type="checkbox"/> 1
<input type="checkbox"/> 5	<input type="checkbox"/> 10	<input type="checkbox"/> 1	<input type="checkbox"/> 1

CANCEL << PREVIOUS NEXT >> PROCESS LATER PROCESS NOW HELP

FIG. 6F

17/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE

1. VIEW NAME: NEW VIEW 1

2. SOURCE FILES

3. FORMAT

4. PREPARATION

5. PROCESSING

6. CLUSTERING

7. PROJECTION

TOPICALITY METHOD: SPECIFY SETTINGS BY NUMBER OF TERMS

0.20

WEAK

0.00

1.00

STRICT

DO NOT USE ASSOCIATIONS

REQUESTED NUMBER OF TOPICS: 200

REQUESTED NUMBER OF CROSS TERMS: 2000

TOPICS MUST APPEAR IN 20 BUT NO MORE THAN RECORDS.

CROSS TERMS MUST APPEAR IN 20 BUT NO MORE THAN RECORDS.

CANCEL

<< PREVIOUS

NEXT >>

PROCESS LATER

PROCESS NOW

HELP

FIG. 6G

18/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE

1. VIEW NAME: NEW VIEW 1

2 SOURCE FILES
3 FORMAT
4 PREPARATION
5. PROCESSING
6 CLUSTERING
7 PROJECTION

TOPICALITY METHOD: SPECIFY SETTINGS BY THRESHOLD

WEAK

0.00

680

0.20

STRICT

1.00

DO NOT USE ASSOCIATIONS

MINIMUM TOPICALITY FOR TOPICS:

0.00

682

2.60

10.00

MINIMUM TOPICALITY FOR CROSS TERMS:

0.00

684

1.80

10.00

TOPICS MUST APPEAR IN

20

686a

BUT NO MORE THAN

RECORDS.

686b

CROSS TERMS MUST APPEAR IN

20

688a

BUT NO MORE THAN

RECORDS.

688b

CANCEL

<< PREVIOUS

NEXT >>

PROCESS LATER

PROCESS NOW

HELP

FIG. 6H

19/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE

1. VIEW NAME: NEW VIEW 1

2. SOURCE FILES
3. FORMAT
4. PREPARATION
5. PROCESSING
6. CLUSTERING
7. PROJECTION

TOPICALITY METHOD: AUTOMATICALLY CALCULATE SETTINGS

WEAK

0.00

0.20

1.00

STRICT

☐ DO NOT USE ASSOCIATIONS

CANCEL

<< PREVIOUS

NEXT >>

PROCESS LATER

PROCESS NOW

HELP

FIG. 6I

20/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE

1. VIEW NAME: NEW VIEW 1

2. SOURCE FILES
3. FORMAT
4. PREPARATION
5. PROCESSING
6. CLUSTERING
7. PROJECTION

TOPICALITY METHOD: AUTOMATICALLY CALCULATE SETTINGS, WITH EMPHASIS ON LOCAL TOPICS

WEAK

0.00

0.20

1.00

STRICT

☐ DO NOT USE ASSOCIATIONS

CANCEL

<< PREVIOUS

NEXT >>

PROCESS LATER

PROCESS NOW

HELP

FIG. 6J

21/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE

1. VIEW NAME: NEW VIEW 1

2. SOURCE FILES

3. FORMAT

4. PREPARATION

5. PROCESSING

6. CLUSTERING

7. PROJECTION

CLUSTERING METHOD: HIERARCHICAL

☐ COMPUTE CLUSTERS BASED ON COHERENCE

NUMBER OF CLUSTERS:

50

1

500

CLUSTER COHERENCE:

70

0

99

☒ CORRELATION ORDER AFTER CLUSTERING

CANCEL

<< PREVIOUS

NEXT >>

PROCESS LATER

PROCESS NOW

HELP

FIG. 6K

22/48

NEW VISUAL ANALYSIS: APOPTOSIS.DISEASE	
1. VIEW NAME: NEW VIEW 1	
2. SOURCE FILES 3. FORMAT 4. PREPARATION 5. PROCESSING 6. CLUSTERING 7. PROJECTION	
CLUSTERING METHOD: KMEANS	
NUMBER OF CLUSTERS:	50
NUMBER OF ITERATIONS:	500
CLUSTER SEEDING:	
<input checked="" type="radio"/> USE RANDOM SEEDING <input type="radio"/> USE DIMENSIONAL SEEDING <input type="checkbox"/> USE SYSTEM TIME TO SEED RANDOM NUMBER GENERATOR RANDOM GENERATOR SEED:	
<input checked="" type="checkbox"/> CORRELATION ORDER AFTER CLUSTERING	
CANCEL	<< PREVIOUS NEXT >> PROCESS LATER PROCESS NOW HELP



FIG. 6L



23/48

NEW VISUAL ANALYSIS: APOPTOSIS DISEASE

1. VIEW NAME:

2. SOURCE FILES **3. FORMAT** **4. PREPARATION** **5. PROCESSING** **6. CLUSTERING** **7. PROJECTION**

CLUSTER COHESION:   3.5 5.0

CLUSTER AREA:   0.0 10.0




CLUSTER SPREAD:   1.0 20.0

FIG. 6M

24/48

**FIG. 7A**




FIG. 7B

26/48

```

NAME=SPROT-ANO
DESC=SWISSPROT ANNOTATIONS
END_DESC
DELIMITER=//

;CORPUS NAME
;CORPUS DESCRIPTION
;RECORD DELIMITER TAG

;FIELD NUMBER
;NAME OF THE FIELD
;DATA TYPE OF THIS FIELD (STRING, NUMERIC, SEQUENCE)
;FIELD TAG AS IT APPEARS IN THE SOURCE FILE
;DATA IS ON A SINGLE LINE
;DON'T USE THIS FIELD FOR THE DOCUMENT VECTOR
;MAKE THIS FIELD SEARCHABLE
;USE THIS FIELD TO MAKE CATEGORIES
;CASE SENSITIVE
;THE TITLE TAG MUST BE A WORD (WHITE SPACE DELIMITED)
;THE FIELD TAG ALWAYS STARTS AT THE BEGINNING OF A LINE

IIFO
NAME=TITLE
TYPE=STRING
TAG=DE
METHOD=LINES:1
DOC_VECTOR=FALSE
SEARCH=TRUE
CORR=TRUE
CASE_SENSITIVE=TRUE
WHOLE_BOUNDARY=TRUE
LINEPOS=START
IIF1
...
IIF...

```

804

FIG. 8

27/48




FIG. 9

28/48




FIG. 10


CREATE READ UPDATE

29/48


FILE NAME	SET UP		PROCESSING PROGRAMS								INTERACTIVE TOOLS AND GRAPHICS								
			VECTOR CREATE				CLUSTER												
	DATASET EDITOR	VIEW EDITOR	NUMERIC_ENGINE	TEXT_ENGINE	K_MEANS	CLUSTER_SID	CORRELATIONORDER	PCA_CLUSTERS	TRIANGLE	DOCPROJECTION	GALAXY	SURFACE MAP	MASTER QUERY	PLOT DATA	RECORD VIEWER	QUERY (WORD)	QUERY (NUM)	GROUP	GIST
<DATASETNAME>.DCAT	C														R				
<DATASETNAME>.PROPERTIES	C										R								
<VIEWNAME>.CLSP		C			R	R				R									
<VIEWNAME>.CLUSTER							C		C										
<VIEWNAME>.CORRV				C									R						
<VIEWNAME>.DCAT				C											R				
<VIEWNAME>.DOCP									C	R									
<VIEWNAME>.DOCTERM				C												R			R
<VIEWNAME>.DOCTERM_INDEX				C												R			R
<VIEWNAME>.DOCV (VECTOR)				C	R	R	R			R	R	R		R			R		
<VIEWNAME>.EDGE									C	R									
<VIEWNAME>.FIELD_OFF				C									R	R	R	R			
<VIEWNAME>.GIF			C								R								
<VIEWNAME>.GROUPS																		U	
<VIEWNAME>.FMT			C	R									R	R	R	R	R		
<VIEWNAME>.HCLS					C	C	R			R	R	R	R		R				
<VIEWNAME>.HEADINGS			C								R	R		R			R		
<VIEWNAME>.IFI				C												R			
<VIEWNAME>.IFI_INDEX				C												R			
<VIEWNAME>.PROPERTIES	U	U	U	U	U	U	U	U	U	U	R	R							
<VIEWNAME>.PUNC			C	R												R	R		
<VIEWNAME>.REL				C													R		
<VIEWNAME>.REPOSITORY											R	R	R	R	R	R	R	R	R
<VIEWNAME>.STOP			C	R													R		
<VIEWNAME>.TL				C							R	R	R	R	R	R			
<VIEWNAME>.TOPIC				C													R		
<VIEWNAME>.VOCAB				C												R			R
<VIEWNAME>.VOCAB_INDEX				C												R			R
TAB DELIMITED COLUMN/ROW SOURCE			R																
TAGGED TEXT SOURCE FILE(S)			C	R											R				
REENGINEERED TAGGED TEXT SOURCE		C	R	R											R				


FIG. 11

30/48

**FIG. 12**


31/48

**FIG. 13**



33/48

FIG. 15







FIG. 16

**FIG. 17**

36/48




FIG. 18

37/48





FIG. 19

38/48

**FIG. 20**

39/48




FIG. 21

40/48

RECORDS VS. ATTRIBUTES

☒ VOCABULARY WORD(S)

☐ VOCABULARY FILE

☐ CATEGORY FIELD(S)

☐ CATEGORY FILE

ATTRIBUTE SOURCES

2210 2220

TYPE IN WORDS, SEPARATED BY SEMICOLON

BROWSE

ADD

BROWSE

2240 2230

2250

DROP DOWN LIST OF FIELDS

CLEAR CANCEL DONE

FIG. 22A

SUBSTITUTE SHEET (RULE 26)

VSDOCID: <WO

0124060A2 1A>

ATTRIBUTES VS. ATTRIBUTES

ROW ATTRIBUTE

☒ VOCABULARY WORD(S)

☐ VOCABULARY FILE

☐ CATEGORY FIELD(S)

☐ CATEGORY FILE

TYPE IN WORDS, SEPARATED BY

BROWSE

ADD

BROWSE

DROP DOWN LIST OF FIELDS

COLUMN ATTRIBUTE

☒ VOCABULARY WORD

☐ VOCABULARY FILE

☐ CATEGORY FIELD

☐ CATEGORY FILE

TYPE IN WORDS, SEPARATED BY

BROWSE

ADD

BROWSE

DROP DOWN LIST OF FIELDS

CLEAR

CANCEL

DONE

2260

FIG. 22B

CURRENT DATA VS HISTORICAL DATA

☒ PREVIOUS VISUALIZATION

☐ DATA MATRIX FILE(S)

BROWSE

BROWSE

HISTORICAL DATA FOR COMPARISON

CLEAR

CANCEL

DONE

2270

FIG. 22C

43/48

	ATTRIBUTE_1	ATTRIBUTE_2	ATTRIBUTE_3	ATTRIBUTE_4	ATTRIBUTE_5	ATTRIBUTE_6
RECORD_1	1	1	1	1	0	0
RECORD_2	0	1	1	1	1	0
RECORD_3	0	1	1	1	0	0
RECORD_4	1	0	1	1	0	0
RECORD_5	1	1	1	0	1	1
RECORD_6	0	1	0	1	0	0

FIG. 23

44/48

	ATTRIBUTE1	ATTRIBUTE2	ATTRIBUTE3	ATTRIBUTE4	ATTRIBUTE5	ATTRIBUTE6
RECORD_1						
RECORD_2						
RECORD_3						
RECORD_4						
RECORD_5						
RECORD_6						

FIG. 24

	ATTRIBUTE1	ATTRIBUTE2	ATTRIBUTE3	ATTRIBUTE4	ATTRIBUTE5	ATTRIBUTE6
CLUSTER_1						
CLUSTER_2						
CLUSTER_3						

FIG. 25

45/48




FIG. 26





FIG. 27


46/48

**FIG. 28**



SUBSTITUTE SHEET (RULE 26)

47/48

TOOL BAR

**FIG. 29**

48/48

**FIG. 30A****FIG. 30B**

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/024060 A3

(51) International Patent Classification⁷: **G06F 17/30**

(21) International Application Number: PCT/US00/26964

(22) International Filing Date:
29 September 2000 (29.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/410,367 30 September 1999 (30.09.1999) US

(71) Applicant: **BATTELLE MEMORIAL INSTITUTE**
[US/US]; 505 King Avenue, Columbus, OH 43201-2693 (US).

(72) Inventors: **SAFFER, Jeffrey, D.**; 202 Hartwood Street, Richland, WA 99352 (US). **CALAPRISTI, Augustin, J.**; 3104 Mount Granite Court W., Richland, WA 99353 (US). **MILLER, Nancy, E.**; 4919 Brookburn Drive, San Diego, CA 92130 (US). **SCARBERRY, Randall, E.**; 2224 Benton Avenue, Richland, WA 99352 (US). **THURSTON, Sarah, J.**; 221 Douglass Avenue, Richland, WA 99352 (US). **HAVRE, Susan, L.**; 300 Rockwood Drive, Richland, WA 99352 (US). **DECKER, Scott, D.**; 1309 Buena Court, Richland, WA 99352 (US). **PAYNE, Deborah, A.**; 1968 Newhaven Loop, Richland, WA 99352 (US). **SOFIA, Heidi, J.**; 383 S. Palouse, Walla Walla, WA 99362 (US). **THOMAS, Gregory, S.**; 93006 East Reata Road, Kennewick, WA 99338 (US). **CHEN, Guang**; 1329 Goethals Drive, Apt. 9, Richland, WA 99352 (US). **CROW, Vernon, L.**; 415 South Grant, Kennewick, WA 99336 (US). **ALBRIGHT, Cory, L.**; 1110 McPherson, Richland, WA 99352 (US). **ZABRISKI, Sean, J.**; 8943 W. Canyon Place, Richland, WA 99352 (US). **GROCH, Kevin, M.**; 2433 George Washington Way, Suite 6105,

Richland, WA 99352 (US). **MALARD, Joel, M.**; 1312 Rochefontaine, Richland, WA 99352 (US). **NOWELL, Lucille, T.**; 40 Edgewood Drive, Richland, WA 99352 (US).

(74) Agents: **GOLDSTEIN, Steven, J.** et al.; Frost Brown Todd LLC, 2500 PNC Center, 201 East Fifth Street, Cincinnati, OH 45202 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

(88) Date of publication of the international search report:
17 April 2003

(15) Information about Correction:
Previous Correction:
see PCT Gazette No. 49/2002 of 5 December 2002, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DATA PROCESSING, ANALYSIS, AND VISUALIZATION SYSTEM FOR USE WITH DISPARATE DATA TYPES

(57) Abstract: A system or method consistent with an embodiment of the present invention is useful in analyzing large volumes of different types of data, such as textual data, numeric data, categorical data, or sequential string data, for use in identifying relationships among the data types or different operations that have been performed on the data. A system or method consistent with the present invention determines and displays the relative content and context of related information and is operative to aid in identifying relationships among disparate data types. Various data types, such as numerical data, protein and DNA sequence data, categorical information, and textual information, such as annotations associated with the numerical data or research papers may be correlated for visual analysis. A variety of user-selectable views may be correlated for user interaction to identify relationships that exist among the different types of data or various operations performed on the data. Furthermore, the user may explore the information contained in sets of records and their associated attributes through the use of interactive 2-D line charts and interactive summary miniplots.

WO 01/024060 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/26964

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06F17/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 92 11602 A (DAVID SARNOFF RESEARCH) 9 July 1992 (1992-07-09) page 6, line 1 -page 7, line 34; figure 2 ---	1
A	US 5 261 093 A (ASMUTH) 9 November 1993 (1993-11-09) column 2, line 22 - line 65 ---	1
A	WO 99 27495 A (PORTOLA DIMENSIONAL SYSTEMS) 3 June 1999 (1999-06-03) page 10, paragraph 4 -page 13, paragraph 2; figures 3-5 -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

11 March 2002

Date of mailing of the international search report

12 08. 2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

GILL, S

INTERNATIONAL SEARCH REPORT

international application No.
PCT/US 00/26964

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claim : 1

Method of analyzing data types according to selected attributes

2. Claims: 2-15,19

A method of analyzing data types using a uniform data structure

3. Claims: 16-18, 20-44

A method of identifying relationships between visualizations of data sets

4. Claims: 45-62

Method of visualizing multiple queries to a database

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/26964

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9211602 A	09-07-1992	US 5257349 A	26-10-1993
		DE 69130509 D	24-12-1998
		DE 69130509 T	22-04-1999
		EP 0563190 A	06-10-1993
		JP 6503667 T	21-04-1994

US 5261093 A	09-11-1993	NONE	

WO 9927495 A	03-06-1999	US 6188403 B	13-02-2001
		AU 5915598 A	15-06-1999
		EP 1038270 A	27-09-2000
		US 6222540 B	24-04-2001
